

# Admin REST API

- User
  - Get user authentication status
  - Create user with KAA\_ADMIN role
  - Change user password
  - Get user profile
  - Edit user profile
  - Get all users
  - Get user
  - Create/Edit user
  - Delete user
- Tenant
  - Get all tenants
  - Get tenant
  - Create/Edit tenant
  - Delete tenant
- Application
  - Get all applications
  - Get application
  - Create/Edit application
  - Delete application
- SDK generation
  - Get versions of all schema types
  - Generate endpoint SDK
- Profiling
  - Get profile schemas
  - Get profile schema
  - Create profile schema
- Grouping
  - Get endpoint groups
  - Get endpoint group
  - Create/Edit endpoint group
  - Delete endpoint group
  - Get profile filter records
  - Get profile filter record
  - Get vacant profile schemas
  - Create/Edit profile filter
  - Activate profile filter
  - Deactivate profile filter
  - Delete profile filter record
- Configuration
  - Get configuration schemas
  - Get configuration schema
  - Create configuration schema
  - Get configuration records
  - Get configuration record
  - Get vacant configuration schemas
  - Create/Edit configuration
  - Activate configuration
  - Deactivate configuration
  - Delete configuration record
- Notifications
  - Get notification schemas
  - Get user notification schemas
  - Get notification schema
  - Create notification schema
  - Get topics
  - Get endpoint group topics
  - Get vacant topics
  - Get topic
  - Create/Edit topic
  - Delete topic
  - Add topic to endpoint group
  - Remove topic from endpoint group
  - Send notification
- Events
  - Get event class families
  - Get event class family
  - Create/Edit event class family
  - Add event class family schema
  - Get event classes
  - Get application event family maps
  - Get application event family map
  - Create/Edit application event family map
  - Get vacant event class families
  - Get application event class families

- [Logging](#)
  - [Get log schemas](#)
  - [Get log schema](#)
  - [Get log schema by application token and schema version](#)
  - [Create log schema](#)
  - [Get log appenders](#)
  - [Get log appender](#)
  - [Create/Edit log appender](#)
  - [Delete log appender](#)

## User

### Get user authentication status

Returns information about the current authorized user.

- **URL**  
/kaaAdmin/rest/api/auth/checkAuth
- **Method:**  
GET
- **URL params**  
None
- **Data params**  
None
- **Success response:**

- **Code:** 200
  - **Example:**

```
{
  "authResult": "OK",
  "authority": "TENANT_DEVELOPER",
  "displayName": "devuser (Tenant Developer)",
  "username": "devuser"
}
```

- **Error response:**

Status codes	Description
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -u devuser:devuser123 -X GET "http://localhost:8080/kaaAdmin/rest/api/auth/checkAuth" | python -m json.tool
```

```
{
  "authResult": "OK",
  "authority": "TENANT_DEVELOPER",
  "displayName": "devuser (Tenant Developer)",
  "username": "devuser"
}
```

### Create user with KAA\_ADMIN role

Creates a user with the KAA\_ADMIN role.

- **URL**  
/kaaAdmin/rest/api/auth/createKaaAdmin?username&password

- **Method:**  
POST

- **URL params**

Parameter	Value	Description
username	string	user name of Kaa admin user
password	string	user password of Kaa admin user, must be no shorter than 6 characters

- **Data params**

None

- **Success response:**

- **Code:** 200

- **Error response:**

Status codes	Description
403 Forbidden	User with the KAA_ADMIN role already exists
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -X POST "http://localhost:8080/kaaAdmin/rest/api/auth/createKaaAdmin?username=kaa&password=kaa" | python -mjson.tool
```

## Change user password

Changes the password of a user.

- **URL**  
/kaaAdmin/rest/api/auth/changePassword?username&oldPassword&newPassword

- **Method:**  
POST

- **URL params**

Parameter	Value	Description
username	string	user name of the user whose password is to be changed
oldPassword	string	old password of the user
newPassword	string	new password of the user, must be no shorter than 6 characters

- **Data params**

None

- **Success response:**

- **Code:** 200
  - **Example:**

```
"OK"
```

- **Error response:**

Status codes	Description
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u devuser:devuser123 -X POST "http://localhost:8080/kaaAdmin/rest/api/auth/changePassword?username=devuser&oldPassword=devuser123&newPassword=devuser12345" | python -mjson.tool
```

```
"OK"
```

## Get user profile

Returns the user profile of the current user. Only authorized users are allowed to perform this operation.

- **URL**  
/kaaAdmin/rest/api/userProfile

- **Method:**  
GET

- **URL params**

None

- **Data params**

None

- **Success response:**

- **Code:** 200
  - **Example:**

```
{
  "authority": "TENANT_DEVELOPER",
  "externalUid": "3",
  "firstName": "Tenant",
  "id": null,
  "lastName": "Developer",
  "mail": "devuser@demoproject.org",
  "tempPassword": null,
  "tenantId": null,
  "username": "devuser"
}
```

- **Error response:**

Status codes	Description
401 Unauthorized	User is not authenticated or invalid credentials provided
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u devuser:devuser123 -X GET "http://localhost:8080/kaaAdmin/rest/api/userProfile" | python -mjson.tool
```

```
{
  "authority": "TENANT_DEVELOPER",
  "externalUid": "3",
  "firstName": "Tenant",
  "id": null,
  "lastName": "Developer",
  "mail": "devuser@demoproject.org",
  "tempPassword": null,
  "tenantId": null,
  "username": "devuser"
}
```

## Edit user profile

Edits the user profile. Only authorized users are allowed to perform this operation.

- **URL**  
/kaaAdmin/rest/api/userProfile

- **Method:**  
POST

- **URL params**  
None

- **Data params**

**Example:**

```
{ "username": "devuser", "firstName": "Dow", "lastName": "Jones", "mail": "jones@demoproject.org", "authority": "TENANT_DEVELOPER" }
```

- **Success response:**

- **Code:** 200
- **Example:**

```
{
  "authority": "TENANT_DEVELOPER",
  "externalUid": "3",
  "firstName": "Dow",
  "id": null,
  "lastName": "Jones",
  "mail": "jones@demoproject.org",
  "tempPassword": null,
  "tenantId": null,
  "username": "devuser"
}
```

- **Error response:**

Status codes	Description
401 Unauthorized	User is not authenticated or invalid credentials provided
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u devuser:devuser123 -X POST -H 'Content-Type: application/json' -d '{"username": "devuser", "firstName": "Dow", "lastName": "Jones", "mail": "jones@demoproject.org", "authority": "TENANT_DEVELOPER"}' "http://localhost:8080/kaaAdmin/rest/api/userProfile" | python -mjson.tool
```

```
{
  "authority": "TENANT_DEVELOPER",
  "externalUid": "3",
  "firstName": "Dow",
  "id": null,
  "lastName": "Jones",
  "mail": "jones@demoproject.org",
  "tempPassword": null,
  "tenantId": null,
  "username": "devuser"
}
```

## Get all users

Returns a list of all users associated with the current authorized user: users whose Tenant ID values match the Tenant ID of the request submitter. Only users with the TENANT\_ADMIN role are allowed to submit this request.

- **URL**  
/kaaAdmin/rest/api/users

- **Method:**

GET

- **URL params**

None

- **Data params**

None

- **Success response:**

- **Code:** 200
  - **Example:**

```
[
  {
    "authority": "TENANT_DEVELOPER",
    "externalUid": "3",
    "firstName": "Dow",
    "id": "21",
    "lastName": "Jones",
    "mail": "jones@demoproject.org",
    "tempPassword": null,
    "tenantId": "10",
    "username": "devuser"
  }
]
```

- **Error response:**

Status codes	Description
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_ADMIN)
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u admin:admin123 -X GET "http://localhost:8080/kaaAdmin/rest/api/users" | python -mjson.tool
```

```
[
  {
    "authority": "TENANT_DEVELOPER",
    "externalUid": "3",
    "firstName": "Dow",
    "id": "21",
    "lastName": "Jones",
    "mail": "jones@demoproject.org",
    "tempPassword": null,
    "tenantId": "10",
    "username": "devuser"
  }
]
```

## Get user

Returns a user. Only users with the TENANT\_ADMIN role are allowed to submit this request. The Tenant ID of requested user must be identical to the Tenant ID of the submitter.

- **URL**  
/kaaAdmin/rest/api/user/{userId}

- **Method:**  
GET

- **URL params**

Parameter	Value	Description
userId	string	User ID of the requested user.

- **Data params**

None

- **Success response:**

- **Code: 200**
  - **Example:**

```
{
  "authority": "TENANT_DEVELOPER",
  "externalUid": "3",
  "firstName": "Dow",
  "id": "21",
  "lastName": "Jones",
  "mail": "jones@demoproject.org",
  "tempPassword": null,
  "tenantId": "10",
  "username": "devuser"
}
```

- **Error response:**

Status codes	Description
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_ADMIN) or the Tenant ID of the requested user does not match the Tenant ID of the authenticated user
404 Not Found	User with the specified userId does not exist

500 Internal Server Error

Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u admin:admin123 -X GET "http://localhost:8080/kaaAdmin/rest/api/user/21" | python -mjson.tool
```

```
{
  "authority": "TENANT_DEVELOPER",
  "externalUid": "3",
  "firstName": "Dow",
  "id": "21",
  "lastName": "Jones",
  "mail": "jones@demoproject.org",
  "tempPassword": null,
  "tenantId": "10",
  "username": "devuser"
}
```

## Create/Edit user

Creates or edits a user. If a user with the specified ID does not exist, it will be created, and its Tenant ID will be set to the Tenant ID of the request submitter. A random password will be generated and sent to the user's Email. If a user with the specified ID exists, the user will be updated. Only users with the TENANT\_ADMIN role can perform this operation.

- **URL**

/kaaAdmin/rest/api/application

- **Method:**

POST

- **URL params**

None

- **Data params**

**Example:**

```
{"username": "chucknorris", "firstName": "Chuck", "lastName": "Norris", "mail": "norris@demoproject.org", "authority": "TENANT_USER"}
```

- **Success response:**

- **Code: 200**

- **Example:**

```
{
  "authority": "TENANT_USER",
  "externalUid": "5",
  "firstName": "Chuck",
  "id": "211",
  "lastName": "Norris",
  "mail": "norris@demoproject.org",
  "tempPassword": "rmOZgpwlmorE",
  "tenantId": "10",
  "username": "chucknorris"
}
```

- **Error response:**

Status codes	Description
--------------	-------------



401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_ADMIN) or the Tenant ID of the editing user does not match the Tenant ID of the authenticated user
404 Not Found	User to be edited with the specified userId does not exist
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u admin:admin123 -X POST -H 'Content-Type: application/json' -d '{"username": "chucknorris", "firstName": "Chuck", "lastName": "Norris", "mail": "norris@demoproject.org", "authority": "TENANT_USER"}' "http://localhost:8080/kaaAdmin/rest/api/user" | python -mjson.tool
```

```
{
  "authority": "TENANT_USER",
  "externalUid": "5",
  "firstName": "Chuck",
  "id": "211",
  "lastName": "Norris",
  "mail": "norris@demoproject.org",
  "tempPassword": "rmOZgpwlmorE",
  "tenantId": "10",
  "username": "chucknorris"
}
```

## Delete user

Deletes a user. Only users with the TENANT\_ADMIN role can perform this operation. The Tenant ID of the user to be deleted must be identical to the Tenant ID of the user who submitted the request.

- **URL**  
/kaaAdmin/rest/api/delUser?userId

- **Method:**  
POST

- **URL params**

Parameter	Value	Description
userId	string	the User ID of the user to be deleted.

- **Data params**

None

- **Success response:**

- **Code:** 200

- **Error response:**

Status codes	Description
400 Bad Request	userId parameter is empty
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_ADMIN) or the Tenant ID of the user to be deleted does not match the Tenant ID of the authenticated user
404 Not Found	User with the specified userId does not exist

500 Internal Server Error

Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u admin:admin123 -X POST "http://localhost:8080/kaaAdmin/rest/api/delUser?userId=211" | python -mjson.tool
```

## Tenant

### Get all tenants

Returns all tenants existing in the system. Only Kaa admin is allowed to submit this request.

- **URL**  
/kaaAdmin/rest/api/tenants

- **Method:**  
GET

- **URL params**  
None

- **Data params**  
None

- **Success response:**

- **Code: 200**
  - **Example:**

```
[  
  {  
    "authority": "TENANT_ADMIN",  
    "externalUid": "2",  
    "firstName": "Tenant",  
    "id": "20",  
    "lastName": "Admin",  
    "mail": "admin@demoproject.org",  
    "tempPassword": null,  
    "tenantId": "10",  
    "tenantName": "Demo Tenant",  
    "username": "admin"  
  }  
]
```

- **Error response:**

Status codes	Description
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the KAA_ADMIN role
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u kaa:kaa123 -X GET "http://localhost:8080/kaaAdmin/rest/api/tenants" | python -mjson.tool
```

```
[
  {
    "authority": "TENANT_ADMIN",
    "externalUid": "2",
    "firstName": "Tenant",
    "id": "20",
    "lastName": "Admin",
    "mail": "admin@demoproject.org",
    "tempPassword": null,
    "tenantId": "10",
    "tenantName": "Demo Tenant",
    "username": "admin"
  }
]
```

## Get tenant

Returns tenant by associated userId.

- **URL**  
/kaaAdmin/rest/api/tenant/{userId}

- **Method:**

GET

- **URL params**

Parameter	Value	Description
userId	string	the ID of the user associated with the requested tenant

- **Data params**

None

- **Success response:**

- **Code: 200**
  - **Example:**

```
{
  "authority": "TENANT_ADMIN",
  "externalUid": "2",
  "firstName": "Tenant",
  "id": "20",
  "lastName": "Admin",
  "mail": "admin@demoproject.org",
  "tempPassword": null,
  "tenantId": "10",
  "tenantName": "Demo Tenant",
  "username": "admin"
}
```

- **Error response:**

Status codes	Description
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the KAA_ADMIN role
404 Not Found	Tenant with the specified userId does not exist
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u kaa:kaa123 -X GET "http://localhost:8080/kaaAdmin/rest/api/tenant/20" | python -mjson.tool
```

```
{
  "authority": "TENANT_ADMIN",
  "externalUid": "2",
  "firstName": "Tenant",
  "id": "20",
  "lastName": "Admin",
  "mail": "admin@demoproject.org",
  "tempPassword": null,
  "tenantId": "10",
  "tenantName": "Demo Tenant",
  "username": "admin"
}
```

## Create/Edit tenant

Creates or edits a tenant. If a tenant with the specified ID does not exist, it will be created. If a tenant with the specified ID exists, it will be updated.

- **URL**  
/kaaAdmin/rest/api/tenant
- **Method:**  
POST
- **URL params**  
None

- **Data params**

**Example:**

```
{"tenantName":"Demo Tenant 2","username":"admin2","authority":"TENANT_ADMIN","mail":"admin2@demoproject.org"}
```

- **Success response:**

- **Code:** 200
- **Example:**

```
{
  "authority": "TENANT_ADMIN",
  "externalUid": "4",
  "firstName": null,
  "id": "210",
  "lastName": null,
  "mail": "admin2@demoproject.org",
  "tempPassword": "at281c23Nhxm",
  "tenantId": "200",
  "tenantName": "Demo Tenant 2",
  "username": "admin2"
}
```

- **Error response:**

Status codes	Description
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the KAA_ADMIN role
404 Not Found	Tenant with the specified userId does not exist

500 Internal Server Error	Unexpected error occurred on the server side
---------------------------	--

- **Sample call:**

```
curl -v -S -u kaa:kaa123 -X POST -H 'Content-Type: application/json' -d '{"tenantName": "Demo Tenant 2", "username": "admin2", "authority": "TENANT_ADMIN", "mail": "admin2@demoproject.org"}' "http://localhost:8080/kaaAdmin/rest/api/tenant" | python -mjson.tool
```

```
{
  "authority": "TENANT_ADMIN",
  "externalUid": "4",
  "firstName": null,
  "id": "210",
  "lastName": null,
  "mail": "admin2@demoproject.org",
  "tempPassword": "at281c23Nhxm",
  "tenantId": "200",
  "tenantName": "Demo Tenant 2",
  "username": "admin2"
}
```

## Delete tenant

Deletes a tenant by associated User ID.

- **URL**

/kaaAdmin/rest/api/delTenant?userId

- **Method:**

POST

- **URL params**

Parameter	Value	Description
userId	string	the ID of the user associated with the tenant to be deleted

- **Data params**

None

- **Success response:**

- **Code:** 200

- **Error response:**

Status codes	Description
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the KAA_ADMIN role
404 Not Found	Tenant with the specified userId does not exist
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u kaa:kaa123 -X POST "http://localhost:8080/kaaAdmin/rest/api/delTenant?userId=210" | python -mjson.tool
```

## Application

## Get all applications

Returns all applications for the current authorized user within the current tenant. The current user must have one of the following roles: TENANT\_ADMIN, TENANT\_DEVELOPER, or TENANT\_USER.

- **URL**  
/kaaAdmin/rest/api/applications

- **Method:**  
GET

- **URL params**  
None

- **Data params**  
None

- **Success response:**

- **Code: 200**
  - **Example:**

```
[
  {
    "applicationToken": "358849227911747",
    "id": "70",
    "logAppendersNames": "mongoDBLogAppender,fileSystemLogAppender",
    "name": "Player",
    "publicKey": null,
    "sequenceNumber": 2,
    "tenantId": "10",
    "userVerifierName": "dummyEndpointUserVerifier"
  },
  {
    "applicationToken": "989414255707149",
    "id": "71",
    "logAppendersNames": "mongoDBLogAppender,fileSystemLogAppender",
    "name": "Smart House",
    "publicKey": null,
    "sequenceNumber": 2,
    "tenantId": "10",
    "userVerifierName": "dummyEndpointUserVerifier"
  },
  {
    "applicationToken": "561087972707255",
    "id": "72",
    "logAppendersNames": "mongoDBLogAppender,fileSystemLogAppender",
    "name": "Test Flume Appender",
    "publicKey": "",
    "sequenceNumber": 2,
    "tenantId": "10",
    "userVerifierName": "dummyEndpointUserVerifier"
  }
]
```

- **Error response:**

Status codes	Description
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_ADMIN, TENANT_DEVELOPER, or TENANT_USER)
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u devuser:devuser123 -X GET "http://localhost:8080/kaaAdmin/rest/api/applications" |  
python -mjson.tool
```

```
[  
  {  
    "applicationToken": "358849227911747",  
    "id": "70",  
    "logAppendersNames": "mongoDBLogAppender,fileSystemLogAppender",  
    "name": "Player",  
    "publicKey": null,  
    "sequenceNumber": 2,  
    "tenantId": "10",  
    "userVerifierName": "dummyEndpointUserVerifier"  
  },  
  {  
    "applicationToken": "989414255707149",  
    "id": "71",  
    "logAppendersNames": "mongoDBLogAppender,fileSystemLogAppender",  
    "name": "Smart House",  
    "publicKey": null,  
    "sequenceNumber": 2,  
    "tenantId": "10",  
    "userVerifierName": "dummyEndpointUserVerifier"  
  },  
  {  
    "applicationToken": "561087972707255",  
    "id": "72",  
    "logAppendersNames": "mongoDBLogAppender,fileSystemLogAppender",  
    "name": "Test Flume Appender",  
    "publicKey": "",  
    "sequenceNumber": 2,  
    "tenantId": "10",  
    "userVerifierName": "dummyEndpointUserVerifier"  
  }  
]
```

## Get application

Returns an application by application ID

- **URL**  
/kaaAdmin/rest/api/application/{applicationId}

- **Method:**  
GET

- **URL params**

Parameter	Value	Description
applicationId	string	the ID of the application

- **Data params**

None

- **Success response:**

- **Code:** 200
  - **Example:**

```
{
  "applicationToken": "989414255707149",
  "id": "71",
  "logAppendersNames": "mongoDBLogAppender, fileSystemLogAppender",
  "name": "Smart House",
  "publicKey": null,
  "sequenceNumber": 2,
  "tenantId": "10",
  "userVerifierName": "dummyEndpointUserVerifier"
}
```

- **Error response:**

Status codes	Description
400 Bad Request	applicationId parameter is empty
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_ADMIN, TENANT_DEVELOPER, or TENANT_USER) or Tenant ID of the application does not match the Tenant ID of the user
404 Not Found	Application with the specified applicationId does not exist
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u devuser:devuser123 -X GET "http://localhost:8080/kaaAdmin/rest/api/application/71" |
python -mjson.tool
```

```
{
  "applicationToken": "989414255707149",
  "id": "71",
  "logAppendersNames": "mongoDBLogAppender, fileSystemLogAppender",
  "name": "Smart House",
  "publicKey": null,
  "sequenceNumber": 2,
  "tenantId": "10",
  "userVerifierName": "dummyEndpointUserVerifier"
}
```

## Create/Edit application

Creates or edits an application. If the application with the specified ID does not exist, it will be created. If the application with the specified ID exists, it will be updated. Only users with the TENANT\_ADMIN role are allowed to perform this operation.

- **URL**  
/kaaAdmin/rest/api/application

- **Method:**  
POST

- **URL params**  
None

- **Data params**  
Example:



```
{"name": "Application 1", "tenantId": "10"}
```

- **Success response:**

- **Code:** 200
- **Example:**

```
{  
  "applicationToken": "094302219096310",  
  "id": "220",  
  "logAppendersNames": "mongoDBLogAppender, fileSystemLogAppender",  
  "name": "Application 1",  
  "publicKey": null,  
  "sequenceNumber": 0,  
  "tenantId": "10",  
  "userVerifierName": "dummyEndpointUserVerifier"  
}
```

- **Error response:**

Status codes	Description
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_ADMIN) or the Tenant ID of the application to be edited does not match the Tenant ID of the user
404 Not Found	Application to be edited with the specified applicationId does not exist
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u admin:admin123 -X POST -H 'Content-Type: application/json' -d '{"name": "Application 1", "tenantId": "10"}' "http://localhost:8080/kaaAdmin/rest/api/application" | python -mjson.tool
```

```
{  
  "applicationToken": "094302219096310",  
  "id": "220",  
  "logAppendersNames": "mongoDBLogAppender, fileSystemLogAppender",  
  "name": "Application 1",  
  "publicKey": null,  
  "sequenceNumber": 0,  
  "tenantId": "10",  
  "userVerifierName": "dummyEndpointUserVerifier"  
}
```

## Delete application

Deletes an application. Only users with the TENANT\_ADMIN role are allowed to perform this operation.

- **URL**  
/kaaAdmin/rest/api/delApplication?applicationId

- **Method:**  
POST

- **URL params**

Parameter	Value	Description
applicationId	string	the ID of the application to be deleted

- **Data params**

None

- **Success response:**

- **Code:** 200

- **Error response:**

Status codes	Description
400 Bad Request	applicationId parameter is empty
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_ADMIN) or the Tenant ID of the application does not match the Tenant ID of the user
404 Not Found	Application with the specified applicationId does not exist
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u admin:admin123 -X POST "http://localhost:8080/kaaAdmin/rest/api/delApplication?applicationId=220" | python -mjson.tool
```

## SDK generation

### Get versions of all schema types

Returns versions for all schema types available in the application. Only users with role TENANT\_DEVELOPER or TENANT\_USER are allowed to requests this information.

- **URL**

/kaaAdmin/rest/api/schemaVersions/{applicationId}

- **Method:**

GET

- **URL params**

Parameter	Value	Description
applicationId	string	the ID of the application

- **Data params**

None

- **Success response:**

- **Code:** 200
  - **Example:**

```

{
  "configurationSchemaVersions": [
    {
      "id": "94",
      "majorVersion": 1,
      "minorVersion": 0
    }
  ],
  "logSchemaVersions": [
    {
      "id": "95",
      "majorVersion": 1,
      "minorVersion": 0
    }
  ],
  "notificationSchemaVersions": [
    {
      "id": "53e8e1ae4b0ab7d05c14dab",
      "majorVersion": 1,
      "minorVersion": 0
    }
  ],
  "profileSchemaVersions": [
    {
      "id": "93",
      "majorVersion": 1,
      "minorVersion": 0
    }
  ]
}

```

- **Error response:**

Status codes	Description
400 Bad Request	applicationId parameter is empty
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application does not match the Tenant ID id of the authenticated user
404 Not Found	Application with the specified applicationId does not exist
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```

curl -v -S -u devuser:devuser123 -X GET "http://localhost:8080/kaaAdmin/rest/api/schemaVersions/71" |
python -mjson.tool

```

```

{
  "configurationSchemaVersions": [
    {
      "id": "94",
      "majorVersion": 1,
      "minorVersion": 0
    }
  ],
  "logSchemaVersions": [
    {
      "id": "95",
      "majorVersion": 1,
      "minorVersion": 0
    }
  ],
  "notificationSchemaVersions": [
    {
      "id": "53e8ee1ae4b0ab7d05c14dab",
      "majorVersion": 1,
      "minorVersion": 0
    }
  ],
  "profileSchemaVersions": [
    {
      "id": "93",
      "majorVersion": 1,
      "minorVersion": 0
    }
  ]
}

```

## Generate endpoint SDK

Generates an endpoint SDK based on the target platform, Application ID, schema versions and event family map IDs specified in the request body. Only users with the TENANT\_DEVELOPER or TENANT\_USER role can perform this operation.

- **URL**  
/kaaAdmin/rest/api/sdk

- **Method:**  
POST

- **URL params**  
None

- **Data params**

**Example:**

```

{"applicationId": "71", "configurationSchemaVersion": "1", "profileSchemaVersion": "1", "notificationSchemaVersion": "1", "logSchemaVersion": "1", "targetPlatform": "ANDROID", "aefMapIds": ["131", "132", "133"]}

```

- **Success response:**
  - **Code:** 200
  - **SDK file raw data**

- **Error response:**

Status codes	Description
400 Bad Request	applicationId parameter is empty

401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application does not match the Tenant ID of the authenticated user
404 Not Found	Application with the specified applicationId does not exist
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -O -J -u devuser:devuser123 -X POST -H 'Content-Type: application/json' -d '{"applicationId": "71", "configurationSchemaVersion": "1", "profileSchemaVersion": "1", "notificationSchemaVersion": "1", "logSchemaVersion": "1", "targetPlatform": "ANDROID", "aefMapIds": ["131", "132", "133"]}' "http://localhost:8080/kaaAdmin/rest/api/sdk"
```

```
< HTTP/1.1 200 OK
* Server Apache-Coyote/1.1 is not blacklisted
< Server: Apache-Coyote/1.1
< Set-Cookie: JSESSIONID=C8F7CDCD67FF3EC19E280269511CD3F3; Path=/; HttpOnly
< Content-disposition: attachment; filename="kaa-client-sdk-android-pl-cl-nl-11.jar"
< Content-Type: application/java-archive
< Content-Length: 2887116
< Date: Thu, 21 Aug 2014 10:19:27 GMT
<
{ [data not shown]
100 2819k 100 2819k 100 196 50.8M 3619 --:--:-- --:--:-- --:--:-- 51.9M
* Connection #0 to host localhost left intact
curl: Saved to filename 'kaa-client-sdk-android-pl-cl-nl-11.jar'
```

## Profiling

### Get profile schemas

Returns the profile schemas for an application. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to request this information. A users can only request schemas for applications associated with the same user.

- **URL**  
/kaaAdmin/rest/api/profileSchemas/{applicationId}

- **Method:**

GET

- **URL params**

Parameter	Value	Description
applicationId	string	the ID of the application.

- **Data params**

None

- **Success response:**

- **Code: 200**
  - **Example:**

```
[
  {
    "applicationId": "71",
    "createdTime": 1407774234272,
    "createdUsername": "admin",
    "description": null,
    "endpointCount": 0,
    "id": "93",
    "majorVersion": 1,
    "minorVersion": 0,
    "name": "Generated",
    "schema": "{\r\n  \r\n  \"type\": \"record\", \r\n  \"name\": \"Profile\", \r\n  \"namespace\": \"org.kaa.config\", \r\n  \"fields\": [\r\n    {\r\n      \"name\": \"Properties\", \r\n      \"type\": {\r\n        \"type\": \"array\", \r\n        \"items\": {\r\n          \"name\": \"ProfileProperty\", \r\n          \"namespace\": \"config.system\", \r\n          \"type\": \"record\", \r\n          \"fields\": [\r\n            {\r\n              \"name\": \"name\", \r\n              \"type\": \"string\" \r\n            }, \r\n            {\r\n              \"name\": \"value\", \r\n              \"type\": \"string\" \r\n            } \r\n          ] \r\n        } \r\n      } \r\n    } \r\n  ] \r\n}"
```

• **Error response:**

Status codes	Description
400 Bad Request	applicationId parameter is empty
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application does not match the Tenant ID of the authenticated user
404 Not Found	Application with the specified applicationId does not exist
500 Internal Server Error	Unexpected error occurred on the server side

• **Sample call:**

```
curl -v -S -u devuser:devuser123 -X GET "http://localhost:8080/kaaAdmin/rest/api/profileSchemas/71" | python -mjson.tool
```

```
[
  {
    "applicationId": "71",
    "createdTime": 1407774234272,
    "createdUsername": "admin",
    "description": null,
    "endpointCount": 0,
    "id": "93",
    "majorVersion": 1,
    "minorVersion": 0,
    "name": "Generated",
    "schema": "{\r\n  \"type\": \"record\", \r\n  \"name\": \"Profile\", \r\n  \"namespace\": \"org.kaa.config\", \r\n  \"fields\": [\r\n    {\r\n      \"name\": \"Properties\", \r\n      \"type\": {\r\n        \"type\": \"array\", \r\n        \"items\": {\r\n          \"name\": \"ProfileProperty\", \r\n          \"namespace\": \"config.system\", \r\n          \"type\": \"record\", \r\n          \"fields\": [\r\n            {\r\n              \"name\": \"name\", \r\n              \"type\": \"string\", \r\n              \"name\": \"value\", \r\n              \"type\": \"string\" \r\n            } \r\n          ] \r\n        } \r\n      } \r\n    ] \r\n  }"
  }
]
```

## Get profile schema

Returns the profile schema by Profile Schema ID. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to request this information.

- **URL**  
/kaaAdmin/rest/api/profileSchema/{profileSchemaId}

- **Method:**  
GET

- **URL params**

Parameter	Value	Description
profileSchemaId	string	the ID of the profile schema

- **Data params**

None

- **Success response:**

- **Code: 200**
  - **Example:**

```
{
  "applicationId": "71",
  "createdTime": 1407774234272,
  "createdUsername": "admin",
  "description": null,
  "endpointCount": 0,
  "id": "93",
  "majorVersion": 1,
  "minorVersion": 0,
  "name": "Generated",
  "schema": "{\r\n  \"type\": \"record\", \r\n  \"name\": \"Profile\", \r\n  \"namespace\": \"org.kaa.config\", \r\n  \"fields\": [\r\n    {\r\n      \"name\": \"Properties\", \r\n      \"type\": {\r\n        \"type\": \"array\", \r\n        \"items\": {\r\n          \"namespace\": \"config.system\", \r\n          \"type\": \"record\", \r\n          \"fields\": [\r\n            {\r\n              \"name\": \"name\", \r\n              \"type\": \"string\" \r\n            }, \r\n            {\r\n              \"name\": \"value\", \r\n              \"type\": \"string\" \r\n            } \r\n          ] \r\n        } \r\n      } \r\n    } \r\n  ] \r\n}"
```

- **Error response:**

Status codes	Description
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application associated with the profile schema does not match the Tenant ID of the authenticated user
404 Not Found	Profile schema with the specified profileSchemaId does not exist
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u devuser:devuser123 -X GET "http://localhost:8080/kaaAdmin/rest/api/profileSchema/93" | python -mjson.tool
```



```

{
  "applicationId": "71",
  "createdTime": 1407774234272,
  "createdUsername": "admin",
  "description": null,
  "endpointCount": 0,
  "id": "93",
  "majorVersion": 1,
  "minorVersion": 0,
  "name": "Generated",
  "schema": "{\r\n  \"type\": \"record\", \r\n  \"name\": \"Profile\", \r\n  \"namespace\": \r\n  \"org.kaa.config\", \r\n  \"fields\": [\r\n    {\r\n      \"name\": \"Properties\", \r\n      \"type\": {\r\n        \"type\": \"array\", \r\n        \"items\": {\r\n          \"name\": \"ProfileProperty\", \r\n          \"namespace\": \"config.system\", \r\n          \"type\": \"record\", \r\n          \"fields\": [\r\n            {\r\n              \"name\": \"name\", \r\n              \"type\": \"string\" \r\n            }, \r\n            {\r\n              \"name\": \"value\", \r\n              \"type\": \"string\" \r\n            } \r\n          ] \r\n        } \r\n      } \r\n    ] \r\n  }"
}

```

## Create profile schema

Uploads a profile schema. A unique version number will be generated (incrementally) for the uploaded schema, and the createdUsername field of the schema will be set to the name of the user who uploaded it. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to perform this operation.

- **URL**  
/kaaAdmin/rest/api/profileSchema
- **Method:**  
POST
- **URL params**  
None
- **Data params**

Multipart/form-data encoding. Fields:

### Example:

```
{"applicationId":"71","name":"Test profile schema","description":"Profile Schema Description"}
```

### File contents example:

```

{
  "type": "record",
  "name": "TestProfile",
  "namespace": "org.kaa.config.test",
  "fields": [
    {
      "name": "Properties",
      "type": {
        "type": "array",
        "items": {
          "name": "ProfileProperty",
          "namespace": "config.system",
          "type": "record",
          "fields": [
            {
              "name": "name",
              "type": "string"
            },
            {
              "name": "value",
              "type": "string"
            }
          ]
        }
      }
    }
  ]
}

```

- **Success response:**

- **Code: 200**

- **Example:**

```

{
  "applicationId": "71",
  "createTime": 1408626073766,
  "createdUsername": "devuser",
  "description": "Profile Schema Description",
  "endpointCount": 0,
  "id": "97",
  "majorVersion": 3,
  "minorVersion": 0,
  "name": "Test profile schema",
  "schema": "{\n  \"type\": \"record\", \n  \"name\": \"TestProfile\", \n  \"namespace\": \"org.kaa.config.test\", \n  \"fields\": [\n    {\n      \"name\": \"Properties\", \n      \"type\": {\n        \"type\": \"array\", \n        \"items\": {\n          \"name\": \"ProfileProperty\", \n          \"namespace\": \"config.system\", \n          \"type\": \"record\", \n          \"fields\": [\n            {\n              \"name\": \"name\", \n              \"type\": \"string\" \n            }, \n            {\n              \"name\": \"value\", \n              \"type\": \"string\" \n            } \n          ] \n        } \n      } \n    } \n  ] \n}"

```

- **Error response:**

Status codes	Description
400 Bad Request	Specified profile schema is not a valid avro schema

401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application associated with the profile schema does not match the Tenant ID of the authenticated user
404 Not Found	File with a schema not found in the form data
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u devuser:devuser123 -F'profileSchema={"applicationId":"71","name":"Test profile schema","description":"Profile Schema Description"};type=application/json' -F file=@profile_schema.json "http://localhost:8080/kaaAdmin/rest/api/profileSchema" | python -mjson.tool
```

```
{
  "applicationId": "71",
  "createdTime": 1408626073766,
  "createdUsername": "devuser",
  "description": "Profile Schema Description",
  "endpointCount": 0,
  "id": "97",
  "majorVersion": 3,
  "minorVersion": 0,
  "name": "Test profile schema",
  "schema": "{\n  \"type\": \"record\",\n  \"name\": \"TestProfile\",\n  \"namespace\": \"org.kaa.config.test\",\n  \"fields\": [\n    {\n      \"name\": \"Properties\",\n      \"type\": {\n        \"type\": \"array\",\n        \"items\": {\n          \"name\": \"ProfileProperty\",\n          \"namespace\": \"config.system\",\n          \"type\": \"record\",\n          \"fields\": [\n            {\n              \"name\": \"name\", \"type\": \"string\"\n            },\n            {\n              \"name\": \"value\", \"type\": \"string\"\n            }\n          ]\n        }\n      }\n    }\n  ]\n}"
```

## Grouping

### Get endpoint groups

Returns all endpoint groups for the specified application. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to request this information.

- **URL**  
/kaaAdmin/rest/api/endpointGroups/{applicationId}

- **Method:**  
GET

- **URL params**

Parameter	Value	Description
applicationId	string	the ID of the application.

- **Data params**

None

- **Success response:**

- **Code:** 200
  - **Example:**

```
[
  {
    "applicationId": "71",
    "createdTime": 1408705246400,
    "createdUsername": "admin",
    "description": null,
    "endpointCount": 0,
    "id": "81",
    "name": "All",
    "sequenceNumber": 0,
    "topics": [],
    "weight": 0
  }
]
```

- **Error response:**

Status codes	Description
400 Bad Request	applicationId parameter is empty
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application does not match the Tenant ID of the authenticated user
404 Not Found	Application with the specified applicationId does not exist
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u devuser:devuser123 -X GET "http://localhost:8080/kaaAdmin/rest/api/endpointGroups/71" |
python -mjson.tool
```

```
[
  {
    "applicationId": "71",
    "createdTime": 1408705246400,
    "createdUsername": "admin",
    "description": null,
    "endpointCount": 0,
    "id": "81",
    "name": "All",
    "sequenceNumber": 0,
    "topics": [],
    "weight": 0
  }
]
```

## Get endpoint group

Returns an endpoint group by Endpoint Group ID. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to request this information.

- **URL**  
/kaaAdmin/rest/api/endpointGroup/{endpointGroupId}

- **Method:**  
GET

- **URL params**

Parameter	Value	Description
endpointGroupld	string	the id of the endpoint group

- **Data params**

None

- **Success response:**

- **Code:** 200

- **Example:**

```
{
  "applicationId": "71",
  "createdTime": 1408705246400,
  "createdUsername": "admin",
  "description": null,
  "endpointCount": 0,
  "id": "81",
  "name": "All",
  "sequenceNumber": 0,
  "topics": [],
  "weight": 0
}
```

- **Error response:**

Status codes	Description
400 Bad Request	endpointGroupld parameter is empty
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application associated with endpoint group does not match the Tenant ID of the authenticated user
404 Not Found	Endpoint group with the specified endpointGroupld does not exist
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u devuser:devuser123 -X GET "http://localhost:8080/kaaAdmin/rest/api/endpointGroup/81" |
python -mjson.tool
```

```
{
  "applicationId": "71",
  "createdTime": 1408705246400,
  "createdUsername": "admin",
  "description": null,
  "endpointCount": 0,
  "id": "81",
  "name": "All",
  "sequenceNumber": 0,
  "topics": [],
  "weight": 0
}
```

## Create/Edit endpoint group

Creates or edits an endpoint group. If an endpoint group with the specified ID does not exist, it will be created. If an endpoint group with the specified ID exists, it will be updated. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to perform this operation.

- **URL**  
/kaaAdmin/rest/api/endpointGroup

- **Method:**  
POST

- **URL params**  
None

- **Data params**

**Example:**

```
{"applicationId": "71", "name": "Test Endpoint Group", "description": "Test Endpoint Group Description", "weight": "1"}
```

- **Success response:**

- **Code:** 200
  - **Example:**

```
{
  "applicationId": "71",
  "createdTime": 1408711565372,
  "createdUsername": "devuser",
  "description": "Test Endpoint Group Description",
  "endpointCount": 0,
  "id": "82",
  "name": "Test Endpoint Group",
  "sequenceNumber": 0,
  "topics": [],
  "weight": 1
}
```

- **Error response:**

Status codes	Description
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application associated with endpoint group does not match the Tenant ID of the authenticated user
404 Not Found	Endpoint group to be edited with the specified endpointGroupId does not exist
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u devuser:devuser123 -X POST -H 'Content-Type: application/json' -d '{"applicationId": "71", "name": "Test Endpoint Group", "description": "Test Endpoint Group Description", "weight": "1"}' "http://localhost:8080/kaaAdmin/rest/api/endpointGroup" | python -mjson.tool
```

```

{
  "applicationId": "71",
  "createdTime": 1408711565372,
  "createdUsername": "devuser",
  "description": "Test Endpoint Group Description",
  "endpointCount": 0,
  "id": "82",
  "name": "Test Endpoint Group",
  "sequenceNumber": 0,
  "topics": [],
  "weight": 1
}

```

## Delete endpoint group

Deletes an endpoint group specified by Endpoint Group ID. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to perform this operation.

- **URL**  
/kaaAdmin/rest/api/delEndpointGroup?endpointGroupId

- **Method:**

POST

- **URL params**

Parameter	Value	Description
endpointGroupId	string	the ID of the endpoint group to be deleted

- **Data params**

None

- **Success response:**

- **Code:** 200

- **Error response:**

Status codes	Description
400 Bad Request	endpointGroupId parameter is empty
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application associated with the endpoint group does not match the Tenant ID of the authenticated user
404 Not Found	Endpoint group with the specified endpointGroupId does not exist
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```

curl -v -S -u devuser:devuser123 -X POST "http://localhost:8080/kaaAdmin/rest/api/delEndpointGroup?endpointGroupId=82" | python -mjson.tool

```

## Get profile filter records

Returns all profile filter records for the specified endpoint group. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to request this information.

- **URL**  
/kaaAdmin/rest/api/profileFilterRecords?endpointGroupId&includeDeprecated

- **Method:**

GET

- **URL params**

Parameter	Value	Description
endpointGroupId	string	the ID of the endpoint group
includeDeprecated	string	["true" or "false"] if "true", all profile filter records will be returned, including deprecated ones. If "false", only active and inactive profile filter records will be returned

- **Data params**

None

- **Success response:**

- **Code: 200**
  - **Example:**

```
[
  {
    "activeProfileFilter": {
      "activatedTime": 1408705246444,
      "activatedUsername": "admin",
      "applicationId": "71",
      "body": "true",
      "createdTime": 1408705246433,
      "createdUsername": null,
      "deactivatedTime": 0,
      "deactivatedUsername": null,
      "description": null,
      "endpointCount": 0,
      "endpointGroupId": "81",
      "id": "102",
      "lastModifyTime": 1408705246433,
      "majorVersion": 1,
      "minorVersion": 0,
      "modifiedUsername": null,
      "schemaId": "93",
      "sequenceNumber": 1,
      "status": "ACTIVE"
    },
    "inactiveProfileFilter": null
  }
]
```

- **Error response:**

Status codes	Description
400 Bad Request	endpointGroupId parameter is empty
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application associated with the endpoint group does not match the Tenant ID of the authenticated user
404 Not Found	Endpoint group with the specified endpointGroupId does not exist
500 Internal	Unexpected error occurred on the server side



- **Sample call:**

```
curl -v -S -u devuser:devuser123 -X GET "http://localhost:8080/kaaAdmin/rest/api/profileFilterRecords?endpointGroupId=81&includeDeprecated=true" | python -mjson.tool
```

```
[
  {
    "activeProfileFilter": {
      "activatedTime": 1408705246444,
      "activatedUsername": "admin",
      "applicationId": "71",
      "body": "true",
      "createdTime": 1408705246433,
      "createdUsername": null,
      "deactivatedTime": 0,
      "deactivatedUsername": null,
      "description": null,
      "endpointCount": 0,
      "endpointGroupId": "81",
      "id": "102",
      "lastModifyTime": 1408705246433,
      "majorVersion": 1,
      "minorVersion": 0,
      "modifiedUsername": null,
      "schemaId": "93",
      "sequenceNumber": 1,
      "status": "ACTIVE"
    },
    "inactiveProfileFilter": null
  }
]
```

## Get profile filter record

Returns the profile filter record for the specified endpoint group and profile schema. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to request this information.

- **URL**  
/kaaAdmin/rest/api/profileFilterRecord?schemald&endpointGroupld

- **Method:**

GET

- **URL params**

Parameter	Value	Description
schemald	string	the ID of the profile schema
endpointGroupld	string	the ID of the endpoint group

- **Data params**

None

- **Success response:**

- **Code:** 200
  - **Example:**

```
{
  "activeProfileFilter": {
    "activatedTime": 1408705246444,
    "activatedUsername": "admin",
```

```

        "applicationId": "71",
        "body": "true",
        "createdTime": 1408705246433,
        "createdUsername": null,
        "deactivatedTime": 0,
        "deactivatedUsername": null,
        "description": null,
        "endpointCount": 0,
        "endpointGroupId": "81",
        "id": "102",
        "lastModifyTime": 1408705246433,
        "majorVersion": 1,
        "minorVersion": 0,
        "modifiedUsername": null,
        "schemaId": "93",
        "sequenceNumber": 1,
        "status": "ACTIVE"
    },
    "inactiveProfileFilter": null
}

```

- **Error response:**

Status codes	Description
400 Bad Request	endpointGroupId parameter is empty
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application associated with the endpoint group does not match the Tenant ID of the authenticated user
404 Not Found	Endpoint group with the specified endpointGroupId does not exist or endpoint group does not have the specified profile filter record
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```

curl -v -S -u devuser:devuser123 -X GET "http://localhost:8080/kaaAdmin/rest/api/profileFilterRecord?schemaId=93&endpointGroupId=81" | python -mjson.tool

```

```

{
  "activeProfileFilter": {
    "activatedTime": 1408705246444,
    "activatedUsername": "admin",
    "applicationId": "71",
    "body": "true",
    "createdTime": 1408705246433,
    "createdUsername": null,
    "deactivatedTime": 0,
    "deactivatedUsername": null,
    "description": null,
    "endpointCount": 0,
    "endpointGroupId": "81",
    "id": "102",
    "lastModifyTime": 1408705246433,
    "majorVersion": 1,
    "minorVersion": 0,
    "modifiedUsername": null,
    "schemaId": "93",
    "sequenceNumber": 1,
    "status": "ACTIVE"
  },
}

```

```
    "inactiveProfileFilter": null
  }
```

## Get vacant profile schemas

Returns all vacant (not being used by endpoint group profile filters) profile schemas for the specified endpoint group. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to request this information.

- **URL**  
/kaaAdmin/rest/api/vacantProfileSchemas?endpointGroupId

- **Method:**  
GET

- **URL params**

Parameter	Value	Description
endpointGroupId	string	the id of the endpoint group

- **Data params**

None

- **Success response:**

- **Code: 200**
  - **Example:**

```
[
  {
    "id": "93",
    "majorVersion": 1,
    "minorVersion": 0
  },
  {
    "id": "99",
    "majorVersion": 2,
    "minorVersion": 0
  }
]
```

- **Error response:**

Status codes	Description
400 Bad Request	endpointGroupId parameter is empty
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application associated with the endpoint group does not match the Tenant ID of the authenticated user
404 Not Found	Endpoint group with the specified endpointGroupId does not exist
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u devuser:devuser123 -X GET "http://localhost:8080/kaaAdmin/rest/api/vacantProfileSchemas?endpointGroupId=83" | python -mjson.tool
```

```
[
  {
    "id": "93",
    "majorVersion": 1,
    "minorVersion": 0
  },
  {
    "id": "99",
    "majorVersion": 2,
    "minorVersion": 0
  }
]
```

## Create/Edit profile filter

Creates or updates a profile filter. If a profile filter with the specified ID does not exist, then it will be created and its createUsername field will be set to the name of the user who has created it. If a profile filter with the specified ID exists, the profile filter will be updated and its modifyUsername will be set to the user who has submitted the request. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to perform this operation.

- **URL**  
/kaaAdmin/rest/api/profileFilter

- **Method:**  
POST

- **URL params**  
None

- **Data params**

### Example:

```
{"applicationId":"71","schemaId":"93","endpointGroupId":"83","majorVersion":"1","minorVersion":"0","description":"Test Profile Filter","body":"true","status":"INACTIVE"}
```

- **Success response:**

- **Code:** 200
  - **Example:**

```
{
  "activatedTime": 0,
  "activatedUsername": null,
  "applicationId": "71",
  "body": "true",
  "createdTime": 1408715796493,
  "createdUsername": "devuser",
  "deactivatedTime": 0,
  "deactivatedUsername": null,
  "description": "Test Profile Filter",
  "endpointCount": 0,
  "endpointGroupId": "83",
  "id": "107",
  "lastModifyTime": 1408715796493,
  "majorVersion": 1,
  "minorVersion": 0,
  "modifiedUsername": null,
  "schemaId": "93",
  "sequenceNumber": 0,
  "status": "INACTIVE"
}
```

- **Error response:**

Status codes	Description
--------------	-------------

401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application associated with the endpoint group does not match the Tenant ID of the authenticated user
404 Not Found	Endpoint group with the specified endpointGroupId does not exist or existing profile filter with the specified profileFilterId not found
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u devuser:devuser123 -X POST -H 'Content-Type: application/json' -d '{"applicationId": "71", "schemaId": "93", "endpointGroupId": "83", "majorVersion": "1", "minorVersion": "0", "description": "Test Profile Filter", "body": "true", "status": "INACTIVE"}' "http://localhost:8080/kaaAdmin/rest/api/profileFilter" | python -mjson.tool
```

```
{
  "activatedTime": 0,
  "activatedUsername": null,
  "applicationId": "71",
  "body": "true",
  "createdTime": 1408715796493,
  "createdUsername": "devuser",
  "deactivatedTime": 0,
  "deactivatedUsername": null,
  "description": "Test Profile Filter",
  "endpointCount": 0,
  "endpointGroupId": "83",
  "id": "107",
  "lastModifyTime": 1408715796493,
  "majorVersion": 1,
  "minorVersion": 0,
  "modifiedUsername": null,
  "schemaId": "93",
  "sequenceNumber": 0,
  "status": "INACTIVE"
}
```

## Activate profile filter

Activates a profile filter. Sets the status field of the profile filter to ACTIVE, increments the sequenceNumber field value by 1, and sets the activateUsername and activatedTime fields to the name of the user who submitted the request and the activation time, respectively. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to perform this operation.

- **URL**  
/kaaAdmin/rest/api/activateProfileFilter

- **Method:**  
POST

- **URL params**  
None

- **Data params**

**Example:**

107

- **Success response:**

- **Code:** 200
  - **Example:**

```

{
  "activatedTime": 1408716471682,
  "activatedUsername": "devuser",
  "applicationId": "71",
  "body": "true",
  "createdTime": 1408715796493,
  "createdUsername": "devuser",
  "deactivatedTime": 0,
  "deactivatedUsername": null,
  "description": "Test Profile Filter",
  "endpointCount": 0,
  "endpointGroupId": "83",
  "id": "107",
  "lastModifyTime": 1408715796493,
  "majorVersion": 1,
  "minorVersion": 0,
  "modifiedUsername": null,
  "schemaId": "93",
  "sequenceNumber": 1,
  "status": "ACTIVE"
}

```

- **Error response:**

Status codes	Description
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application associated with the endpoint group does not match the Tenant ID of the authenticated user
404 Not Found	Profile filter with the specified profileFilterId not found
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```

curl -v -S -u devuser:devuser123 -X POST -H 'Content-Type: text/plain' -d'107' "http://localhost:8080 /kaaAdmin/rest/api/activateProfileFilter" | python -mjson.tool

```

```

{
  "activatedTime": 1408716471682,
  "activatedUsername": "devuser",
  "applicationId": "71",
  "body": "true",
  "createdTime": 1408715796493,
  "createdUsername": "devuser",
  "deactivatedTime": 0,
  "deactivatedUsername": null,
  "description": "Test Profile Filter",
  "endpointCount": 0,
  "endpointGroupId": "83",
  "id": "107",
  "lastModifyTime": 1408715796493,
  "majorVersion": 1,
  "minorVersion": 0,
  "modifiedUsername": null,
  "schemaId": "93",
  "sequenceNumber": 1,
  "status": "ACTIVE"
}

```

## Deactivate profile filter

Deactivates a profile filter. Sets the status field of the profile filter to DEPRECATED, sets the deactivatedTime field value to the time of the deactivation request, and sets the deactivateUsername field to the name of the user who has submitted the request. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to perform this operation.

- **URL**  
/kaaAdmin/rest/api/deactivateProfileFilter

- **Method:**  
POST

- **URL params**  
None

- **Data params**

**Example:**

```
107
```

- **Success response:**

- **Code:** 200
  - **Example:**

```
{
  "activatedTime": 1408716471682,
  "activatedUsername": "devuser",
  "applicationId": "71",
  "body": "true",
  "createdTime": 1408715796493,
  "createdUsername": "devuser",
  "deactivatedTime": 1408716757502,
  "deactivatedUsername": "devuser",
  "description": "Test Profile Filter",
  "endpointCount": 0,
  "endpointGroupId": "83",
  "id": "107",
  "lastModifyTime": 1408715796493,
  "majorVersion": 1,
  "minorVersion": 0,
  "modifiedUsername": null,
  "schemaId": "93",
  "sequenceNumber": 1,
  "status": "DEPRECATED"
}
```

- **Error response:**

Status codes	Description
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application associated with the endpoint group does not match the Tenant ID of the authenticated user
404 Not Found	Profile filter with the specified profileFilterId not found
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u devuser:devuser123 -X POST -H 'Content-Type: text/plain' -d'107' "http://localhost:8080 /kaaAdmin/rest/api/deactivateProfileFilter" | python -mjson.tool
```

```

{
  "activatedTime": 1408716471682,
  "activatedUsername": "devuser",
  "applicationId": "71",
  "body": "true",
  "createdTime": 1408715796493,
  "createdUsername": "devuser",
  "deactivatedTime": 1408716757502,
  "deactivatedUsername": "devuser",
  "description": "Test Profile Filter",
  "endpointCount": 0,
  "endpointGroupId": "83",
  "id": "107",
  "lastModifyTime": 1408715796493,
  "majorVersion": 1,
  "minorVersion": 0,
  "modifiedUsername": null,
  "schemaId": "93",
  "sequenceNumber": 1,
  "status": "DEPRECATED"
}

```

## Delete profile filter record

Deletes a profile filter record by profile schema ID and endpoint group ID. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to perform this operation.

- **URL**  
/kaaAdmin/rest/api/delProfileFilterRecord?schemald&endpointGroupId

- **Method:**  
POST

- **URL params**

Parameter	Value	Description
schemald	string	the ID of the profile schema
endpointGroupId	string	the ID of the endpoint group

- **Data params**

None

- **Success response:**

- **Code:** 200

- **Error response:**

Status codes	Description
400 Bad Request	endpointGroupId parameter is empty
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application associated with the endpoint group does not match the Tenant ID of the authenticated user
404 Not Found	Endpoint group with the specified endpointGroupId does not exist or the endpoint group does not have the specified profile filter record
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call**



```
curl -v -S -u devuser:devuser123 -X POST "http://localhost:8080/kaaAdmin/rest/api/delProfileFilterRecord?schemaId=93&endpointGroupId=83" | python -mjson.tool
```

## Configuration

### Get configuration schemas

Returns all configuration schemas for the specified application. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to perform this operation. The application must be associated with the user who has submitted the request.

- **URL**  
/kaaAdmin/rest/api/configurationSchemas/{applicationId}

- **Method:**

GET

- **URL params**

Parameter	Value	Description
applicationId	string	the ID of the application.

- **Data params**

None

- **Success response:**

- **Code: 200**
  - **Example:**

```
[
  {
    "applicationId": "71",
    "baseSchema": "{\n  \"type\": \"record\",\n  \"name\": \"ConfigurationSchema\",\n  \"namespace\": \"org.kaa.config\",\n  \"fields\": [\n    {\n      \"name\": \"Properties\",\n      \"type\": {\n        \"type\": \"array\",\n        \"items\": {\n          \"name\": \"ConfigurationProperty\",\n          \"namespace\": \"config.system\",\n          \"type\": \"record\",\n          \"fields\": [\n            {\n              \"name\": \"name\",\n              \"type\": \"string\"\n            },\n            {\n              \"name\": \"value\",\n              \"type\": \"string\"\n            },\n            {\n              \"name\": \"__uuid\",\n              \"type\": {\n                \"name\": \"uuidT\",\n                \"type\": \"fixed\",\n                \"size\": 16,\n                \"namespace\": \"org.kaaproject.configuration\",\n                \"null\": \"\"\n              }\n            }\n          ]\n        },\n        \"symbols\": {\n          \"name\": \"__uuid\",\n          \"type\": {\n            \"name\": \"org.kaaproject.configuration.uuidT\",\n            \"null\": \"\"\n          }\n        }\n      }\n    },\n    {\n      \"name\": \"createdTime\",\n      \"type\": \"long\"\n    },\n    {\n      \"name\": \"createdUsername\",\n      \"type\": \"string\"\n    },\n    {\n      \"name\": \"description\",\n      \"type\": \"string\"\n    },\n    {\n      \"name\": \"endpointCount\",\n      \"type\": \"int\"\n    },\n    {\n      \"name\": \"id\",\n      \"type\": \"int\"\n    },\n    {\n      \"name\": \"majorVersion\",\n      \"type\": \"int\"\n    },\n    {\n      \"name\": \"minorVersion\",\n      \"type\": \"int\"\n    },\n    {\n      \"name\": \"name\",\n      \"type\": \"string\"\n    },\n    {\n      \"name\": \"overrideSchema\",\n      \"type\": {\n        \"type\": \"record\",\n        \"name\": \"ConfigurationSchema\",\n        \"namespace\": \"org.kaa.config\",\n        \"fields\": [\n          {\n            \"name\": \"Properties\",\n            \"type\": {\n              \"type\": \"array\",\n              \"items\": {\n                \"name\": \"ConfigurationProperty\",\n                \"namespace\": \"config.system\",\n                \"type\": \"record\",\n                \"fields\": [\n                  {\n                    \"name\": \"name\",\n                    \"type\": \"string\"\n                  },\n                  {\n                    \"name\": \"value\",\n                    \"type\": {\n                      \"name\": \"string\",\n                      \"type\": \"fixed\",\n                      \"size\": 16,\n                      \"namespace\": \"org.kaaproject.configuration\",\n                      \"null\": \"\"\n                    }\n                  },\n                  {\n                    \"name\": \"__uuid\",\n                    \"type\": {\n                      \"name\": \"org.kaaproject.configuration.uuidT\",\n                      \"null\": \"\"\n                    }\n                  }\n                ]\n              },\n              \"symbols\": {\n                \"name\": \"__uuid\",\n                \"type\": {\n                  \"name\": \"org.kaaproject.configuration.uuidT\",\n                  \"null\": \"\"\n                }\n              }\n            }\n          },\n          {\n            \"name\": \"protocolSchema\",\n            \"type\": {\n              \"type\": \"record\",\n              \"name\": \"ConfigurationSchema\",\n              \"namespace\": \"org.kaa.config\",\n              \"fields\": [\n                {\n                  \"name\": \"Properties\",\n                  \"type\": {\n                    \"type\": \"array\",\n                    \"items\": {\n                      \"name\": \"ConfigurationProperty\",\n                      \"namespace\": \"config.system\",\n                      \"type\": \"record\",\n                      \"fields\": [\n                        {\n                          \"name\": \"name\",\n                          \"type\": \"string\"\n                        },\n                        {\n                          \"name\": \"value\",\n                          \"type\": {\n                            \"name\": \"string\",\n                            \"type\": \"fixed\",\n                            \"size\": 16,\n                            \"namespace\": \"org.kaaproject.configuration\",\n                            \"null\": \"\"\n                          }\n                        },\n                        {\n                          \"name\": \"__uuid\",\n                          \"type\": {\n                            \"name\": \"org.kaaproject.configuration.uuidT\",\n                            \"null\": \"\"\n                          }\n                        }\n                      ]\n                    },\n                    \"symbols\": {\n                      \"name\": \"__uuid\",\n                      \"type\": {\n                        \"name\": \"org.kaaproject.configuration.uuidT\",\n                        \"null\": \"\"\n                      }\n                    }\n                  }\n                }\n              ]\n            }\n          }\n        ]\n      }\n    }\n  ]\n}"
```

```

unchangedT"}],{"name\":\"__uuid\",\"type\":{\"name\":\"uuidT\",\"type\":\"fixed\",\"size\":16,\"namespace\":\"org.kaaproject.configuration\"}},\"org.kaaproject.configuration.uuidT\"}},{"symbols\":[\"reset\"],\"name\":\"resetT\",\"type\":\"enum\",\"namespace\":\"org.kaaproject.configuration\"},\"org.kaaproject.configuration.unchangedT\"}},{"name\":\"__uuid\",\"type\":\"org.kaaproject.configuration.uuidT\"}},\"config.system.ConfigurationProperty\"}},\"namespace\":\"org.kaaproject.configuration\"},\"type\":\"array\"},
  \"schema\": \"{\\r\\n    \\\"type\\\": \\\"record\\\",\\r\\n    \\\"name\\\": \\\"ConfigurationSchema\\\",
\\r\\n    \\\"namespace\\\": \\\"org.kaa.config\\\",\\r\\n    \\\"fields\\\": [{\\r\\n        {\\r\\n
\\\"name\\\": \\\"Properties\\\",\\r\\n            \\\"type\\\": {\\r\\n                \\\"type\\\": \\\"array\\\",
\\r\\n                \\\"items\\\": {\\r\\n                    \\\"name\\\": \\\"ConfigurationProperty\\\",
\\r\\n                    \\\"namespace\\\": \\\"config.system\\\",\\r\\n                    \\\"type\\\":
\\\"record\\\",\\r\\n                    \\\"fields\\\": [{\\r\\n
{\\r\\n                        \\\"name\\\": \\\"name\\\",\\r\\n                        \\\"
type\\\": \\\"string\\\"\\r\\n                    },\\r\\n
{\\r\\n                        \\\"name\\\": \\\"value\\\",\\r\\n                        \\\"
type\\\": \\\"string\\\"\\r\\n                    }\\r\\n                }\\r\\n            }\\r\\n
}\\r\\n        }\\r\\n    }\\r\\n    }\\r\\n    }\\r\\n    }\",
    \"status\": null
  }
]

```

• **Error response:**

Status codes	Description
400 Bad Request	applicationId parameter is empty
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application does not match the Tenant ID of the authenticated user
404 Not Found	Application with the specified applicationId does not exist
500 Internal Server Error	Unexpected error occurred on the server side

• **Sample call:**

```
curl -v -S -u devuser:devuser123 -X GET "http://localhost:8080/kaaAdmin/rest/api/configurationSchemas/71" | python -mjson.tool
```

```

[
  {
    "applicationId": "71",
    "baseSchema": "{\\\"type\\\":\\\"record\\\",\\\"name\\\":\\\"ConfigurationSchema\\\",\\\"namespace\\\":\\\"org.kaa.config\\\",\\\"fields\\\":[{\\\"name\\\":\\\"Properties\\\",\\\"type\\\":{\\\"type\\\":\\\"array\\\",\\\"items\\\":{\\\"name\\\":\\\"ConfigurationProperty\\\",\\\"namespace\\\":\\\"config.system\\\",\\\"type\\\":\\\"record\\\",\\\"fields\\\":[{\\\"name\\\":\\\"name\\\",\\\"type\\\":\\\"string\\\",{\\\"name\\\":\\\"value\\\",\\\"type\\\":\\\"string\\\",{\\\"name\\\":\\\"__uuid\\\",\\\"type\\\":[{\\\"name\\\":\\\"uuidT\\\",\\\"type\\\":\\\"fixed\\\",\\\"size\\\":16,\\\"namespace\\\":\\\"org.kaaproject.configuration\\\",\\\"null\\\"}]}]}]}],{\\\"name\\\":\\\"__uuid\\\",\\\"type\\\":[\\\"org.kaaproject.configuration.uuidT\\\",\\\"null\\\"]}]}\",
    \"createdTime\": 140863899001,
    \"createdUsername\": \"admin\",
    \"description\": null,
    \"endpointCount\": 0,
    \"id\": \"94\",
    \"majorVersion\": 1,
    \"minorVersion\": 0,
    \"name\": \"Generated\",
    \"overrideSchema\": \"{\\\"type\\\":\\\"record\\\",\\\"name\\\":\\\"ConfigurationSchema\\\",\\\"namespace\\\":\\\"org.kaa.config\\\",\\\"fields\\\":[{\\\"name\\\":\\\"Properties\\\",\\\"type\\\":[{\\\"type\\\":\\\"array\\\",\\\"items\\\":{\\\"name\\\":\\\"ConfigurationProperty\\\",\\\"namespace\\\":\\\"config.system\\\",\\\"type\\\":\\\"record\\\",\\\"fields\\\":[{\\\"name\\\":\\\"name\\\",\\\"type\\\":[\\\"string\\\",{\\\"symbols\\\":[\\\"unchanged\\\"],\\\"name\\\":\\\"unchangedT\\\",\\\"

```

```

type\":"enum\","namespace\":"org.kaaproject.configuration"}]},{"name\":"value\","type\":["string\","org.kaaproject.configuration.unchangedT"}]},{"name\":"__uuid\","type\":["name\":"uuidT\","type\":"fixed\","size\":16,"namespace\":"org.kaaproject.configuration"}],"null"}]}],"org.kaaproject.configuration.unchangedT"}]},{"name\":"__uuid\","type\":["org.kaaproject.configuration.uuidT\","null"}]}]}",
  "protocolSchema": "{\n  \"items\": {\n    \"name\": \"deltaT\", \"type\": \"record\", \"fields\": {\n      \"name\": \"delta\", \"type\": {\n        \"type\": \"record\", \"name\": \"ConfigurationSchema\", \"namespace\": \"org.kaa.config\", \"fields\": {\n          \"name\": \"Properties\", \"type\": {\n            \"type\": \"array\", \"items\": {\n              \"name\": \"ConfigurationProperty\", \"namespace\": \"config.system\", \"type\": \"record\", \"fields\": {\n                \"name\": \"name\", \"type\": [\"string\", {\n                  \"name\": \"__uuid\", \"type\": [\"name\": \"uuidT\", \"type\": \"fixed\", \"size\": 16, \"namespace\": \"org.kaaproject.configuration\"}]}], \"org.kaaproject.configuration.uuidT\"}], \"symbols\": [\"reset\"], \"name\": \"resetT\", \"type\": \"enum\", \"namespace\": \"org.kaaproject.configuration\", \"org.kaaproject.configuration.unchangedT\"}], {\n                  \"name\": \"__uuid\", \"type\": \"org.kaaproject.configuration.uuidT\"}]}], \"config.system.ConfigurationProperty\"}], \"namespace\": \"org.kaaproject.configuration\", \"type\": \"array\"\",
    \"schema\": \"{\\r\\n      \\type\\: \\record\\,\\r\\n      \\name\\: \\\"ConfigurationSchema\\\",\\r\\n      \\namespace\\: \\org.kaa.config\\,\\r\\n      \\fields\\: {\\r\\n        {\\r\\n          \\name\\: \\Properties\\,\\r\\n          \\type\\: {\\r\\n            \\type\\: \\array\\,\\r\\n            \\items\\: {\\r\\n              \\name\\: \\ConfigurationProperty\\,\\r\\n              \\namespace\\: \\config.system\\,\\r\\n              \\type\\: \\record\\,\\r\\n              \\fields\\: {\\r\\n                {\\r\\n                  \\name\\: \\name\\,\\r\\n                  \\type\\: \\string\\,\\r\\n                  \\name\\: \\value\\,\\r\\n                  \\type\\: \\string\\,\\r\\n                }\\r\\n              }\\r\\n            }\\r\\n          }\\r\\n        }\\r\\n      }\\r\\n    }\\r\\n  }\",
    \"status\": null
  }
}
]

```

## Get configuration schema

Returns a configuration schema by configuration schema ID. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to perform this operation.

- **URL**  
/kaaAdmin/rest/api/configurationSchema/{configurationSchemaId}

- **Method:**  
GET

- **URL params**

Parameter	Value	Description
configurationSchemaId	string	the ID of the configuration schema

- **Data params**

None

- **Success response:**

- **Code: 200**
  - **Example:**

```

{
  "applicationId": "71",
  "baseSchema": "{\n  \"type\": \"record\", \"name\": \"ConfigurationSchema\", \"namespace\": \"org.kaa.config\", \"fields\": {\n    \"name\": \"Properties\", \"type\": {\n      \"type\": \"array\", \"items\": {\n        \"name\": \"ConfigurationProperty\", \"namespace\": \"config.system\", \"type\": \"record\", \"fields\": {\n          \"name\": \"name\", \"type\": \"string\", {\n            \"name\": \"value\", \"type\": \"string\", {\n              \"name\": \"__uuid\", \"type\": {\n                \"name\": \"uuidT\", \"type\": \"fixed\", \"size\": 16, \"namespace\": \"org.kaaproject.configuration\", \"null\"}]}]}], {\n            \"name\": \"__uuid\", \"type\": [\"org.kaaproject.configuration.uuidT\", \"null\"}]}]}], {\n            \"name\": \"__uuid\", \"type\": \"org.kaaproject.configuration.uuidT\", \"null\"}]}]}\",
    \"createdTime\": 1408638999001,
  }
}

```

```

    "createdUsername": "admin",
    "description": null,
    "endpointCount": 0,
    "id": "94",
    "majorVersion": 1,
    "minorVersion": 0,
    "name": "Generated",
    "overrideSchema": "{\n  \"type\": \"record\", \"name\": \"ConfigurationSchema\", \"namespace\":\n  \\\"org.kaa.config\\\", \"fields\": [{\n    \"name\": \"Properties\", \"type\": [{\n      \"type\": \"array\", \"\n      items\": {\n        \"name\": \"ConfigurationProperty\", \"namespace\": \"config.system\", \"type\": \"\n        record\", \"fields\": [{\n          \"name\": \"name\", \"type\": [\"string\", {\n            \"symbols\": [\"unchanged\"]\n          },\n          \"name\": \"unchangedT\", \"type\": \"enum\", \"namespace\": \"org.kaaproject.configuration\"}],\n          {\n            \"name\": \"value\", \"type\": [\"string\", \"org.kaaproject.configuration.unchangedT\"]\n          },\n          {\n            \"name\": \"__uuid\", \"type\": [{\n              \"name\": \"uuidT\", \"type\": \"fixed\", \"size\": 16,\n              \"namespace\": \"org.kaaproject.configuration\", \"null\": []\n            }], \"org.kaaproject.configuration.unchangedT\"}],\n          {\n            \"name\": \"__uuid\", \"type\": [\"org.kaaproject.configuration.uuidT\", \"\n            null\"]\n          }]\n        }\n      },\n      \"protocolSchema\": \"{\n        \"items\": {\n          \"name\": \"deltaT\", \"type\": \"record\", \"fields\": [{\n            \"name\": \"delta\", \"type\": [{\n              \"type\": \"record\", \"name\": \"ConfigurationSchema\", \"\n              namespace\": \"org.kaa.config\", \"fields\": [{\n                \"name\": \"Properties\", \"type\": [{\n                  \"type\": \"\n                  array\", \"items\": [{\n                    \"name\": \"ConfigurationProperty\", \"namespace\": \"config.system\", \"\n                    type\": \"record\", \"fields\": [{\n                      \"name\": \"name\", \"type\": [\"string\", {\n                        \"symbols\": [\"\n                        unchanged\"]\n                      },\n                      \"name\": \"unchangedT\", \"type\": \"enum\", \"namespace\": \"org.kaaproject.\n                      configuration\"}],\n                      {\n                        \"name\": \"value\", \"type\": [\"string\", \"org.kaaproject.configuration.\n                        unchangedT\"]\n                      },\n                      {\n                        \"name\": \"__uuid\", \"type\": [{\n                          \"name\": \"uuidT\", \"type\": \"fixed\", \"\n                          size\": 16, \"namespace\": \"org.kaaproject.configuration\"}],\n                          \"org.kaaproject.configuration.\n                          uuidT\"}],\n                      {\n                        \"symbols\": [\"reset\"], \"name\": \"resetT\", \"type\": \"enum\", \"namespace\": \"\n                        org.kaaproject.configuration\", \"org.kaaproject.configuration.unchangedT\"}],\n                      {\n                        \"name\": \"\n                        __uuid\", \"type\": [\"org.kaaproject.configuration.uuidT\"]\n                      }], \"config.system.\n                      ConfigurationProperty\"}], \"namespace\": \"org.kaaproject.configuration\", \"type\": \"\n                      array\"}\n                    },\n                    \"schema\": \"{\r\n      \"type\": \"record\", \r\n      \"name\": \"ConfigurationSchema\", \r\n      \"namespace\": \"org.kaa.config\", \r\n      \"fields\": [\r\n        {\r\n          \"name\": \"Properties\", \r\n          \"type\": {\r\n            \"type\": \"array\", \r\n            \"items\": {\r\n              \"name\": \"ConfigurationProperty\", \r\n              \"namespace\": \"config.system\", \r\n              \"type\":\n              \"record\", \r\n              \"fields\": [\r\n                {\r\n                  \"name\": \"name\", \r\n                  \"\n                  type\": \"string\" \r\n                }, \r\n                {\r\n                  \"name\": \"value\", \r\n                  \"\n                  type\": \"string\" \r\n                } \r\n              ] \r\n            } \r\n          } \r\n        } \r\n      ] \r\n    },\n    \"status\": null\n  }\n}

```

• **Error response:**

Status codes	Description
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application associated with the configuration schema does not match the Tenant ID of the authenticated user
404 Not Found	Configuration schema with the specified configurationSchemald does not exist
500 Internal Server Error	Unexpected error occurred on the server side

• **Sample call:**

```

curl -v -S -u devuser:devuser123 -X GET "http://localhost:8080/kaaAdmin/rest/api/configurationSchema/94" | python -mjson.tool

```

```

{
  "applicationId": "71",
  "baseSchema": "{ \"type\": \"record\", \"name\": \"ConfigurationSchema\", \"namespace\": \"org.kaa.config\", \"fields\": [{ \"name\": \"Properties\", \"type\": { \"type\": \"array\", \"items\": { \"name\": \"ConfigurationProperty\", \"namespace\": \"config.system\", \"type\": \"record\", \"fields\": [{ \"name\": \"name\", \"type\": \"string\" }, { \"name\": \"value\", \"type\": \"string\" }, { \"name\": \"__uuid\", \"type\": { \"name\": \"uuidT\", \"type\": \"fixed\", \"size\": 16, \"namespace\": \"org.kaaproject.configuration\" }, \"null\": \"\" } ] } } ], { \"name\": \"__uuid\", \"type\": { \"name\": \"uuidT\", \"type\": \"fixed\", \"size\": 16, \"namespace\": \"org.kaaproject.configuration\" }, \"null\": \"\" } ] }",
  "createdTime": 140863899001,
  "createdUsername": "admin",
  "description": null,
  "endpointCount": 0,
  "id": "94",
  "majorVersion": 1,
  "minorVersion": 0,
  "name": "Generated",
  "overrideSchema": "{ \"type\": \"record\", \"name\": \"ConfigurationSchema\", \"namespace\": \"org.kaa.config\", \"fields\": [{ \"name\": \"Properties\", \"type\": { \"type\": \"array\", \"items\": { \"name\": \"ConfigurationProperty\", \"namespace\": \"config.system\", \"type\": \"record\", \"fields\": [{ \"name\": \"name\", \"type\": [ \"string\", { \"symbols\": [ \"unchanged\" ], \"name\": \"unchangedT\", \"type\": \"enum\", \"namespace\": \"org.kaaproject.configuration\" } ] }, { \"name\": \"value\", \"type\": [ \"string\", \"org.kaaproject.configuration.unchangedT\" ] }, { \"name\": \"__uuid\", \"type\": { \"name\": \"uuidT\", \"type\": \"fixed\", \"size\": 16, \"namespace\": \"org.kaaproject.configuration\" }, \"null\": \"\" } ] } }, { \"name\": \"__uuid\", \"type\": { \"name\": \"uuidT\", \"type\": \"fixed\", \"size\": 16, \"namespace\": \"org.kaaproject.configuration\" }, \"null\": \"\" } ] }",
  "protocolSchema": "{ \"items\": { \"name\": \"deltaT\", \"type\": \"record\", \"fields\": [{ \"name\": \"delta\", \"type\": { \"type\": \"record\", \"name\": \"ConfigurationSchema\", \"namespace\": \"org.kaa.config\", \"fields\": [{ \"name\": \"Properties\", \"type\": { \"type\": \"array\", \"items\": { \"name\": \"ConfigurationProperty\", \"namespace\": \"config.system\", \"type\": \"record\", \"fields\": [{ \"name\": \"name\", \"type\": [ \"string\", { \"symbols\": [ \"unchanged\" ], \"name\": \"unchangedT\", \"type\": \"enum\", \"namespace\": \"org.kaaproject.configuration\" } ] }, { \"name\": \"value\", \"type\": [ \"string\", \"org.kaaproject.configuration.unchangedT\" ] }, { \"name\": \"__uuid\", \"type\": { \"name\": \"uuidT\", \"type\": \"fixed\", \"size\": 16, \"namespace\": \"org.kaaproject.configuration\" } } ] }, { \"symbols\": [ \"reset\" ], \"name\": \"resetT\", \"type\": \"enum\", \"namespace\": \"org.kaaproject.configuration\" }, { \"name\": \"__uuid\", \"type\": { \"name\": \"uuidT\", \"type\": \"fixed\", \"size\": 16, \"namespace\": \"org.kaaproject.configuration\" } } ] }, { \"name\": \"__uuid\", \"type\": { \"name\": \"uuidT\", \"type\": \"fixed\", \"size\": 16, \"namespace\": \"org.kaaproject.configuration\" } } ] }, { \"name\": \"__uuid\", \"type\": { \"name\": \"uuidT\", \"type\": \"fixed\", \"size\": 16, \"namespace\": \"org.kaaproject.configuration\" } } ] }, { \"name\": \"__uuid\", \"type\": { \"name\": \"uuidT\", \"type\": \"fixed\", \"size\": 16, \"namespace\": \"org.kaaproject.configuration\" } } ] }",
  "schema": "{\r\n  \"type\": \"record\", \r\n  \"name\": \"ConfigurationSchema\", \r\n  \"namespace\": \"org.kaa.config\", \r\n  \"fields\": [\r\n    {\r\n      \"name\": \"Properties\", \r\n      \"type\": {\r\n        \"type\": \"array\", \r\n        \"items\": {\r\n          \"name\": \"ConfigurationProperty\", \r\n          \"namespace\": \"config.system\", \r\n          \"type\": \"record\", \r\n          \"fields\": [\r\n            {\r\n              \"name\": \"name\", \r\n              \"type\": \"string\", \r\n              \"value\": \"value\", \r\n              \"type\": \"string\", \r\n              \"__uuid\": \"__uuid\", \r\n              \"type\": \"fixed\", \r\n              \"size\": 16, \r\n              \"namespace\": \"org.kaaproject.configuration\" \r\n            }, \r\n            {\r\n              \"name\": \"__uuid\", \r\n              \"type\": \"fixed\", \r\n              \"size\": 16, \r\n              \"namespace\": \"org.kaaproject.configuration\" \r\n            } \r\n          ] \r\n        } \r\n      } \r\n    }, \r\n    {\r\n      \"name\": \"__uuid\", \r\n      \"type\": \"fixed\", \r\n      \"size\": 16, \r\n      \"namespace\": \"org.kaaproject.configuration\" \r\n    } \r\n  ] \r\n}",
  "status": null
}

```

## Create configuration schema

Uploads a configuration schema. A unique version number will be generated (incrementally) for the uploaded schema, and the createUsername field of the schema will be set to the name of the user who uploaded it. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to perform this operation.

- **URL**  
/kaaAdmin/rest/api/configurationSchema
- **Method:**  
POST
- **URL params**  
None
- **Data params**  
Multipart/form-data encoding. Fields:

**Example:**

```
{ "applicationId": "71", "name": "Test configuration schema", "description": "Configuration Schema Description" }
```

**File contents example:**

```
{
  "type": "record",
  "name": "TestConfigurationSchema",
  "namespace": "org.kaa.config.test",
  "fields": [
    {
      "name": "Properties",
      "type": {
        "type": "array",
        "items": {
          "name": "ConfigurationProperty",
          "namespace": "config.system",
          "type": "record",
          "fields": [
            {
              "name": "name",
              "type": "string"
            },
            {
              "name": "value",
              "type": "string"
            }
          ]
        }
      }
    }
  ]
}
```

- **Success response:**

- **Code:** 200
- **Example:**

```
{
  "applicationId": "71",
  "baseSchema": "{ \"type\": \"record\", \"name\": \"TestConfigurationSchema\", \"namespace\": \"org.kaa.config.test\", \"fields\": [{ \"name\": \"Properties\", \"type\": { \"type\": \"array\", \"items\": { \"name\": \"ConfigurationProperty\", \"namespace\": \"config.system\", \"type\": \"record\", \"fields\": [{ \"name\": \"name\", \"type\": \"string\" }, { \"name\": \"value\", \"type\": \"string\" }, { \"name\": \"__uuid\", \"type\": { \"name\": \"uuidT\", \"type\": \"fixed\", \"size\": 16, \"namespace\": \"org.kaaproject.configuration\" }, \"null\": \"\" } ] } }, { \"name\": \"__uuid\", \"type\": [ \"org.kaaproject.configuration.uuidT\", \"null\" ] } ] }\",
  "createdTime": 1408705295749,
  "createdUsername": "devuser",
  "description": "Configuration Schema Description",
  "endpointCount": 0,
  "id": "96",
  "majorVersion": 2,
  "minorVersion": 0,
  "name": "Test configuration schema",
  "overrideSchema": "{ \"type\": \"record\", \"name\": \"TestConfigurationSchema\", \"namespace\": \"org.kaa.config.test\", \"fields\": [{ \"name\": \"Properties\", \"type\": { \"type\": \"array\", \"items\": { \"name\": \"ConfigurationProperty\", \"namespace\": \"config.system\", \"type\": \"record\", \"fields\": [{ \"name\": \"name\", \"type\": \"string\", \"symbols\": [ \"unchanged\" ], \"name\": \"unchangedT\", \"type\": \"enum\", \"namespace\": \"org.kaaproject.configuration\" } ] }, { \"name\": \"value\", \"type\": [ \"string\", \"org.kaaproject.configuration.unchangedT\" ] }, { \"name\": \"__uuid\", \"type\": { \"name\": \"uuidT\", \"type\": \"fixed\", \"size\": 16, \"namespace\": \"org.kaaproject.configuration\" }, \"null\": \"\" } ] } }, { \"name\": \"__uuid\", \"type\": [ \"org.kaaproject.configuration.unchangedT\", \"null\" ] } ] }\",
  "null": ""
}
```

```

    "protocolSchema": "{\n  \"items\": {\n    \"name\": \"deltaT\", \"type\": \"record\", \"fields\": [\n      {\n        \"name\": \"delta\", \"type\": [\n          {\n            \"type\": \"record\", \"name\": \"TestConfigurationSchema\", \"namespace\": \"org.kaa.config.test\", \"fields\": [\n              {\n                \"name\": \"Properties\", \"type\": [\n                  {\n                    \"type\": \"array\", \"items\": [\n                      {\n                        \"name\": \"ConfigurationProperty\", \"namespace\": \"config.system\", \"type\": \"record\", \"fields\": [\n                          {\n                            \"name\": \"name\", \"type\": [\"string\", {\n                              \"symbols\": [\"unchanged\"], \"name\": \"unchangedT\", \"type\": \"enum\", \"namespace\": \"org.kaaproject.configuration\"}]\n                        }, {\n                          \"name\": \"value\", \"type\": [\"string\", \"org.kaaproject.configuration.unchangedT\"]\n                        }, {\n                          \"name\": \"__uuid\", \"type\": {\n                            \"name\": \"uuidT\", \"type\": \"fixed\", \"size\": 16, \"namespace\": \"org.kaaproject.configuration\"}]\n                        }, {\n                          \"symbols\": [\"reset\"], \"name\": \"resetT\", \"type\": \"enum\", \"namespace\": \"org.kaaproject.configuration\", \"org.kaaproject.configuration.unchangedT\"]\n                        }, {\n                          \"name\": \"__uuid\", \"type\": \"org.kaaproject.configuration.uuidT\"]\n                        }, {\n                          \"symbols\": [\"reset\"], \"name\": \"resetT\", \"type\": \"enum\", \"namespace\": \"org.kaaproject.configuration\", \"org.kaaproject.configuration.unchangedT\"]\n                        }, {\n                          \"name\": \"__uuid\", \"type\": \"org.kaaproject.configuration.uuidT\"]\n                        }\n                      }\n                    ]\n                  }\n                }\n              }\n            ]\n          }\n        }\n      }\n    ]\n  },\n  \"schema\": {\n    \"type\": \"record\", \"name\": \"TestConfigurationSchema\", \"namespace\": \"org.kaa.config.test\", \"fields\": [\n      {\n        \"name\": \"Properties\", \"type\": {\n          \"type\": \"array\", \"items\": {\n            \"name\": \"ConfigurationProperty\", \"namespace\": \"config.system\", \"type\": \"record\", \"fields\": [\n              {\n                \"name\": \"name\", \"type\": [\"string\", {\n                  \"symbols\": [\"unchanged\"], \"name\": \"unchangedT\", \"type\": \"enum\", \"namespace\": \"org.kaaproject.configuration\"}]\n                }, {\n                  \"name\": \"value\", \"type\": [\"string\", \"org.kaaproject.configuration.unchangedT\"]\n                }, {\n                  \"name\": \"__uuid\", \"type\": {\n                    \"name\": \"uuidT\", \"type\": \"fixed\", \"size\": 16, \"namespace\": \"org.kaaproject.configuration\"}]\n                }, {\n                  \"symbols\": [\"reset\"], \"name\": \"resetT\", \"type\": \"enum\", \"namespace\": \"org.kaaproject.configuration\", \"org.kaaproject.configuration.unchangedT\"]\n                }, {\n                  \"name\": \"__uuid\", \"type\": \"org.kaaproject.configuration.uuidT\"]\n                }\n              }\n            ]\n          }\n        }\n      }\n    ]\n  },\n  \"status\": null\n}\n}

```

- **Error response:**

Status codes	Description
400 Bad Request	Specified configuration schema is not a valid avro schema
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application associated with the configuration schema does not match the Tenant ID of the authenticated user
404 Not Found	File with a schema not found in the form data
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```

curl -v -S -u devuser:devuser123 -F'configurationSchema={"applicationId":"71","name":"Test configuration schema","description":"Configuration Schema Description"};type=application/json' -F file=@configuration_schema.json "http://localhost:8080/kaaAdmin/rest/api/configurationSchema" | python -mjson.tool

```

```

{
  "applicationId": "71",
  "baseSchema": "{\n  \"type\": \"record\", \"name\": \"TestConfigurationSchema\", \"namespace\": \"org.kaa.config.test\", \"fields\": [\n    {\n      \"name\": \"Properties\", \"type\": [\n        {\n          \"type\": \"array\", \"items\": [\n            {\n              \"name\": \"ConfigurationProperty\", \"namespace\": \"config.system\", \"type\": \"record\", \"fields\": [\n                {\n                  \"name\": \"name\", \"type\": [\"string\", {\n                    \"symbols\": [\"unchanged\"], \"name\": \"unchangedT\", \"type\": \"enum\", \"namespace\": \"org.kaaproject.configuration\"}]\n                }, {\n                  \"name\": \"value\", \"type\": [\"string\", \"org.kaaproject.configuration.unchangedT\"]\n                }, {\n                  \"name\": \"__uuid\", \"type\": {\n                    \"name\": \"uuidT\", \"type\": \"fixed\", \"size\": 16, \"namespace\": \"org.kaaproject.configuration\"}]\n                }, {\n                  \"symbols\": [\"reset\"], \"name\": \"resetT\", \"type\": \"enum\", \"namespace\": \"org.kaaproject.configuration\", \"org.kaaproject.configuration.unchangedT\"]\n                }, {\n                  \"name\": \"__uuid\", \"type\": \"org.kaaproject.configuration.uuidT\"]\n                }\n              }\n            ]\n          }\n        }\n      }\n    ]\n  },\n  \"createdTime\": 1408705295749,\n  \"createdUsername\": \"devuser\", \n  \"description\": \"Configuration Schema Description\",

```

```

    "endpointCount": 0,
    "id": "96",
    "majorVersion": 2,
    "minorVersion": 0,
    "name": "Test configuration schema",
    "overrideSchema": "{ \"type\": \"record\", \"name\": \"TestConfigurationSchema\", \"namespace\": \"org.kaa.config.test\", \"fields\": [{ \"name\": \"Properties\", \"type\": [{ \"type\": \"array\", \"items\": [{ \"name\": \"ConfigurationProperty\", \"namespace\": \"config.system\", \"type\": \"record\", \"fields\": [{ \"name\": \"name\", \"type\": [\"string\", { \"symbols\": [\"unchanged\"] }, \"name\": \"unchangedT\", \"type\": \"enum\", \"namespace\": \"org.kaaproject.configuration\"}], { \"name\": \"value\", \"type\": [\"string\", \"org.kaaproject.configuration.unchangedT\"] }, { \"name\": \"__uuid\", \"type\": [\"name\": \"uuidT\", \"type\": \"fixed\", \"size\": 16, \"namespace\": \"org.kaaproject.configuration\"], \"null\": \"\"]}], \"org.kaaproject.configuration.unchangedT\"}], { \"name\": \"__uuid\", \"type\": [\"org.kaaproject.configuration.uuidT\", \"null\"] } ] }\",
    "protocolSchema": "{ \"items\": { \"name\": \"deltaT\", \"type\": \"record\", \"fields\": [{ \"name\": \"delta\", \"type\": [\"type\": \"record\", \"name\": \"TestConfigurationSchema\", \"namespace\": \"org.kaa.config.test\", \"fields\": [{ \"name\": \"Properties\", \"type\": [{ \"type\": \"array\", \"items\": [{ \"name\": \"ConfigurationProperty\", \"namespace\": \"config.system\", \"type\": \"record\", \"fields\": [{ \"name\": \"name\", \"type\": [\"string\", { \"symbols\": [\"unchanged\"] }, \"name\": \"unchangedT\", \"type\": \"enum\", \"namespace\": \"org.kaaproject.configuration\"}], { \"name\": \"value\", \"type\": [\"string\", \"org.kaaproject.configuration.unchangedT\"] }, { \"name\": \"__uuid\", \"type\": [\"name\": \"uuidT\", \"type\": \"fixed\", \"size\": 16, \"namespace\": \"org.kaaproject.configuration\"] } ]}], \"org.kaaproject.configuration.uuidT\"}], { \"symbols\": [\"reset\"], \"name\": \"resetT\", \"type\": \"enum\", \"namespace\": \"org.kaaproject.configuration\" }, \"org.kaaproject.configuration.unchangedT\" ], { \"name\": \"__uuid\", \"type\": \"org.kaaproject.configuration.uuidT\" } ] }, \"config.system.ConfigurationProperty\" ] }\", \"namespace\": \"org.kaaproject.configuration\" }, \"type\": \"array\" }\",
    "schema": "{ \n    \"type\": \"record\", \n    \"name\": \"TestConfigurationSchema\", \n    \"namespace\": \"org.kaa.config.test\", \n    \"fields\": [ \n        { \n            \"name\": \"Properties\", \n            \"type\": { \n                \"type\": \"array\", \n                \"items\": { \n                    \"name\": \"ConfigurationProperty\", \n                    \"namespace\": \"config.system\", \n                    \"type\": \"record\", \n                    \"fields\": [ \n                        { \n                            \"name\": \"name\", \n                            \"type\": \"string\" \n                        }, \n                        { \n                            \"name\": \"value\", \n                            \"type\": \"string\" \n                        } \n                    ] \n                } \n            } \n        } \n    ] \n    \"status\": null \n }

```

## Get configuration records

Returns all configuration records for the specified endpoint group. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to request this information.

- **URL**  
/kaaAdmin/rest/api/configurationRecords?endpointGroupIid&includeDeprecated

- **Method:**  
GET

- **URL params**

Parameter	Value	Description
endpointGroupIid	string	the ID of the endpoint group
includeDeprecated	string	[“true” or “false”] if “true”, all configuration records will be returned, including deprecated ones. If “false”, only active and inactive configuration records will be returned

- **Data params**

None

- **Success response:**

- **Code:** 200
  - **Example:**



```
[
  {
    "activeConfiguration": {
      "activatedTime": 1408705246553,
      "activatedUsername": "admin",
      "applicationId": "71",
      "body": "{\n\"Properties\":[\n,\"__uuid\":{\n\"org.kaaproject.configuration.uuidT\":\n\"k\u00ff\u00ca\u00f6\u00018\u00b5\u00bb\u00bcI\u00dc\u0094\u00acB\"}}",
      "createdTime": 1408705246535,
      "createdUsername": "admin",
      "deactivatedTime": 0,
      "deactivatedUsername": null,
      "description": "Generated",
      "endpointCount": 0,
      "endpointGroupId": "81",
      "id": "103",
      "lastModifyTime": 1408705246539,
      "majorVersion": 1,
      "minorVersion": 0,
      "modifiedUsername": null,
      "protocolSchema": "{\n\"items\":{\n\"name\":\n\"deltaT\", \"type\":\n\"record\", \"\nfields\":[\n{\n\"name\":\n\"delta\", \"type\":[\n\"type\":\n\"record\", \"name\":\n\"ConfigurationSchema\", \"namespace\":\n\"org.kaa.config\", \"fields\":[\n{\n\"name\":\n\"Properties\", \"type\":[\n\"type\":\n\"array\", \"items\":[\n{\n\"name\":\n\"ConfigurationProperty\", \"namespace\":\n\"config.system\", \"type\":\n\"record\", \"fields\":[\n{\n\"name\":\n\"name\", \"type\":[\n\"string\", \"symbols\":[\n\"unchanged\"], \"name\":\n\"unchangedT\", \"type\":\n\"enum\", \"namespace\":\n\"org.kaaproject.configuration\"}}], {\n\"name\":\n\"value\", \"type\":[\n\"string\", \"org.kaaproject.configuration.unchangedT\"}}], {\n\"name\":\n\"__uuid\", \"type\":{\n\"name\":\n\"uuidT\", \"type\":\n\"fixed\", \"size\":16, \"namespace\":\n\"org.kaaproject.configuration\"}}}], \"org.kaaproject.configuration.uuidT\"}}], {\n\"symbols\":[\n\"reset\"], \"name\":\n\"resetT\", \"type\":\n\"enum\", \"namespace\":\n\"org.kaaproject.configuration\"}, \"org.kaaproject.configuration.unchangedT\"}], {\n\"name\":\n\"__uuid\", \"type\":\n\"org.kaaproject.configuration.uuidT\"}}], \"config.system.ConfigurationProperty\"}}], \"namespace\":\n\"org.kaaproject.configuration\", \"type\":\n\"array\"}",
      "schemaId": "94",
      "sequenceNumber": 1,
      "status": "ACTIVE"
    },
    "inactiveConfiguration": null
  },
  {
    "activeConfiguration": {
      "activatedTime": 1408705295840,
      "activatedUsername": "devuser",
      "applicationId": "71",
      "body": "{\n\"Properties\":[\n,\"__uuid\":{\n\"org.kaaproject.configuration.uuidT\":\n\"\\rV\u00efRG\u009aC\u00fe\u00a9 5\u00d3S\u00d91A\"}}",
      "createdTime": 1408705295819,
      "createdUsername": "devuser",
      "deactivatedTime": 0,
      "deactivatedUsername": null,
      "description": "Generated",
      "endpointCount": 0,
      "endpointGroupId": "81",
      "id": "104",
      "lastModifyTime": 1408705295824,
      "majorVersion": 2,
      "minorVersion": 0,
      "modifiedUsername": null,
      "protocolSchema": "{\n\"items\":{\n\"name\":\n\"deltaT\", \"type\":\n\"record\", \"\nfields\":[\n{\n\"name\":\n\"delta\", \"type\":[\n\"type\":\n\"record\", \"name\":\n\"TestConfigurationSchema\", \"namespace\":\n\"org.kaa.config.test\", \"fields\":[\n{\n\"name\":\n\"Properties\", \"type\":[\n\"type\":\n\"array\", \"items\":[\n{\n\"name\":\n\"ConfigurationProperty\", \"namespace\":\n\"config.system\", \"type\":\n\"record\", \"fields\":[\n{\n\"name\":\n\"name\", \"type\":[\n\"string\", \"symbols\":[\n\"unchanged\"], \"name\":\n\"unchangedT\", \"type\":\n\"enum\", \"namespace\":\n\"org.kaaproject.configuration\"}}], {\n\"name\":\n\"value\", \"type\":[\n\"string\", \"org.kaaproject.configuration.unchangedT\"}}], {\n\"name\":\n\"__uuid\", \"type\":{\n\"name\":\n\"uuidT\", \"type\":\n\"fixed\", \"size\":16, \"namespace\":\n\"org.kaaproject.configuration\"}}}], \"org.kaaproject.configuration.uuidT\"}}], {\n\"symbols\":[\n\"reset\"], \"name\":\n\"resetT\", \"type\":\n\"enum\", \"namespace\":\n\"org.kaaproject.configuration\"}, \"org.kaaproject.configuration.unchangedT\"}], {\n\"name\":\n\"__uuid\", \"type\":\n\"org.kaaproject.configuration.
```

```

uuidT\}}],\"config.system.ConfigurationProperty\}}],\"namespace\": \"org.kaaproject.
configuration\", \"type\": \"array\"},
    \"schemaId\": \"96\",
    \"sequenceNumber\": 1,
    \"status\": \"ACTIVE\"
  },
  \"inactiveConfiguration\": null
},
{
  \"activeConfiguration\": {
    \"activatedTime\": 1408705339202,
    \"activatedUsername\": \"devuser\",
    \"applicationId\": \"71\",
    \"body\": \"{\\"Properties\\\": [], \\"__uuid\\\": {\"org.kaaproject.configuration.uuidT\\\":
\\+\\u0016r\\u00b8\\u00f7*Nt\\u0098+\\u001c'\\n\\u00f9\\u00e5\\u00cb\\}\"},
    \"createdTime\": 1408705339183,
    \"createdUsername\": \"devuser\",
    \"deactivatedTime\": 0,
    \"deactivatedUsername\": null,
    \"description\": \"Generated\",
    \"endpointCount\": 0,
    \"endpointGroupId\": \"81\",
    \"id\": \"105\",
    \"lastModifyTime\": 1408705339188,
    \"majorVersion\": 3,
    \"minorVersion\": 0,
    \"modifiedUsername\": null,
    \"protocolSchema\": \"{\\"items\\\": {\"name\\\": \"deltaT\", \"type\\\": \"record\", \"
fields\\\": [ {\"name\\\": \"delta\", \"type\\\": [ {\"type\\\": \"record\", \"name\\\": \"
TestConfigurationSchema\", \"namespace\\\": \"org.kaa.config.test\", \"fields\\\": [ {\"name\\\": \"
Properties\", \"type\\\": [ {\"type\\\": \"array\", \"items\\\": [ {\"name\\\": \"ConfigurationProperty\", \"
namespace\\\": \"config.system\", \"type\\\": \"record\", \"fields\\\": [ {\"name\\\": \"name\", \"type\\\":
[\"string\", {\"symbols\\\": [\"unchanged\"], \"name\\\": \"unchangedT\", \"type\\\": \"enum\", \"
namespace\\\": \"org.kaaproject.configuration\"} ] }, {\"name\\\": \"value\", \"type\\\": [\"string\", \"
org.kaaproject.configuration.unchangedT\" ] }, {\"name\\\": \"__uuid\", \"type\\\": {\"name\\\": \"
uuidT\", \"type\\\": \"fixed\", \"size\\\": 16, \"namespace\\\": \"org.kaaproject.configuration\"} ] } ] }, \"
org.kaaproject.configuration.uuidT\" ] }, {\"symbols\\\": [\"reset\"], \"name\\\": \"resetT\", \"
type\\\": \"enum\", \"namespace\\\": \"org.kaaproject.configuration\"}, \"org.kaaproject.
configuration.unchangedT\" ] }, {\"name\\\": \"__uuid\", \"type\\\": \"org.kaaproject.configuration.
uuidT\"} ] } ], \"config.system.ConfigurationProperty\}}], \"namespace\\\": \"org.kaaproject.
configuration\", \"type\\\": \"array\"},
    \"schemaId\": \"97\",
    \"sequenceNumber\": 1,
    \"status\": \"ACTIVE\"
  },
  \"inactiveConfiguration\": null
}
}
]

```

• **Error response:**

Status codes	Description
400 Bad Request	endpointGroupId parameter is empty
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application associated with the endpoint group does not match the Tenant ID of the authenticated user
404 Not Found	Endpoint group with the specified endpointGroupId does not exist
500 Internal Server Error	Unexpected error occurred on the server side

• **Sample call:**

```
curl -v -S -u devuser:devuser123 -X GET "http://localhost:8080/kaaAdmin/rest/api/configurationRecords?endpointGroupId=81&includeDeprecated=true" | python -mjson.tool
```

```
[
  {
    "activeConfiguration": {
      "activatedTime": 1408705246553,
      "activatedUsername": "admin",
      "applicationId": "71",
      "body": "{\"Properties\": [], \"__uuid\": {\"org.kaaproject.configuration.uuidT\": \"k\u00ff\u00ca\u00f6~OI\u0018\u00b5\u00bb\u00bcI\u00dc\u0094\u00acB\"}}",
      "createdTime": 1408705246535,
      "createdUsername": "admin",
      "deactivatedTime": 0,
      "deactivatedUsername": null,
      "description": "Generated",
      "endpointCount": 0,
      "endpointGroupId": "81",
      "id": "103",
      "lastModifyTime": 1408705246539,
      "majorVersion": 1,
      "minorVersion": 0,
      "modifiedUsername": null,
      "protocolSchema": "{\"items\": {\"name\": \"deltaT\", \"type\": \"record\", \"fields\": [{\"name\": \"delta\", \"type\": [{\"type\": \"record\", \"name\": \"ConfigurationSchema\", \"namespace\": \"org.kaa.config\", \"fields\": [{\"name\": \"Properties\", \"type\": [{\"type\": \"array\", \"items\": [{\"name\": \"ConfigurationProperty\", \"namespace\": \"config.system\", \"type\": \"record\", \"fields\": [{\"name\": \"name\", \"type\": [\"string\", {\"symbols\": [\"unchanged\"], \"name\": \"unchangedT\", \"type\": \"enum\", \"namespace\": \"org.kaaproject.configuration\"}], {\"name\": \"value\", \"type\": [\"string\", \"org.kaaproject.configuration.unchangedT\"], {\"name\": \"__uuid\", \"type\": {\"name\": \"uuidT\", \"type\": \"fixed\", \"size\": 16, \"namespace\": \"org.kaaproject.configuration\"}]}], \"org.kaaproject.configuration.uuidT\"}], {\"symbols\": [\"reset\"], \"name\": \"resetT\", \"type\": \"enum\", \"namespace\": \"org.kaaproject.configuration\"}, \"org.kaaproject.configuration.unchangedT\"], {\"name\": \"__uuid\", \"type\": \"org.kaaproject.configuration.uuidT\"}], \"config.system.ConfigurationProperty\"}], \"namespace\": \"org.kaaproject.configuration\", \"type\": \"array\"}",
      "schemaId": "94",
      "sequenceNumber": 1,
      "status": "ACTIVE"
    },
    "inactiveConfiguration": null
  },
  {
    "activeConfiguration": {
      "activatedTime": 1408705295840,
      "activatedUsername": "devuser",
      "applicationId": "71",
      "body": "{\"Properties\": [], \"__uuid\": {\"org.kaaproject.configuration.uuidT\": \"\rV\u00efRG\u009aC\u00fe\u00a9 5\u00d3S\u00d91A\"}}",
      "createdTime": 1408705295819,
      "createdUsername": "devuser",
      "deactivatedTime": 0,
      "deactivatedUsername": null,
      "description": "Generated",
      "endpointCount": 0,
      "endpointGroupId": "81",
      "id": "104",
      "lastModifyTime": 1408705295824,
      "majorVersion": 2,
      "minorVersion": 0,
      "modifiedUsername": null,
      "protocolSchema": "{\"items\": {\"name\": \"deltaT\", \"type\": \"record\", \"fields\": [{\"name\": \"delta\", \"type\": [{\"type\": \"record\", \"name\": \"TestConfigurationSchema\", \"namespace\": \"org.kaa.config.test\", \"fields\": [{\"name\": \"Properties\", \"type\": [{\"type\": \"array\", \"items\": [{\"name\": \"ConfigurationProperty\", \"namespace\": \"config.system\", \"type\": \"record\", \"fields\": [{\"name\": \"name\", \"type\": [\"string\", {\"symbols\": [\"unchanged\"], \"name\": \"unchangedT\", \"type\": \"enum\", \"namespace\": \"org.kaaproject.configuration\"}], {\"name\": \"value\", \"type\": [\"string\", \"org.kaaproject.configuration.unchangedT\"], {\"name\": \"__uuid\", \"type\": {\"name\": \"uuidT\", \"type\": \"fixed\", \"size\": 16, \"namespace\": \"org.kaaproject.configuration\"}]}], \"org.kaaproject.configuration.uuidT\"}], {\"symbols\": [\"reset\"], \"name\": \"
```

```

resetT\", \"type\": \"enum\", \"namespace\": \"org.kaaproject.configuration\"}, \"org.kaaproject.
configuration.unchangedT\" ]}, {\"name\": \"__uuid\", \"type\": \"org.kaaproject.configuration.
uuidT\" }}, \"config.system.ConfigurationProperty\" ]}], \"namespace\": \"org.kaaproject.
configuration\"}, \"type\": \"array\"\",
    \"schemaId\": \"96\",
    \"sequenceNumber\": 1,
    \"status\": \"ACTIVE\"
  },
  \"inactiveConfiguration\": null
},
{
  \"activeConfiguration\": {
    \"activatedTime\": 1408705339202,
    \"activatedUsername\": \"devuser\",
    \"applicationId\": \"71\",
    \"body\": \"{\\\"Properties\\\": [], \\\"__uuid\\\": {\\\"org.kaaproject.configuration.uuidT\\\": \\\"
+\\u0016r\\u00b8\\u00f7*Nt\\u0098+\\u001C'\\n\\u00f9\\u00e5\\u00cb\\\"}}\",
    \"createdTime\": 1408705339183,
    \"createdUsername\": \"devuser\",
    \"deactivatedTime\": 0,
    \"deactivatedUsername\": null,
    \"description\": \"Generated\",
    \"endpointCount\": 0,
    \"endpointGroupId\": \"81\",
    \"id\": \"105\",
    \"lastModifyTime\": 1408705339188,
    \"majorVersion\": 3,
    \"minorVersion\": 0,
    \"modifiedUsername\": null,
    \"protocolSchema\": \"{\\\"items\\\": {\\\"name\\\": \\\"deltaT\", \\\"type\\\": \\\"record\\\", \\\"fields\\\": [{\\\"
name\\\": \\\"delta\\\", \\\"type\\\": [{\\\"type\\\": \\\"record\\\", \\\"name\\\": \\\"TestConfigurationSchema\\\", \\\"namespace\\\":
\\\"org.kaa.config.test\\\", \\\"fields\\\": [{\\\"name\\\": \\\"Properties\\\", \\\"type\\\": [{\\\"type\\\": \\\"array\\\", \\\"
items\\\": [{\\\"name\\\": \\\"ConfigurationProperty\\\", \\\"namespace\\\": \\\"config.system\\\", \\\"type\\\": \\\"record\\\", \\\"
fields\\\": [{\\\"name\\\": \\\"name\\\", \\\"type\\\": [\\\"string\\\", {\\\"symbols\\\": [\\\"unchanged\\\"]}, \\\"name\\\": \\\"
unchangedT\\\", \\\"type\\\": \\\"enum\\\", \\\"namespace\\\": \\\"org.kaaproject.configuration\\\" ]}], {\\\"name\\\": \\\"
value\\\", \\\"type\\\": [\\\"string\\\", \\\"org.kaaproject.configuration.unchangedT\\\"]}, {\\\"name\\\": \\\"__uuid\\\", \\\"
type\\\": {\\\"name\\\": \\\"uuidT\\\", \\\"type\\\": \\\"fixed\\\", \\\"size\\\": 16, \\\"namespace\\\": \\\"org.kaaproject.
configuration\\\" } }], \\\"org.kaaproject.configuration.uuidT\\\" ]}, {\\\"symbols\\\": [\\\"reset\\\"], \\\"name\\\": \\\"
resetT\\\", \\\"type\\\": \\\"enum\\\", \\\"namespace\\\": \\\"org.kaaproject.configuration\\\"}, \\\"org.kaaproject.
configuration.unchangedT\\\" ]}, {\\\"name\\\": \\\"__uuid\\\", \\\"type\\\": \\\"org.kaaproject.configuration.
uuidT\\\" }}, \\\"config.system.ConfigurationProperty\\\" ]}], \\\"namespace\\\": \\\"org.kaaproject.
configuration\\\", \\\"type\\\": \\\"array\\\"\",
    \"schemaId\": \"97\",
    \"sequenceNumber\": 1,
    \"status\": \"ACTIVE\"
  },
  \"inactiveConfiguration\": null
}
]

```

## Get configuration record

Returns the configuration record for the specified endpoint group and configuration schema. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to request this information.

- **URL**  
/kaaAdmin/rest/api/configurationRecord?schemald&endpointGroupld

- **Method:**  
GET

- **URL params**

Parameter	Value	Description
schemald	string	the ID of the configuration schema
endpointGroupld	string	the ID of the endpoint group

- **Data params**

None

- **Success response:**

- **Code: 200**
  - **Example:**

```
{
  "activeConfiguration": {
    "activatedTime": 1408705339202,
    "activatedUsername": "devuser",
    "applicationId": "71",
    "body": "{ \"Properties\": [], \"__uuid\": { \"org.kaaproject.configuration.uuidT\": \"
+\\u0016r\\u00b8\\u00f7*Nt\\u0098+\\u001C'\\n\\u00f9\\u00e5\\u00cb\" } }",
    "createdTime": 1408705339183,
    "createdUsername": "devuser",
    "deactivatedTime": 0,
    "deactivatedUsername": null,
    "description": "Generated",
    "endpointCount": 0,
    "endpointGroupId": "81",
    "id": "105",
    "lastModifyTime": 1408705339188,
    "majorVersion": 3,
    "minorVersion": 0,
    "modifiedUsername": null,
    "protocolSchema": "{ \"items\": { \"name\": \"deltaT\", \"type\": \"record\", \"fields\":
[ { \"name\": \"delta\", \"type\": [ { \"type\": \"record\", \"name\": \"TestConfigurationSchema\", \"
namespace\": \"org.kaa.config.test\", \"fields\": [ { \"name\": \"Properties\", \"type\": [ { \"
type\": \"array\", \"items\": [ { \"name\": \"ConfigurationProperty\", \"namespace\": \"config.
system\", \"type\": \"record\", \"fields\": [ { \"name\": \"name\", \"type\": [ \"string\", { \"
symbols\": [ \"unchanged\", \"name\": \"unchangedT\", \"type\": \"enum\", \"namespace\": \"org.
kaaproject.configuration\" } ] }, { \"name\": \"value\", \"type\": [ \"string\", \"org.kaaproject.
configuration.unchangedT\" ] }, { \"name\": \"__uuid\", \"type\": { \"name\": \"uuidT\", \"type\": \"
fixed\", \"size\": 16, \"namespace\": \"org.kaaproject.configuration\" } } ] }, \"org.kaaproject.
configuration.uuidT\" } ], \"symbols\": [ \"reset\", \"name\": \"resetT\", \"type\": \"enum\", \"
namespace\": \"org.kaaproject.configuration\", \"org.kaaproject.configuration.unchangedT\" ] },
{ \"name\": \"__uuid\", \"type\": \"org.kaaproject.configuration.uuidT\" } ] }, \"config.system.
ConfigurationProperty\" ] }, \"namespace\": \"org.kaaproject.configuration\", \"type\": \"
array\" }",
    "schemaId": "97",
    "sequenceNumber": 1,
    "status": "ACTIVE"
  },
  "inactiveConfiguration": null
}
```

- **Error response:**

Status codes	Description
400 Bad Request	endpointGroupId parameter is empty
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application associated with the endpoint group does not match the Tenant ID of the authenticated user
404 Not Found	Endpoint group with the specified endpointGroupId does not exist or the endpoint group does not have the requested configuration record
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u devuser:devuser123 -X GET "http://localhost:8080/kaaAdmin/rest/api/configurationRecord?schemaId=97&endpointGroupId=81" | python -mjson.tool
```

```
{
  "activeConfiguration": {
    "activatedTime": 1408705339202,
    "activatedUsername": "devuser",
    "applicationId": "71",
    "body": "{ \"Properties\": [], \"__uuid\": { \"org.kaaproject.configuration.uuidT\": \"+\u0016r\u00b8\u00f7*Nt\u0098+\u001c'\u00f9\u00e5\u00cb\" } }",
    "createdTime": 1408705339183,
    "createdUsername": "devuser",
    "deactivatedTime": 0,
    "deactivatedUsername": null,
    "description": "Generated",
    "endpointCount": 0,
    "endpointGroupId": "81",
    "id": "105",
    "lastModifyTime": 1408705339188,
    "majorVersion": 3,
    "minorVersion": 0,
    "modifiedUsername": null,
    "protocolSchema": "{ \"items\": { \"name\": \"deltaT\", \"type\": \"record\", \"fields\": { \"name\": \"delta\", \"type\": [ { \"type\": \"record\", \"name\": \"TestConfigurationSchema\", \"namespace\": \"org.kaa.config.test\", \"fields\": { \"name\": \"Properties\", \"type\": [ { \"type\": \"array\", \"items\": [ { \"name\": \"ConfigurationProperty\", \"namespace\": \"config.system\", \"type\": \"record\", \"fields\": [ { \"name\": \"name\", \"type\": [ \"string\", { \"symbols\": [ \"unchanged\" ], \"name\": \"unchangedT\", \"type\": \"enum\", \"namespace\": \"org.kaaproject.configuration\" } ] }, { \"name\": \"value\", \"type\": [ \"string\", \"org.kaaproject.configuration.unchangedT\" ] }, { \"name\": \"__uuid\", \"type\": { \"name\": \"uuidT\", \"type\": \"fixed\", \"size\": 16, \"namespace\": \"org.kaaproject.configuration\" } } ] }, \"org.kaaproject.configuration.uuidT\" ] }, { \"symbols\": [ \"reset\" ], \"name\": \"resetT\", \"type\": \"enum\", \"namespace\": \"org.kaaproject.configuration\" }, \"org.kaaproject.configuration.unchangedT\" ] }, { \"name\": \"__uuid\", \"type\": \"org.kaaproject.configuration.uuidT\" } ] }, \"config.system.ConfigurationProperty\" ] }, \"namespace\": \"org.kaaproject.configuration\", \"type\": \"array\" }",
    "schemaId": "97",
    "sequenceNumber": 1,
    "status": "ACTIVE"
  },
  "inactiveConfiguration": null
}
```

## Get vacant configuration schemas

Returns all vacant (not being used by endpoint group configurations) configuration schemas for the specified endpoint group. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to request this information.

- **URL**  
/kaaAdmin/rest/api/vacantConfigurationSchemas?endpointGroupId

- **Method:**  
GET

- **URL params**

Parameter	Value	Description
endpointGroupId	string	the ID of the endpoint group

- **Data params**

None

- **Success response:**

- **Code:** 200

- **Example:**

```
[
  {
    "id": "94",
    "majorVersion": 1,
    "minorVersion": 0
  },
  {
    "id": "96",
    "majorVersion": 2,
    "minorVersion": 0
  },
  {
    "id": "97",
    "majorVersion": 3,
    "minorVersion": 0
  }
]
```

- **Error response:**

Status codes	Description
400 Bad Request	endpointGroupId parameter is empty
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application associated with the endpoint group does not match the Tenant ID of the authenticated user
404 Not Found	Endpoint group with the specified endpointGroupId does not exist
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u devuser:devuser123 -X GET "http://localhost:8080/kaaAdmin/rest/api/vacantConfigurationSchemas?endpointGroupId=83" | python -mjson.tool
```

```
[
  {
    "id": "94",
    "majorVersion": 1,
    "minorVersion": 0
  },
  {
    "id": "96",
    "majorVersion": 2,
    "minorVersion": 0
  },
  {
    "id": "97",
    "majorVersion": 3,
    "minorVersion": 0
  }
]
```

## Create/Edit configuration

Creates or updates a configuration. If a configuration with the specified ID does not exist, then it will be created and its createUsername field will be set to the name of the user who has uploaded it. If a configuration with the specified ID exists, the configuration will be updated and its modifyUsername will be set to the user who has submitted the request. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to perform this operation.

- **URL**  
/kaaAdmin/rest/api/configuration

- **Method:**  
POST

- **URL params**  
None

- **Data params**

**Example:**

```
{
  "applicationId": "71",
  "schemaId": "200",
  "endpointGroupId": "83",
  "majorVersion": "4",
  "minorVersion": "0",
  "description": "Test Configuration",
  "body": {
    "testField1": {
      "string": "abc"
    },
    "testField2": {
      "org.kaaproject.configuration.unchangedT": "unchanged",
      "__uuid": null
    },
    "status": "INACTIVE"
  }
}
```

- **Success response:**

- **Code:** 200
  - **Example:**

```
{
  "activatedTime": 0,
  "activatedUsername": null,
  "applicationId": "71",
  "body": {
    "testField1": {
      "string": "abc"
    },
    "testField2": {
      "org.kaaproject.configuration.unchangedT": "unchanged",
      "__uuid": "4\u001D\u0005\u001D\u00b5\u0094H\u00e0\u009e\u00b3\u00b0\u00d7I\u008d6"
    },
    "createdTime": 1408722949496,
    "createdUsername": "devuser",
    "deactivatedTime": 0,
    "deactivatedUsername": null,
    "description": "Test Configuration",
    "endpointCount": 0,
    "endpointGroupId": "83",
    "id": "109",
    "lastModifyTime": 1408722949504,
    "majorVersion": 4,
    "minorVersion": 0,
    "modifiedUsername": null,
    "protocolSchema": {
      "items": {
        "name": "deltaT",
        "type": "record",
        "fields": {
          "name": "delta",
          "type": {
            "name": "testT",
            "type": "record",
            "addressable": true,
            "fields": {
              "name": "testField1",
              "type": "string",
              "symbols": ["unchanged"],
              "name": "unchangedT",
              "type": "enum",
              "namespace": "org.kaaproject.configuration"
            },
            "by_default": "",
            "optional": true,
            "name": "testField2",
            "type": ["null"],
            "type": "record",
            "name": "testRecordT",
            "namespace": "org.kaa.config",
            "fields": {
              "name": "testField3",
              "type": "int",
              "org.kaaproject.configuration.unchangedT": ""
            },
            "name": "__uuid",
            "type": {
              "name": "uuidT",
              "type": "fixed",
              "size": 16,
              "namespace": "org.kaaproject.configuration"
            }
          },
          "org.kaaproject.configuration.unchangedT": "",
          "name": "__uuid",
          "type": "org.kaaproject.configuration.uuidT",
          "namespace": "org.kaa.config",
          "org.kaa.config.testRecordT": ""
        },
        "namespace": "org.kaaproject.configuration",
        "type": "array"
      },
      "schemaId": "200",
      "sequenceNumber": 0,
      "status": "INACTIVE"
    }
  }
}
```

- **Error response:**

Status codes	Description



401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application associated with the endpoint group does not match the Tenant ID of the authenticated user
404 Not Found	Endpoint group with the specified endpointGroupId does not exist or a configuration with the specified configurationId not found
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u devuser:devuser123 -X POST -H 'Content-Type: application/json' -d '{"applicationId": "71", "schemaId": "200", "endpointGroupId": "83", "majorVersion": "4", "minorVersion": "0", "description": "Test Configuration", "body": {"testField1": {"string": "abc"}, "testField2": {"org.kaaproject.configuration.unchangedT": "unchanged"}, "__uuid": null}, "status": "INACTIVE"}' "http://localhost:8080/kaaAdmin/rest/api/configuration" | python -mjson.tool
```

```
{
  "activatedTime": 0,
  "activatedUsername": null,
  "applicationId": "71",
  "body": {"testField1": {"string": "abc"}, "testField2": {"org.kaaproject.configuration.unchangedT": "unchanged"}, "__uuid": {"org.kaaproject.configuration.uuidT": "4\\u001D\\u0005\\u001D\\u00b5\\u0094H\\u00e0\\u009e\\u00b32\\u00b0\\u00d7I\\u008d6\\}"},
  "createdTime": 1408722949496,
  "createdUsername": "devuser",
  "deactivatedTime": 0,
  "deactivatedUsername": null,
  "description": "Test Configuration",
  "endpointCount": 0,
  "endpointGroupId": "83",
  "id": "109",
  "lastModifyTime": 1408722949504,
  "majorVersion": 4,
  "minorVersion": 0,
  "modifiedUsername": null,
  "protocolSchema": {"items": {"name": "deltaT", "type": "record", "fields": [{"name": "delta", "type": [{"name": "testT", "type": "record", "addressable": true, "fields": [{"name": "testField1", "type": [{"string": "unchanged"}], "name": "unchangedT", "type": "enum", "namespace": "org.kaaproject.configuration"}], "by_default": ""}, {"optional": true, "name": "testField2", "type": [{"null"}, {"type": "record", "name": "testRecordT", "namespace": "org.kaa.config", "fields": [{"name": "testField3", "type": [{"int", "org.kaaproject.configuration.unchangedT"}], "name": "__uuid", "type": {"name": "uuidT", "type": "fixed", "size": 16, "namespace": "org.kaaproject.configuration"}]}], "org.kaaproject.configuration.unchangedT"}], "name": "__uuid", "type": "org.kaaproject.configuration.uuidT"}], "namespace": "org.kaa.config", "org.kaa.config.testRecordT"}], "namespace": "org.kaaproject.configuration", "type": "array"},
  "schemaId": "200",
  "sequenceNumber": 0,
  "status": "INACTIVE"
}
```

## Activate configuration

Activates a configuration. Sets the status field of the configuration to ACTIVE, increments the sequenceNumber field value by 1, and sets the activateUsername and activatedTime fields to the name of the user who has submitted the request and the activation time, respectively. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to perform this operation.

- **URL**  
/kaaAdmin/rest/api/activateConfiguration
- **Method:**  
POST
- **URL params**

None

- **Data params**

- **Example:**

```
109
```

- **Success response:**

- **Code: 200**

- **Example:**

```
{
  "activatedTime": 1408723122998,
  "activatedUsername": "devuser",
  "applicationId": "71",
  "body": "{\"testField1\":{\"string\":\"abc\"},\"testField2\":{\"org.kaaproject.configuration.unchangedT\":\"unchanged\"},\"__uuid\":{\"org.kaaproject.configuration.uuidT\":\"4\\u001D\\u0005\\u001D\\u00b5\\u0094H\\u00e0\\u009e\\u00b32\\u00b0\\u00d7I\\u008d6\"}}",
  "createTime": 1408722949496,
  "createdUsername": "devuser",
  "deactivatedTime": 0,
  "deactivatedUsername": null,
  "description": "Test Configuration",
  "endpointCount": 0,
  "endpointGroupId": "83",
  "id": "109",
  "lastModifyTime": 1408722949504,
  "majorVersion": 4,
  "minorVersion": 0,
  "modifiedUsername": null,
  "protocolSchema": "{\"items\":{\"name\":\"deltaT\",\"type\":\"record\",\"fields\":{\"name\":\"delta\",\"type\":{\"name\":\"testT\",\"type\":\"record\",\"addressable\":true,\"fields\":{\"name\":\"testField1\",\"type\":{\"string\",\"symbols\":{\"unchanged\"},\"name\":\"unchangedT\",\"type\":\"enum\",\"namespace\":\"org.kaaproject.configuration\"}},\"by_default\":\"\"},{\"optional\":true,\"name\":\"testField2\",\"type\":{\"null\"},\"type\":\"record\",\"name\":\"testRecordT\",\"namespace\":\"org.kaa.config\",\"fields\":{\"name\":\"testField3\",\"type\":{\"int\",\"org.kaaproject.configuration.unchangedT\"}},\"name\":\"__uuid\",\"type\":{\"name\":\"uuidT\",\"type\":\"fixed\",\"size\":16,\"namespace\":\"org.kaaproject.configuration\"}}}],\"org.kaaproject.configuration.unchangedT\"}},\"name\":\"__uuid\",\"type\":\"org.kaaproject.configuration.uuidT\"}},\"namespace\":\"org.kaa.config\",\"org.kaa.config.testRecordT\"}},\"namespace\":\"org.kaaproject.configuration\"},\"type\":\"array\"},
  "schemaId": "200",
  "sequenceNumber": 1,
  "status": "ACTIVE"
}
```

- **Error response:**

Status codes	Description
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not required the role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application associated with the endpoint group does not match the Tenant ID of the authenticated user
404 Not Found	Configuration with the specified configurationId not found
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u devuser:devuser123 -X POST -H 'Content-Type: text/plain' -d'109' "http://localhost:8080/kaaAdmin/rest/api/activateConfiguration" | python -mjson.tool
```

```

{
  "activatedTime": 1408723122998,
  "activatedUsername": "devuser",
  "applicationId": "71",
  "body": "{ \"testField1\": { \"string\": \"abc\" }, \"testField2\": { \"org.kaaproject.configuration.
unchangedT\": \"unchanged\" }, \"__uuid\": { \"org.kaaproject.configuration.uuidT\": \"
4\\u001D\\u0005\\u001D\\u00b5\\u0094H\\u00e0\\u009e\\u00b32\\u00b0\\u00d7I\\u008d6\" } }",
  "createdTime": 1408722949496,
  "createdUsername": "devuser",
  "deactivatedTime": 0,
  "deactivatedUsername": null,
  "description": "Test Configuration",
  "endpointCount": 0,
  "endpointGroupId": "83",
  "id": "109",
  "lastModifyTime": 1408722949504,
  "majorVersion": 4,
  "minorVersion": 0,
  "modifiedUsername": null,
  "protocolSchema": "{ \"items\": { \"name\": \"deltaT\", \"type\": \"record\", \"fields\": [ { \"name\": \"
delta\", \"type\": [ { \"name\": \"testT\", \"type\": \"record\", \"addressable\": true, \"fields\": [ { \"
name\": \"testField1\", \"type\": [ \"string\", { \"symbols\": [ \"unchanged\" ], \"name\": \"unchangedT\", \"
type\": \"enum\", \"namespace\": \"org.kaaproject.configuration\" } ], \"by_default\": \"\" }, { \"
optional\": true, \"name\": \"testField2\", \"type\": [ \"null\", { \"type\": \"record\", \"name\": \"
testRecordT\", \"namespace\": \"org.kaa.config\", \"fields\": [ { \"name\": \"testField3\", \"type\": [ \"
int\", \"org.kaaproject.configuration.unchangedT\" ] }, { \"name\": \"__uuid\", \"type\": { \"name\": \"
uuidT\", \"type\": \"fixed\", \"size\": 16, \"namespace\": \"org.kaaproject.configuration\" } } ] }, \"org.
kaaproject.configuration.unchangedT\" ] }, { \"name\": \"__uuid\", \"type\": \"org.kaaproject.
configuration.uuidT\" } ], \"namespace\": \"org.kaa.config\", \"org.kaa.config.testRecordT\" ] } ], \"
namespace\": \"org.kaaproject.configuration\", \"type\": \"array\" }",
  "schemaId": "200",
  "sequenceNumber": 1,
  "status": "ACTIVE"
}

```

## Deactivate configuration

Deactivates a configuration. Sets the status field of the configuration to DEPRECATED, sets the deactivatedTime field value to the time of the deactivation request, and sets the deactivateUsername field to the name of the user who has submitted the request. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to perform this operation.

- **URL**  
/kaaAdmin/rest/api/deactivateConfiguration

- **Method:**  
POST

- **URL params**  
None

- **Data params**

**Example:**

```
109
```

- **Success response:**

- **Code:** 200
  - **Example:**

```

{
  "activatedTime": 1408723122998,
  "activatedUsername": "devuser",
  "applicationId": "71",
  "body": "{ \"testField1\": { \"string\": \"abc\" }, \"testField2\": { \"org.kaaproject.

```

```

configuration.unchangedT\":"\\"unchanged\\"},\\"__uuid\\":{\\"org.kaaproject.configuration.
uuidT\\":\"4\\u001D\\u0005\\u001D\\u00b5\\u0094H\\u00e0\\u009e\\u00b32\\u00b0\\u00d7I\\u008d6\\"}},
  \"createdTime\": 1408722949496,
  \"createdUsername\": \"devuser\",
  \"deactivatedTime\": 1408723248810,
  \"deactivatedUsername\": \"devuser\",
  \"description\": \"Test Configuration\",
  \"endpointCount\": 0,
  \"endpointGroupId\": \"83\",
  \"id\": \"109\",
  \"lastModifyTime\": 1408722949504,
  \"majorVersion\": 4,
  \"minorVersion\": 0,
  \"modifiedUsername\": null,
  \"protocolSchema\": \"{\\"items\\":{\\"name\\":\"deltaT\\\",\\\"type\\\":\"record\\\",\\\"fields\\\":[{\\"
name\\\":\"delta\\\",\\\"type\\\":[{\\"name\\\":\"testT\\\",\\\"type\\\":\"record\\\",\\\"addressable\\\":true,\\\"
fields\\\":[{\\"name\\\":\"testField1\\\",\\\"type\\\":[{\\"string\\\",{\\"symbols\\\":[{\\"unchanged\\\"},\\\"
name\\\":\"unchangedT\\\",\\\"type\\\":\"enum\\\",\\\"namespace\\\":\"org.kaaproject.configuration\\\"}],\\\"
by_default\\\":\"\\\"},{\\"optional\\\":true,\\\"name\\\":\"testField2\\\",\\\"type\\\":[{\\"null\\\",{\\"type\\\":
\\\"record\\\",\\\"name\\\":\"testRecordT\\\",\\\"namespace\\\":\"org.kaa.config\\\",\\\"fields\\\":[{\\"name\\\":
\\\"testField3\\\",\\\"type\\\":[\"int\\\",\\\"org.kaaproject.configuration.unchangedT\\\"]},{\\"name\\\":\"
__uuid\\\",\\\"type\\\":{\\"name\\\":\"uuidT\\\",\\\"type\\\":\"fixed\\\",\\\"size\\\":16,\\\"namespace\\\":\"org.
kaaproject.configuration\\\"}]}],\\\"org.kaaproject.configuration.unchangedT\\\"}],{\\"name\\\":\"
__uuid\\\",\\\"type\\\":\"org.kaaproject.configuration.uuidT\\\"}],\\\"namespace\\\":\"org.kaa.
config\\\",\\\"org.kaa.config.testRecordT\\\"]}],\\\"namespace\\\":\"org.kaaproject.configuration\\\"},
\\\"type\\\":\"array\\\"}\",
  \"schemaId\": \"200\",
  \"sequenceNumber\": 1,
  \"status\": \"DEPRECATED\"
}

```

- **Error response:**

Status codes	Description
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application associated with the endpoint group does not match the Tenant ID of the authenticated user
404 Not Found	Configuration with the specified configurationId not found
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```

curl -v -S -u devuser:devuser123 -X POST -H 'Content-Type: text/plain' -d'109' "http://localhost:8080
/kaaAdmin/rest/api/deactivateConfiguration" | python -mjson.tool

```

```

{
  \"activatedTime\": 1408723122998,
  \"activatedUsername\": \"devuser\",
  \"applicationId\": \"71\",
  \"body\": \"{\\"testField1\\\":{\\"string\\\":\"abc\\\"},\\\"testField2\\\":{\\"org.kaaproject.configuration.
unchangedT\\\":\"\\\"unchanged\\\"},\\"__uuid\\\":{\\"org.kaaproject.configuration.uuidT\\\":\"
4\\u001D\\u0005\\u001D\\u00b5\\u0094H\\u00e0\\u009e\\u00b32\\u00b0\\u00d7I\\u008d6\\"}}\",
  \"createdTime\": 1408722949496,
  \"createdUsername\": \"devuser\",
  \"deactivatedTime\": 1408723248810,
  \"deactivatedUsername\": \"devuser\",
  \"description\": \"Test Configuration\",
  \"endpointCount\": 0,
  \"endpointGroupId\": \"83\",
  \"id\": \"109\",
  \"lastModifyTime\": 1408722949504,

```

```

    "majorVersion": 4,
    "minorVersion": 0,
    "modifiedUsername": null,
    "protocolSchema": "{ \"items\": { \"name\": \"deltaT\", \"type\": \"record\", \"fields\": [ { \"name\": \"delta\", \"type\": [ { \"name\": \"testT\", \"type\": \"record\", \"addressable\": true, \"fields\": [ { \"name\": \"testField1\", \"type\": [ \"string\", { \"symbols\": [ \"unchanged\" ], \"name\": \"unchangedT\", \"type\": \"enum\", \"namespace\": \"org.kaaproject.configuration\" } ], \"by_default\": \"\" }, { \"optional\": true, \"name\": \"testField2\", \"type\": [ \"null\", { \"type\": \"record\", \"name\": \"testRecordT\", \"namespace\": \"org.kaa.config\", \"fields\": [ { \"name\": \"testField3\", \"type\": [ \"int\", \"org.kaaproject.configuration.unchangedT\" ] }, { \"name\": \"__uuid\", \"type\": { \"name\": \"uuidT\", \"type\": \"fixed\", \"size\": 16, \"namespace\": \"org.kaaproject.configuration\" } } ] }, \"org.kaaproject.configuration.unchangedT\" ] }, { \"name\": \"__uuid\", \"type\": \"org.kaaproject.configuration.uuidT\" } ], \"namespace\": \"org.kaa.config\", \"org.kaa.config.testRecordT\" } ] }, \"namespace\": \"org.kaaproject.configuration\", \"type\": \"array\" }\",
    \"schemaId\": \"200\",
    \"sequenceNumber\": 1,
    \"status\": \"DEPRECATED\"
  }

```

## Delete configuration record

Deletes a configuration record by configuration schema ID and endpoint group ID. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to perform this operation.

- **URL**  
/kaaAdmin/rest/api/delConfigurationRecord?schemaId&endpointGroupId

- **Method:**  
POST

- **URL params**

Parameter	Value	Description
schemaId	string	the ID of the configuration schema
endpointGroupId	string	the ID of the endpoint group

- **Data params**

None

- **Success response:**

- **Code:** 200

- **Error response:**

Status codes	Description
400 Bad Request	endpointGroupId parameter is empty
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application associated with the endpoint group does not match the Tenant ID of the authenticated user
404 Not Found	Endpoint group with the specified endpointGroupId does not exist or the endpoint group does not have the requested configuration record
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```

curl -v -S -u devuser:devuser123 -X POST "http://localhost:8080/kaaAdmin/rest/api/delConfigurationRecord?schemaId=200&endpointGroupId=83" | python -mjson.tool

```

# Notifications

## Get notification schemas

Returns notification schemas for an application. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to request this information. The Tenant ID value of the application must match the Tenant ID of the request submitter.

- **URL**  
/kaaAdmin/rest/api/notificationSchemas/{applicationId}

- **Method:**  
GET

- **URL params**

Parameter	Value	Description
applicationId	string	the ID of the application.

- **Data params**

None

- **Success response:**

- **Code:** 200
  - **Example:**

```
[
  {
    "applicationId": "71",
    "createdTime": 1408705246572,
    "createdUsername": "admin",
    "description": null,
    "endpointCount": 0,
    "id": "53f722dee4b0ac13c6a8634d",
    "majorVersion": 1,
    "minorVersion": 0,
    "name": "Generated",
    "schema": "{\r\n  \"type\": \"record\", \r\n  \"name\": \"Notification\", \r\n  \"namespace\": \"org.kaa.config\", \r\n  \"fields\": [\r\n    {\r\n      \"name\": \"message\", \r\n      \"type\": \"string\" \r\n    } \r\n  ] \r\n}",
    "type": "USER"
  }
]
```

- **Error response:**

Status codes	Description
400 Bad Request	applicationId parameter is empty
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application does not match the Tenant ID of the authenticated user

404 Not Found	Application with the specified applicationId does not exist
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u devuser:devuser123 -X GET "http://localhost:8080/kaaAdmin/rest/api/notificationSchemas/71" | python -mjson.tool
```

```
[
  {
    "applicationId": "71",
    "createdTime": 1408705246572,
    "createdUsername": "admin",
    "description": null,
    "endpointCount": 0,
    "id": "53f722dee4b0ac13c6a8634d",
    "majorVersion": 1,
    "minorVersion": 0,
    "name": "Generated",
    "schema": "{\r\n  \"type\": \"record\",\r\n  \"name\": \"Notification\",\r\n  \"namespace\": \"org.kaa.config\",\r\n  \"fields\": [\r\n    {\r\n      \"name\": \"message\",\r\n      \"type\": \"string\"\r\n    }\r\n  ],\r\n  \"type\": \"USER\""}",
    "type": "USER"
  }
]
```

## Get user notification schemas

Returns user notification schemas for an application. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to request this information.

- **URL**  
/kaaAdmin/rest/api/userNotificationSchemas/{applicationId}

- **Method:**

GET

- **URL params**

Parameter	Value	Description
applicationId	string	the ID of the application.

- **Data params**

None

- **Success response:**

- **Code:** 200
  - **Example:**

```
[
  {
    "id": "53f722dee4b0ac13c6a8634d",
    "majorVersion": 1,
    "minorVersion": 0
  }
]
```

- **Error response:**

--	--

Status codes	Description
400 Bad Request	applicationId parameter is empty
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application does not match the Tenant ID of the authenticated user
404 Not Found	Application with the specified applicationId does not exist
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u devuser:devuser123 -X GET "http://localhost:8080/kaaAdmin/rest/api/userNotificationSchemas/71" | python -mjson.tool
```

```
[
  {
    "id": "53f722dee4b0ac13c6a8634d",
    "majorVersion": 1,
    "minorVersion": 0
  }
]
```

## Get notification schema

Returns a notification schema by notification schema ID. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to request this information.

- **URL**  
/kaaAdmin/rest/api/notificationSchema/{notificationSchemaId}

- **Method:**

GET

- **URL params**

Parameter	Value	Description
notificationSchemaId	string	the ID of the notification schema

- **Data params**

None

- **Success response:**

- **Code:** 200
  - **Example:**

```
{
  "applicationId": "71",
  "createdTime": 1408705246572,
  "createdUsername": "admin",
  "description": null,
  "endpointCount": 0,
  "id": "53f722dee4b0ac13c6a8634d",
  "majorVersion": 1,
  "minorVersion": 0,
  "name": "Generated",
  "schema": "{\r\n  \"type\": \"record\", \r\n  \"name\": \"Notification\", \r\n  \"namespace\": \"org.kaa.config\", \r\n  \"fields\": [\r\n    {\r\n      \"name\":
```



```
\message\", \r\n
    "type": "USER"
}
}
}
```

- **Error response:**

Status codes	Description
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application associated with the notification schema does not match the Tenant ID of the authenticated user
404 Not Found	Notification schema with the specified notificationSchemald does not exist
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u devuser:devuser123 -X GET "http://localhost:8080/kaaAdmin/rest/api/notificationSchema/53f722dee4b0ac13c6a8634d" | python -mjson.tool
```

```
{
  "applicationId": "71",
  "createdTime": 1408705246572,
  "createdUsername": "admin",
  "description": null,
  "endpointCount": 0,
  "id": "53f722dee4b0ac13c6a8634d",
  "majorVersion": 1,
  "minorVersion": 0,
  "name": "Generated",
  "schema": "{\r\n  \"type\": \"record\", \r\n  \"name\": \"Notification\", \r\n  \"namespace\": \"org.kaa.config\", \r\n  \"fields\": [\r\n    {\r\n      \"name\": \"message\", \r\n      \"type\": \"string\" \r\n    } \r\n  ], \r\n  \"type\": \"USER\"
}"
}
```

## Create notification schema

Uploads a notification schema. A unique version number will be generated (incrementally) for this schema, and the createUsername field of the schema will be set to the name of the user who has uploaded it. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to perform this operation.

- **URL**  
/kaaAdmin/rest/api/notificationSchema

- **Method:**  
POST

- **URL params**

None

- **Data params**

Multipart/form-data encoding. Fields:

**Example:**

```
{"applicationId": "71", "name": "Test notification schema", "description": "Notification Schema Description"}
```

**File contents example:**

```
{
  "type": "record",
  "name": "TestNotification",
  "namespace": "org.kaa.config.test",
  "fields": [
    {
      "name": "message",
      "type": "string"
    }
  ]
}
```

• **Success response:**

- **Code:** 200

- **Example:**

```
{
  "applicationId": "71",
  "createdTime": 1408706536184,
  "createdUsername": "devuser",
  "description": "Notification Schema Description",
  "endpointCount": 0,
  "id": "53f727e8e4b0ac13c6a8634e",
  "majorVersion": 2,
  "minorVersion": 0,
  "name": "Test notification schema",
  "schema": "{\n  \"type\": \"record\",\n  \"name\": \"TestNotification\",\n  \"namespace\": \"org.kaa.config.test\",\n  \"fields\": [\n    {\n      \"name\": \"message\",\n      \"type\": \"string\"\n    }\n  ]\n}",
  "type": "USER"
}
```

• **Error response:**

Status codes	Description
400 Bad Request	Specified notification schema is not a valid avro schema
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application associated with the notification schema does not match the Tenant ID of the authenticated user
404 Not Found	File with a schema not found in the form data
500 Internal Server Error	Unexpected error occurred on the server side

• **Sample call:**

```
curl -v -S -u devuser:devuser123 -F'notificationSchema={"applicationId":"71","name":"Test notification schema","description":"Notification Schema Description"};type=application/json' -F file=@notification_schema.json "http://localhost:8080/kaaAdmin/rest/api/notificationSchema" | python -mjson.tool
```

```
{
  "applicationId": "71",
  "createdTime": 1408706536184,
  "createdUsername": "devuser",
```

```

    "description": "Notification Schema Description",
    "endpointCount": 0,
    "id": "53f727e8e4b0ac13c6a8634e",
    "majorVersion": 2,
    "minorVersion": 0,
    "name": "Test notification schema",
    "schema": "{\n  \type\": \"record\",\n  \name\": \"TestNotification\",\n  \"
namespace\": \"org.kaa.config.test\",\n  \fields\": {\n    {\n      \name\": \"
message\",\n      \type\": \"string\"\n    }\n  }\n}",
    "type": "USER"
  }

```

## Get topics

Returns all topics for the specified application. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to request this information.

- **URL**  
/kaaAdmin/rest/api/topics/{applicationId}

- **Method:**  
GET

- **URL params**

Parameter	Value	Description
applicationId	string	the ID of the application.

- **Data params**

None

- **Success response:**

- **Code: 200**
  - **Example:**

```

[
  {
    "applicationId": "71",
    "createdTime": 1409133583238,
    "createdUsername": "devuser",
    "description": "Test topic description",
    "id": "230",
    "name": "Test topic",
    "secNum": 0,
    "type": "MANDATORY"
  }
]

```

- **Error response:**

Status codes	Description
400 Bad Request	applicationId parameter is empty
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application does not match the Tenant ID of the authenticated user
404 Not Found	Application with the specified applicationId does not exist
500 Internal	Unexpected error occurred on the server side

Server Error

- **Sample call:**

```
curl -v -S -u devuser:devuser123 -X GET "http://localhost:8080/kaaAdmin/rest/api/topics/71" | python -m json.tool
```

```
[
  {
    "applicationId": "71",
    "createdTime": 1409133583238,
    "createdUsername": "devuser",
    "description": "Test topic description",
    "id": "230",
    "name": "Test topic",
    "secNum": 0,
    "type": "MANDATORY"
  }
]
```

## Get endpoint group topics

Returns all topics for the specified endpoint group. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to request this information.

- **URL**

/kaaAdmin/rest/api/topics?endpointGroupId

- **Method:**

GET

- **URL params**

Parameter	Value	Description
endpointGroupId	string	the ID of the endpoint group.

- **Data params**

None

- **Success response:**

- **Code: 200**

- **Example:**

```
[
  {
    "applicationId": "71",
    "createdTime": 1409133583238,
    "createdUsername": "devuser",
    "description": "Test topic description",
    "id": "230",
    "name": "Test topic",
    "secNum": 0,
    "type": "MANDATORY"
  }
]
```

- **Error response:**

Status codes	Description
--------------	-------------

400 Bad Request	endpointGroupId parameter is empty
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application associated with the endpoint group does not match the Tenant ID of the authenticated user
404 Not Found	Endpoint group with the specified endpointGroupId does not exist
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u devuser:devuser123 -X GET "http://localhost:8080/kaaAdmin/rest/api/topics?endpointGroupId=83" | python -mjson.tool
```

```
[
  {
    "applicationId": "71",
    "createdTime": 1409133583238,
    "createdUsername": "devuser",
    "description": "Test topic description",
    "id": "230",
    "name": "Test topic",
    "secNum": 0,
    "type": "MANDATORY"
  }
]
```

## Get vacant topics

Returns all vacant (not present in the endpoint group) topics for the specified endpoint group. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to request this information.

- **URL**  
/kaaAdmin/rest/api/vacantTopics/{endpointGroupId}

- **Method:**  
GET

- **URL params**

Parameter	Value	Description
endpointGroupId	string	the ID of the endpoint group.

- **Data params**

None

- **Success response:**

- **Code:** 200
  - **Example:**

```
[
  {
    "applicationId": "71",
    "createdTime": 1409134343927,
    "createdUsername": "devuser",
    "description": "Test topic 2 description",
    "id": "231",
    "name": "Test topic 2",
    "secNum": 0,
  }
]
```

```
        "type": "VOLUNTARY"
    }
]
```

- **Error response:**

Status codes	Description
400 Bad Request	endpointGroupId parameter is empty
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application associated with the endpoint group does not match the Tenant ID of the authenticated user
404 Not Found	Endpoint group with the specified endpointGroupId does not exist
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u devuser:devuser123 -X GET "http://localhost:8080/kaaAdmin/rest/api/vacantTopics/83" | python -mjson.tool
```

```
[
  {
    "applicationId": "71",
    "createdTime": 1409134343927,
    "createdUsername": "devuser",
    "description": "Test topic 2 description",
    "id": "231",
    "name": "Test topic 2",
    "secNum": 0,
    "type": "VOLUNTARY"
  }
]
```

## Get topic

Returns a topic by topic ID. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to request this information.

- **URL**

/kaaAdmin/rest/api/topic/{topicId}

- **Method:**

GET

- **URL params**

Parameter	Value	Description
topicId	string	the ID of the topic

- **Data params**

None

- **Success response:**

- **Code: 200**

- **Example:**

```
{
  "applicationId": "71",
  "createdTime": 1409133583238,
  "createdUsername": "devuser",
  "description": "Test topic description",
  "id": "230",
  "name": "Test topic",
  "secNum": 0,
  "type": "MANDATORY"
}
```

- **Error response:**

Status codes	Description
400 Bad Request	topicId parameter is empty
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application associated with the topic does not match the Tenant ID of the authenticated user
404 Not Found	Topic with the specified topicId does not exist
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u devuser:devuser123 -X GET "http://localhost:8080/kaaAdmin/rest/api/topic/230" | python -m json.tool
```

```
{
  "applicationId": "71",
  "createdTime": 1409133583238,
  "createdUsername": "devuser",
  "description": "Test topic description",
  "id": "230",
  "name": "Test topic",
  "secNum": 0,
  "type": "MANDATORY"
}
```

## Create/Edit topic

Creates or edits a topic. If a topic with the specified ID does not exist, it will be created. If a topic with the specified ID exists, it will be updated. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to perform this operation.

- **URL**  
/kaaAdmin/rest/api/topic

- **Method:**  
POST

- **URL params**  
None

- **Data params**

**Example:**

```
{"applicationId": "71", "name": "Test topic 3", "type": "MANDATORY", "description": "Test topic 3 Description"}
```

- **Success response:**

- **Code:** 200

- **Example:**

```
{  "applicationId": "71",  "createdTime": 1409135244357,  "createdUsername": "devuser",  "description": "Test topic 3 Description",  "id": "232",  "name": "Test topic 3",  "secNum": 0,  "type": "MANDATORY"}
```

- **Error response:**

Status codes	Description
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application associated with the topic does not match the Tenant ID of the authenticated user
404 Not Found	Topic to be edited with the specified topicId does not exist
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u devuser:devuser123 -X POST -H 'Content-Type: application/json' -d '{"applicationId": "71", "name": "Test topic 3", "type": "MANDATORY", "description": "Test topic 3 Description"}' "http://localhost:8080/kaaAdmin/rest/api/topic" | python -mjson.tool
```

```
{  "applicationId": "71",  "createdTime": 1409135244357,  "createdUsername": "devuser",  "description": "Test topic 3 Description",  "id": "232",  "name": "Test topic 3",  "secNum": 0,  "type": "MANDATORY"}
```

## Delete topic

Deletes a topic. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to perform this operation.

- **URL**

/kaaAdmin/rest/api/delTopic?topicId

- **Method:**

POST

- **URL params**

Parameter	Value	Description



topicId	string	the ID of the topic to be deleted
---------	--------	-----------------------------------

- **Data params**

None

- **Success response:**

- **Code:** 200

- **Error response:**

Status codes	Description
400 Bad Request	topicId parameter is empty
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application associated with the topic does not match the Tenant ID of the authenticated user
404 Not Found	Topic with the specified topicId does not exist
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u devuser:devuser123 -X POST "http://localhost:8080/kaaAdmin/rest/api/delTopic?topicId=232" | python -mjson.tool
```

## Add topic to endpoint group

Adds the specified topic to the specified endpoint group. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to perform this operation.

- **URL**

/kaaAdmin/rest/api/addTopicToEpGroup?endpointGroupId&topicId

- **Method:**

POST

- **URL params**

Parameter	Value	Description
endpointGroupId	string	the ID of the endpoint group
topicId	string	the ID of the topic

- **Data params**

None

- **Success response:**

- **Code:** 200

- **Error response:**

Status codes	Description
400 Bad Request	endpointGroupId or topicId parameter is empty
401 Unauthorized	User is not authenticated or invalid credentials provided

403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application associated with the topic or the endpoint group does not match the Tenant ID of the authenticated user
404 Not Found	Topic with the specified topicId or endpoint group with the specified endpointGroupId does not exist
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u devuser:devuser123 -X POST "http://localhost:8080/kaaAdmin/rest/api/addTopicToEpGroup?endpointGroupId=83&topicId=231" | python -mjson.tool
```

## Remove topic from endpoint group

Removes the specified topic from the specified endpoint group. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to perform this operation.

- **URL**  
/kaaAdmin/rest/api/removeTopicFromEpGroup?endpointGroupId&topicId

- **Method:**  
POST

- **URL params**

Parameter	Value	Description
endpointGroupId	string	the ID of the endpoint group
topicId	string	the ID of the topic

- **Data params**

None

- **Success response:**

- **Code:** 200

- **Error response:**

Status codes	Description
400 Bad Request	endpointGroupId or topicId parameter is empty
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application associated with the topic or the endpoint group does not match the Tenant ID of the authenticated user
404 Not Found	Topic with the specified topicId or endpoint group with the specified endpointGroupId does not exist
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u devuser:devuser123 -X POST "http://localhost:8080/kaaAdmin/rest/api/removeTopicFromEpGroup?endpointGroupId=83&topicId=231" | python -mjson.tool
```

## Send notification

Sends a notification with the notification body from the specified file. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to perform this operation.

- **URL**  
/kaaAdmin/rest/api/sendNotification

- **Method:**  
POST

- **URL params**  
None

- **Data params**  
Multipart/form-data encoding. Fields:

**Example:**

```
{ "applicationId": "71", "schemaId": "53f722dee4b0ac13c6a8634d", "version": "1", "topicId": "230", "type": "USER" }
```

**File contents example:**

```
{ "message": "Hello world!" }
```

- **Success response:**

- **Code:** 200

- **Error response:**

Status codes	Description
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the specified application or the application associated with the specified topic does not match the Tenant ID of the authenticated user
404 Not Found	File with the notification body not found in the form data or application with the specified ID does not exist or topic with the specified ID does not exist
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u devuser:devuser123 -F'notification={"applicationId":"71","schemaId":"53f722dee4b0ac13c6a8634d","version":"1","topicId":"230","type":"USER"};type=application/json' -F file=@notification.json "http://localhost:8080/kaaAdmin/rest/api/sendNotification" | python -mjson.tool
```

## Events

### Get event class families

Returns all event class families for the current authorized user within the current tenant. Only users with the TENANT\_ADMIN role are allowed to request this information.

• **URL**  
/kaaAdmin/rest/api/eventClassFamilies

• **Method:**  
GET

• **URL params**  
None

• **Data params**  
None

• **Success response:**

• **Code:** 200  
• **Example:**

```
[
  {
    "className": "PlayerClassFamily",
    "createdTime": 1408705243720,
    "createdUsername": "admin",
    "description": null,
    "id": "30",
    "name": "Player Event Class Family",
    "namespace": "org.kaaproject.kaa.demo.player",
    "schemas": [
      {
        "createdTime": 1408705244624,
        "createdUsername": "admin",
        "id": "40",
        "schema": "[\r\n{\r\n  \"namespace\": \"org.kaaproject.kaa.demo.player\",
\r\n  \"type\": \"record\",
\r\n  \"classType\": \"event\",
\r\n  \"name\": \"
DeviceInfoRequest\",
\r\n  \"fields\": []\r\n},
\r\n{\r\n  \"namespace\": \"org.kaaproject.kaa.
demo.player\",
\r\n  \"type\": \"record\",
\r\n  \"classType\": \"object\",
\r\n  \"name\": \"
DeviceInfo\",
\r\n  \"fields\": [\r\n    {\"name\": \"model\", \"type\": [\"string\", \"
null\"]},
\r\n    {\"name\": \"product\", \"type\": [\"string\", \"null\"]},
\r\n    {\"
name\": \"manufacturer\", \"type\": [\"string\", \"null\"]},
\r\n    {\"name\": \"device\",
\r\n  \"type\": [\"string\", \"null\"]},
\r\n    {\"name\": \"brand\", \"type\": [\"string\", \"
null\"]}\r\n  ]\r\n},
\r\n{\r\n  \"namespace\": \"org.kaaproject.kaa.demo.player\",
\r\n  \"
type\": \"record\",
\r\n  \"classType\": \"event\",
\r\n  \"name\": \"DeviceInfoResponse\",
\r\n
\"fields\": [\r\n\t{\"name\": \"deviceInfo\", \"type\": [\"org.kaaproject.kaa.demo.player.
DeviceInfo\", \"null\"]}\r\n  ]\r\n},
\r\n{\r\n  \"namespace\": \"org.kaaproject.kaa.demo.
player\",
\r\n  \"type\": \"record\",
\r\n  \"classType\": \"event\",
\r\n  \"name\": \"
PlaylistRequest\",
\r\n  \"fields\": []\r\n},
\r\n{\r\n  \"namespace\": \"org.kaaproject.kaa.
demo.player\",
\r\n  \"type\": \"record\",
\r\n  \"classType\": \"object\",
\r\n  \"name\": \"
SongInfo\",
\r\n  \"fields\": [\r\n    {\"name\": \"title\", \"type\": [\"string\", \"
null\"]},
\r\n    {\"name\": \"artist\", \"type\": [\"string\", \"null\"]},
\r\n    {\"
name\": \"url\", \"type\": [\"string\", \"null\"]},
\r\n    {\"name\": \"displayName\", \"
type\": [\"string\", \"null\"]},
\r\n    {\"name\": \"duration\", \"type\": [\"int\", \"
null\"]},
\r\n    {\"name\": \"album\", \"type\": [\"string\", \"null\"]}\r\n  ]\r\n},
\r\n
{\r\n  \"namespace\": \"org.kaaproject.kaa.demo.player\",
\r\n  \"type\": \"record\",
\r\n  \"
classType\": \"event\",
\r\n  \"name\": \"PlaylistResponse\",
\r\n  \"fields\": [\r\n\t{\"
name\": \"playlist\", \"type\": [{\"type\": \"array\", \"items\": \"org.kaaproject.kaa.demo.
player.SongInfo\"}, \"null\"]}\r\n  ]\r\n},
\r\n{\r\n  \"namespace\": \"org.kaaproject.kaa.
demo.player\",
\r\n  \"type\": \"record\",
\r\n  \"classType\": \"event\",
\r\n  \"name\": \"
PlayRequest\",
\r\n  \"fields\": [\r\n    {\"name\": \"url\", \"type\": [\"string\", \"
null\"]}\r\n  ]\r\n},
\r\n{\r\n  \"namespace\": \"org.kaaproject.kaa.demo.player\",
\r\n  \"
type\": \"record\",
\r\n  \"classType\": \"event\",
\r\n  \"name\": \"PauseRequest\",
\r\n  \"
fields\": []\r\n},
\r\n{\r\n  \"namespace\": \"org.kaaproject.kaa.demo.player\",
\r\n  \"
type\": \"record\",
\r\n  \"classType\": \"event\",
\r\n  \"name\": \"StopRequest\",
\r\n  \"
fields\": []\r\n},
\r\n{\r\n  \"namespace\": \"org.kaaproject.kaa.demo.player\",
\r\n  \"
type\": \"record\",
\r\n  \"classType\": \"event\",
\r\n  \"name\": \"PlaybackInfoRequest\",
\r\n
\"fields\": []\r\n},
\r\n{\r\n  \"namespace\": \"org.kaaproject.kaa.demo.player\",
\r\n  \"
type\": \"enum\",
\r\n  \"classType\": \"object\",
\r\n  \"name\": \"PlaybackStatus\",
\r\n  \"
symbols\": [\"PLAYING\", \"PAUSED\", \"STOPPED\"]\r\n},
\r\n{\r\n  \"namespace\": \"org.
kaaproject.kaa.demo.player\",
\r\n  \"type\": \"record\",
\r\n  \"classType\": \"object\",
\r\n
\"name\": \"PlaybackInfo\",
\r\n  \"fields\": [\r\n    {\"name\": \"url\", \"type\": [\"
string\", \"null\"]},
\r\n    {\"name\": \"time\", \"type\": [\"int\", \"null\"]},
\r\n    {\"
```

```
name\": \"status\", \"type\": [\"org.kaaproject.kaa.demo.player.PlaybackStatus\", \"null\"]}
\r\n ]\r\n},\r\n{\r\n \"namespace\": \"org.kaaproject.kaa.demo.player\", \r\n \"type\": \"
record\", \r\n \"classType\": \"event\", \r\n \"name\": \"PlaybackInfoResponse\", \r\n \"
fields\": [\r\n\t{\"name\": \"playbackInfo\", \"type\": [\"org.kaaproject.kaa.demo.player.
PlaybackInfo\", \"null\"]}\r\n ]\r\n},\r\n{\r\n \"namespace\": \"org.kaaproject.kaa.demo.
player\", \r\n \"type\": \"record\", \r\n \"classType\": \"event\", \r\n \"name\": \"
BatteryInfoRequest\", \r\n \"fields\": [ ]\r\n},\r\n{\r\n \"namespace\": \"org.kaaproject.kaa.
demo.player\", \r\n \"type\": \"enum\", \r\n \"classType\": \"object\", \r\n \"name\": \"
BatteryChargingStatus\", \r\n \"symbols\": [\"NOT_CHARGING\", \"CHARGING\", \"CHARGED\"]
\r\n},\r\n{\r\n \"namespace\": \"org.kaaproject.kaa.demo.player\", \r\n \"type\": \"record\",
\r\n \"classType\": \"object\", \r\n \"name\": \"BatteryInfo\", \r\n \"fields\": [\r\n\t {\"
name\": \"batteryLife\", \"type\": [\"int\", \"null\"]},\r\n\t {\"name\": \"
chargingStatus\", \"type\": [\"org.kaaproject.kaa.demo.player.BatteryChargingStatus\", \"
null\"]}\r\n ]\r\n},\r\n{\r\n \"namespace\": \"org.kaaproject.kaa.demo.player\", \r\n \"
type\": \"record\", \r\n \"classType\": \"event\", \r\n \"name\": \"BatteryInfoResponse\",
\r\n \"fields\": [\r\n\t {\"name\": \"batteryInfo\", \"type\": [\"org.kaaproject.kaa.demo.
player.BatteryInfo\", \"null\"]}\r\n ]\r\n}\r\n}],
\"version\": 1
}
],
\"tenantId\": \"10\"
},
{
\"className\": \"DeviceEventClassFamily\",
\"createdTime\": 1408705246098,
\"createdUsername\": \"admin\",
\"description\": null,
\"id\": \"31\",
\"name\": \"Device Event Class Family\",
\"namespace\": \"org.kaaproject.kaa.demo.smarthouse.device\",
\"schemas\": [
{
\"createdTime\": 1408705246155,
\"createdUsername\": \"admin\",
\"id\": \"41\",
\"schema\": \"[\r\n{\r\n \"namespace\": \"org.kaaproject.kaa.demo.smarthouse.
device\", \r\n \"type\": \"record\", \r\n \"classType\": \"event\", \r\n \"name\": \"
DeviceInfoRequest\", \r\n \"fields\": [ ]\r\n},\r\n{\r\n \"namespace\": \"org.kaaproject.kaa.
demo.smarthouse.device\", \r\n \"type\": \"enum\", \r\n \"classType\": \"object\", \r\n \"
name\": \"DeviceType\", \r\n \"symbols\": [\"THERMOSTAT\", \"TV\", \"SOUND_SYSTEM\", \"
LAMP\"]\r\n},\r\n{\r\n \"namespace\": \"org.kaaproject.kaa.demo.smarthouse.device\", \r\n \"
type\": \"record\", \r\n \"classType\": \"object\", \r\n \"name\": \"DeviceInfo\", \r\n \"
fields\": [\r\n\t {\"name\": \"deviceType\", \"type\": [\"org.kaaproject.kaa.demo.
smarthouse.device.DeviceType\", \"null\"]},\r\n\t {\"name\": \"model\", \"type\": [\"
string\", \"null\"]},\r\n\t {\"name\": \"manufacturer\", \"type\": [\"string\", \"null\"]}
\r\n ]\r\n},\r\n{\r\n \"namespace\": \"org.kaaproject.kaa.demo.smarthouse.device\", \r\n \"
type\": \"record\", \r\n \"classType\": \"event\", \r\n \"name\": \"DeviceInfoResponse\", \r\n
\"fields\": [\r\n\t {\"name\": \"deviceInfo\", \"type\": [\"org.kaaproject.kaa.demo.
smarthouse.device.DeviceInfo\", \"null\"]}\r\n ]\r\n}\r\n]\r\n\",
\"version\": 1
}
],
\"tenantId\": \"10\"
},
{
\"className\": \"ThermoEventClassFamily\",
\"createdTime\": 1408705246201,
\"createdUsername\": \"admin\",
\"description\": null,
\"id\": \"32\",
\"name\": \"Thermo Event Class Family\",
\"namespace\": \"org.kaaproject.kaa.demo.smarthouse.thermo\",
\"schemas\": [
{
\"createdTime\": 1408705246242,
\"createdUsername\": \"admin\",
\"id\": \"42\",
\"schema\": \"[\r\n{\r\n \"namespace\": \"org.kaaproject.kaa.demo.smarthouse.
thermo\", \r\n \"type\": \"record\", \r\n \"classType\": \"event\", \r\n \"name\": \"
ThermostatInfoRequest\", \r\n \"fields\": [ ]\r\n},\r\n{\r\n \"namespace\": \"org.kaaproject.
kaa.demo.smarthouse.thermo\", \r\n \"type\": \"record\", \r\n \"classType\": \"object\", \r\n
```

```

"name": "ThermostatInfo",\r\n "fields": [\r\n  {"name": "degree", "type": [\r\n    "int", "null"]},\r\n  {"name": "targetDegree", "type": [\r\n    "int", "null"]},\r\n  {"name": "isSetManually", "type": ["boolean", "null"]}\r\n ]\r\n },\r\n {\r\n  "namespace": "org.kaaproject.kaa.demo.smarthouse.thermo",\r\n  "type": "record",\r\n  "classType": "event",\r\n  "name": "ThermostatInfoResponse",\r\n  "fields": [\r\n    {"name": "thermostatInfo", "type": ["org.kaaproject.kaa.demo.smarthouse.thermo.ThermostatInfo", "null"]}\r\n  ]\r\n },\r\n {\r\n  "namespace": "org.kaaproject.kaa.demo.smarthouse.thermo",\r\n  "type": "record",\r\n  "classType": "event",\r\n  "name": "ChangeDegreeRequest",\r\n  "fields": [\r\n    {"name": "degree", "type": ["int", "null"]}\r\n  ]\r\n }],
"version": 1
}
],
"tenantId": "10"
},
{
  "className": "MusicEventClassFamily",
  "createdTime": 1408705246282,
  "createdUsername": "admin",
  "description": null,
  "id": "33",
  "name": "Music Event Class Family",
  "namespace": "org.kaaproject.kaa.demo.smarthouse.music",
  "schemas": [
    {
      "createdTime": 1408705246328,
      "createdUsername": "admin",
      "id": "43",
      "schema": "[\r\n{\r\n  "namespace": "org.kaaproject.kaa.demo.smarthouse.music",\r\n  "type": "record",\r\n  "classType": "event",\r\n  "name": "PlaylistRequest",\r\n  "fields": [\r\n    {\r\n      "namespace": "org.kaaproject.kaa.demo.smarthouse.music",\r\n      "type": "record",\r\n      "classType": "object",\r\n      "name": "SongInfo",\r\n      "fields": [\r\n        {"name": "title", "type": ["string", "null"]},\r\n        {"name": "artist", "type": ["string", "null"]},\r\n        {"name": "url", "type": ["string", "null"]},\r\n        {"name": "displayName", "type": ["string", "null"]},\r\n        {"name": "duration", "type": ["int", "null"]},\r\n        {"name": "album", "type": ["string", "null"]}\r\n      ]\r\n },\r\n {\r\n      "namespace": "org.kaaproject.kaa.demo.smarthouse.music",\r\n      "type": "record",\r\n      "classType": "event",\r\n      "name": "PlaylistResponse",\r\n      "fields": [\r\n        {"name": "playlist", "type": [{"type": "array", "items": "org.kaaproject.kaa.demo.smarthouse.music.SongInfo"}, "null"]}\r\n      ]\r\n },\r\n {\r\n      "namespace": "org.kaaproject.kaa.demo.smarthouse.music",\r\n      "type": "record",\r\n      "classType": "event",\r\n      "name": "PlayRequest",\r\n      "fields": [\r\n        {"name": "url", "type": ["string", "null"]}\r\n      ]\r\n },\r\n {\r\n      "namespace": "org.kaaproject.kaa.demo.smarthouse.music",\r\n      "type": "record",\r\n      "classType": "event",\r\n      "name": "PauseRequest",\r\n      "fields": [\r\n      ]\r\n },\r\n {\r\n      "namespace": "org.kaaproject.kaa.demo.smarthouse.music",\r\n      "type": "record",\r\n      "classType": "event",\r\n      "name": "StopRequest",\r\n      "fields": [\r\n      ]\r\n },\r\n {\r\n      "namespace": "org.kaaproject.kaa.demo.smarthouse.music",\r\n      "type": "record",\r\n      "classType": "event",\r\n      "name": "PlaybackInfoRequest",\r\n      "fields": [\r\n      ]\r\n },\r\n {\r\n      "namespace": "org.kaaproject.kaa.demo.smarthouse.music",\r\n      "type": "record",\r\n      "classType": "event",\r\n      "name": "ChangeVolumeRequest",\r\n      "fields": [\r\n        {"name": "volume", "type": ["int", "null"]}\r\n      ]\r\n },\r\n {\r\n      "namespace": "org.kaaproject.kaa.demo.smarthouse.music",\r\n      "type": "record",\r\n      "classType": "event",\r\n      "name": "SeekRequest",\r\n      "fields": [\r\n        {"name": "time", "type": ["int", "null"]}\r\n      ]\r\n },\r\n {\r\n      "namespace": "org.kaaproject.kaa.demo.smarthouse.music",\r\n      "type": "enum",\r\n      "classType": "object",\r\n      "name": "PlaybackStatus",\r\n      "symbols": ["PLAYING", "PAUSED", "STOPPED"]\r\n },\r\n {\r\n      "namespace": "org.kaaproject.kaa.demo.smarthouse.music",\r\n      "type": "record",\r\n      "classType": "object",\r\n      "name": "PlaybackInfo",\r\n      "fields": [\r\n        {"name": "song", "type": ["org.kaaproject.kaa.demo.smarthouse.music.SongInfo", "null"]},\r\n        {"name": "time", "type": ["int", "null"]},\r\n        {"name": "volume", "type": ["int", "null"]},\r\n        {"name": "maxVolume", "type": ["int", "null"]},\r\n        {"name": "timeSetOnDevice", "type": ["boolean", "null"]},\r\n        {"name": "volumeSetOnDevice", "type": ["boolean", "null"]},\r\n        {"name": "status", "type": ["org.kaaproject.kaa.demo.smarthouse.music.PlaybackStatus", "null"]}\r\n      ]\r\n },\r\n {\r\n      "namespace": "org.kaaproject.kaa.demo.smarthouse.music",\r\n      "type": "record",\r\n      "classType": "event",\r\n      "name": "PlaybackInfoResponse",\r\n      "fields": [\r\n        {"name": "playbackInfo", "type": ["org.kaaproject.kaa.demo.smarthouse.music.PlaybackInfo", "null"]}\r\n      ]\r\n }],
"version": 1

```

```

    }
  ],
  "tenantId": "10"
}
]

```

• **Error response:**

Status codes	Description
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the TENANT_ADMIN role
500 Internal Server Error	Unexpected error occurred on the server side

• **Sample call:**

```

curl -v -S -u admin:admin123 -X GET "http://localhost:8080/kaaAdmin/rest/api/eventClassFamilies" |
python -mjson.tool

```

```

[
  {
    "className": "PlayerClassFamily",
    "createdTime": 1408705243720,
    "createdUsername": "admin",
    "description": null,
    "id": "30",
    "name": "Player Event Class Family",
    "namespace": "org.kaaproject.kaa.demo.player",
    "schemas": [
      {
        "createdTime": 1408705244624,
        "createdUsername": "admin",
        "id": "40",
        "schema": "[\r\n{\r\n  \"namespace\": \"org.kaaproject.kaa.demo.player\", \r\n  \"type\": \"record\", \r\n  \"classType\": \"event\", \r\n  \"name\": \"DeviceInfoRequest\", \r\n  \"fields\": [\r\n    {\r\n      \"namespace\": \"org.kaaproject.kaa.demo.player\", \r\n      \"type\": \"record\", \r\n      \"classType\": \"object\", \r\n      \"name\": \"DeviceInfo\", \r\n      \"fields\": [\r\n        {\r\n          \"name\": \"model\", \"type\": [\"string\", \"null\"]}, \r\n          {\r\n            \"name\": \"product\", \"type\": [\"string\", \"null\"]}, \r\n          {\r\n            \"name\": \"manufacturer\", \"type\": [\"string\", \"null\"]}, \r\n          {\r\n            \"name\": \"device\", \"type\": [\"string\", \"null\"]}, \r\n          {\r\n            \"name\": \"brand\", \"type\": [\"string\", \"null\"]}\r\n        ]\r\n      }, \r\n      {\r\n        \"namespace\": \"org.kaaproject.kaa.demo.player\", \r\n        \"type\": \"record\", \r\n        \"classType\": \"event\", \r\n        \"name\": \"DeviceInfoResponse\", \r\n        \"fields\": [\r\n          {\r\n            \"name\": \"deviceInfo\", \"type\": [\"org.kaaproject.kaa.demo.player.DeviceInfo\", \"null\"]}\r\n        ]\r\n      }, \r\n      {\r\n        \"namespace\": \"org.kaaproject.kaa.demo.player\", \r\n        \"type\": \"record\", \r\n        \"classType\": \"event\", \r\n        \"name\": \"PlaylistRequest\", \r\n        \"fields\": [\r\n          {\r\n            \"namespace\": \"org.kaaproject.kaa.demo.player\", \r\n            \"type\": \"record\", \r\n            \"classType\": \"object\", \r\n            \"name\": \"SongInfo\", \r\n            \"fields\": [\r\n              {\r\n                \"name\": \"title\", \"type\": [\"string\", \"null\"]}, \r\n              {\r\n                \"name\": \"artist\", \"type\": [\"string\", \"null\"]}, \r\n              {\r\n                \"name\": \"url\", \"type\": [\"string\", \"null\"]}, \r\n              {\r\n                \"name\": \"displayName\", \"type\": [\"string\", \"null\"]}, \r\n              {\r\n                \"name\": \"duration\", \"type\": [\"int\", \"null\"]}, \r\n              {\r\n                \"name\": \"album\", \"type\": [\"string\", \"null\"]}\r\n            ]\r\n          }, \r\n          {\r\n            \"namespace\": \"org.kaaproject.kaa.demo.player\", \r\n            \"type\": \"record\", \r\n            \"classType\": \"event\", \r\n            \"name\": \"PlaylistResponse\", \r\n            \"fields\": [\r\n              {\r\n                \"name\": \"playlist\", \"type\": [\"type\": \"array\", \"items\": \"org.kaaproject.kaa.demo.player.SongInfo\", \"null\"]}\r\n            ]\r\n          }, \r\n          {\r\n            \"namespace\": \"org.kaaproject.kaa.demo.player\", \r\n            \"type\": \"record\", \r\n            \"classType\": \"event\", \r\n            \"name\": \"PlayRequest\", \r\n            \"fields\": [\r\n              {\r\n                \"name\": \"url\", \"type\": [\"string\", \"null\"]}\r\n            ]\r\n          }, \r\n          {\r\n            \"namespace\": \"org.kaaproject.kaa.demo.player\", \r\n            \"type\": \"record\", \r\n            \"classType\": \"event\", \r\n            \"name\": \"PauseRequest\", \r\n            \"fields\": [\r\n              {\r\n                \"namespace\": \"org.kaaproject.kaa.demo.player\", \r\n                \"type\": \"record\", \r\n                \"classType\": \"event\", \r\n                \"name\": \"StopRequest\", \r\n                \"fields\": [\r\n                  {\r\n                    \"namespace\": \"org.kaaproject.kaa.demo.player\", \r\n                    \"type\": \"record\", \r\n                    \"classType\": \"event\", \r\n                    \"name\": \"PlaybackInfoRequest\", \r\n                    \"fields\": [\r\n                      {\r\n                        \"namespace\": \"org.kaaproject.kaa.demo.player\", \r\n                        \"type\": \"enum\", \r\n                        \"classType\": \"object\", \r\n                        \"name\": \"PlaybackStatus\", \r\n                        \"symbols\": [\"PLAYING\", \"PAUSED\", \"STOPPED\"]}\r\n                    ]\r\n                  }\r\n                ]\r\n              }\r\n            ]\r\n          }\r\n        ]\r\n      }\r\n    ]\r\n  }\r\n]

```

```
{\r\n \"namespace\": \"org.kaaproject.kaa.demo.player\", \r\n \"type\": \"record\", \r\n \"classType\": \"object\", \r\n \"name\": \"PlaybackInfo\", \r\n \"fields\": [\r\n {\"name\": \"url\", \"type\": [\"string\", \"null\"]}, \r\n {\"name\": \"time\", \"type\": [\"int\", \"null\"]}, \r\n {\"name\": \"status\", \"type\": [\"org.kaaproject.kaa.demo.player.PlaybackStatus\", \"null\"]} \r\n ] \r\n }, \r\n {\r\n \"namespace\": \"org.kaaproject.kaa.demo.player\", \r\n \"type\": \"record\", \r\n \"classType\": \"event\", \r\n \"name\": \"PlaybackInfoResponse\", \r\n \"fields\": [\r\n {\"name\": \"playbackInfo\", \"type\": [\"org.kaaproject.kaa.demo.player.PlaybackInfo\", \"null\"]} \r\n ] \r\n }, \r\n {\r\n \"namespace\": \"org.kaaproject.kaa.demo.player\", \r\n \"type\": \"record\", \r\n \"classType\": \"event\", \r\n \"name\": \"BatteryInfoRequest\", \r\n \"fields\": [ \r\n ], \r\n {\r\n \"namespace\": \"org.kaaproject.kaa.demo.player\", \r\n \"type\": \"enum\", \r\n \"classType\": \"object\", \r\n \"name\": \"BatteryChargingStatus\", \r\n \"symbols\": [\"NOT_CHARGING\", \"CHARGING\", \"CHARGED\"] \r\n }, \r\n {\r\n \"namespace\": \"org.kaaproject.kaa.demo.player\", \r\n \"type\": \"record\", \r\n \"classType\": \"object\", \r\n \"name\": \"BatteryInfo\", \r\n \"fields\": [\r\n {\"name\": \"batteryLife\", \"type\": [\"int\", \"null\"]}, \r\n {\"name\": \"chargingStatus\", \"type\": [\"org.kaaproject.kaa.demo.player.BatteryChargingStatus\", \"null\"]} \r\n ] \r\n }, \r\n {\r\n \"namespace\": \"org.kaaproject.kaa.demo.player\", \r\n \"type\": \"record\", \r\n \"classType\": \"event\", \r\n \"name\": \"BatteryInfoResponse\", \r\n \"fields\": [\r\n {\"name\": \"batteryInfo\", \"type\": [\"org.kaaproject.kaa.demo.player.BatteryInfo\", \"null\"]} \r\n ] \r\n } \r\n ], \r\n \"version\": 1 \r\n } \r\n ], \r\n \"tenantId\": \"10\" \r\n }, \r\n { \r\n \"className\": \"DeviceEventClassFamily\", \r\n \"createdTime\": 1408705246098, \r\n \"createdUsername\": \"admin\", \r\n \"description\": null, \r\n \"id\": \"31\", \r\n \"name\": \"Device Event Class Family\", \r\n \"namespace\": \"org.kaaproject.kaa.demo.smarthouse.device\", \r\n \"schemas\": [ \r\n { \r\n \"createdTime\": 1408705246155, \r\n \"createdUsername\": \"admin\", \r\n \"id\": \"41\", \r\n \"schema\": \"[\r\n {\r\n \"namespace\": \"org.kaaproject.kaa.demo.smarthouse.device\", \r\n \"type\": \"record\", \r\n \"classType\": \"event\", \r\n \"name\": \"DeviceInfoRequest\", \r\n \"fields\": [ \r\n ], \r\n {\r\n \"namespace\": \"org.kaaproject.kaa.demo.smarthouse.device\", \r\n \"type\": \"enum\", \r\n \"classType\": \"object\", \r\n \"name\": \"DeviceInfoResponse\", \r\n \"symbols\": [\"THERMOSTAT\", \"TV\", \"SOUND_SYSTEM\", \"LAMP\"] \r\n }, \r\n {\r\n \"namespace\": \"org.kaaproject.kaa.demo.smarthouse.device\", \r\n \"type\": \"record\", \r\n \"classType\": \"object\", \r\n \"name\": \"DeviceInfo\", \r\n \"fields\": [\r\n {\"name\": \"deviceType\", \"type\": [\"org.kaaproject.kaa.demo.smarthouse.device.DeviceType\", \"null\"]}, \r\n {\"name\": \"model\", \"type\": [\"string\", \"null\"]}, \r\n {\"name\": \"manufacturer\", \"type\": [\"string\", \"null\"]} \r\n ] \r\n }, \r\n {\r\n \"namespace\": \"org.kaaproject.kaa.demo.smarthouse.device\", \r\n \"type\": \"record\", \r\n \"classType\": \"event\", \r\n \"name\": \"DeviceInfoResponse\", \r\n \"fields\": [\r\n {\"name\": \"deviceInfo\", \"type\": [\"org.kaaproject.kaa.demo.smarthouse.device.DeviceInfo\", \"null\"]} \r\n ] \r\n } \r\n ], \r\n \"version\": 1 \r\n } \r\n ], \r\n \"tenantId\": \"10\" \r\n }, \r\n { \r\n \"className\": \"ThermoEventClassFamily\", \r\n \"createdTime\": 1408705246201, \r\n \"createdUsername\": \"admin\", \r\n \"description\": null, \r\n \"id\": \"32\", \r\n \"name\": \"Thermo Event Class Family\", \r\n \"namespace\": \"org.kaaproject.kaa.demo.smarthouse.thermo\", \r\n \"schemas\": [ \r\n { \r\n \"createdTime\": 1408705246242, \r\n \"createdUsername\": \"admin\", \r\n \"id\": \"42\", \r\n \"schema\": \"[\r\n {\r\n \"namespace\": \"org.kaaproject.kaa.demo.smarthouse.thermo\", \r\n \"type\": \"record\", \r\n \"classType\": \"event\", \r\n \"name\": \"ThermostatInfoRequest\", \r\n \"fields\": [ \r\n ], \r\n {\r\n \"namespace\": \"org.kaaproject.kaa.demo.smarthouse.thermo\", \r\n \"type\": \"enum\", \r\n \"classType\": \"object\", \r\n \"name\": \"ThermostatInfoResponse\", \r\n \"symbols\": [\"HEATING\", \"COOLING\", \"OFF\"] \r\n }, \r\n {\r\n \"namespace\": \"org.kaaproject.kaa.demo.smarthouse.thermo\", \r\n \"type\": \"record\", \r\n \"classType\": \"object\", \r\n \"name\": \"ThermostatInfo\", \r\n \"fields\": [\r\n {\"name\": \"currentTemp\", \"type\": [\"float\", \"null\"]}, \r\n {\"name\": \"targetTemp\", \"type\": [\"float\", \"null\"]}, \r\n {\"name\": \"mode\", \"type\": [\"ThermostatInfoResponse\", \"null\"]} \r\n ] \r\n }, \r\n {\r\n \"namespace\": \"org.kaaproject.kaa.demo.smarthouse.thermo\", \r\n \"type\": \"record\", \r\n \"classType\": \"event\", \r\n \"name\": \"ThermostatInfoResponse\", \r\n \"fields\": [\r\n {\"name\": \"thermostatInfo\", \"type\": [\"org.kaaproject.kaa.demo.smarthouse.thermo.ThermostatInfo\", \"null\"]} \r\n ] \r\n } \r\n ], \r\n \"version\": 1 \r\n } \r\n ], \r\n \"tenantId\": \"10\" \r\n } \r\n ] \r\n }
```



```
\r\n \"fields\": [\r\n],\r\n{\r\n \"namespace\": \"org.kaaproject.kaa.demo.smarthouse.thermo\",
\r\n \"type\": \"record\", \r\n \"classType\": \"object\", \r\n \"name\": \"ThermostatInfo\", \r\n \"fields\": [\r\n {\"name\": \"degree\", \"type\": [\"int\", \"null\"]}, \r\n {\"name\": \"targetDegree\", \"type\": [\"int\", \"null\"]}, \r\n {\"name\": \"isSetManually\", \"type\": [\"boolean\", \"null\"]} \r\n ] \r\n }, \r\n {\r\n \"namespace\": \"org.kaaproject.kaa.demo.smarthouse.thermo\", \r\n \"type\": \"record\", \r\n \"classType\": \"event\", \r\n \"name\": \"ThermostatInfoResponse\", \r\n \"fields\": [\r\n {\"name\": \"thermostatInfo\", \"type\": [\"org.kaaproject.kaa.demo.smarthouse.thermo.ThermostatInfo\", \"null\"]} \r\n ] \r\n }, \r\n {\r\n \"namespace\": \"org.kaaproject.kaa.demo.smarthouse.thermo\", \r\n \"type\": \"record\", \r\n \"classType\": \"event\", \r\n \"name\": \"ChangeDegreeRequest\", \r\n \"fields\": [\r\n {\"name\": \"degree\", \"type\": [\"int\", \"null\"]} \r\n ] \r\n },
\"version\": 1
}
],
\"tenantId\": \"10\"
},
{
\"className\": \"MusicEventClassFamily\",
\"createdTime\": 1408705246282,
\"createdUsername\": \"admin\",
\"description\": null,
\"id\": \"33\",
\"name\": \"Music Event Class Family\",
\"namespace\": \"org.kaaproject.kaa.demo.smarthouse.music\",
\"schemas\": [
{
\"createdTime\": 1408705246328,
\"createdUsername\": \"admin\",
\"id\": \"43\",
\"schema\": \"[\r\n{\r\n \"namespace\": \"org.kaaproject.kaa.demo.smarthouse.music\",
\r\n \"type\": \"record\", \r\n \"classType\": \"event\", \r\n \"name\": \"PlaylistRequest\", \r\n \"fields\": [\r\n], \r\n {\r\n \"namespace\": \"org.kaaproject.kaa.demo.smarthouse.music\", \r\n \"type\": \"record\", \r\n \"classType\": \"object\", \r\n \"name\": \"SongInfo\", \r\n \"fields\": [\r\n {\"name\": \"title\", \"type\": [\"string\", \"null\"]}, \r\n {\"name\": \"artist\", \"type\": [\"string\", \"null\"]}, \r\n {\"name\": \"url\", \"type\": [\"string\", \"null\"]}, \r\n {\"name\": \"displayName\", \"type\": [\"string\", \"null\"]}, \r\n {\"name\": \"album\", \"type\": [\"string\", \"null\"]} \r\n ] \r\n }, \r\n {\r\n \"namespace\": \"org.kaaproject.kaa.demo.smarthouse.music\", \r\n \"type\": \"record\", \r\n \"classType\": \"event\", \r\n \"name\": \"PlaylistResponse\", \r\n \"fields\": [\r\n {\"name\": \"playlist\", \"type\": [\"array\", \"items\": \"org.kaaproject.kaa.demo.smarthouse.music.SongInfo\", \"null\"]} \r\n ] \r\n }, \r\n {\r\n \"namespace\": \"org.kaaproject.kaa.demo.smarthouse.music\", \r\n \"type\": \"record\", \r\n \"classType\": \"event\", \r\n \"name\": \"PlayRequest\", \r\n \"fields\": [\r\n {\"name\": \"url\", \"type\": [\"string\", \"null\"]} \r\n ] \r\n }, \r\n {\r\n \"namespace\": \"org.kaaproject.kaa.demo.smarthouse.music\", \r\n \"type\": \"record\", \r\n \"classType\": \"event\", \r\n \"name\": \"PauseRequest\", \r\n \"fields\": [\r\n], \r\n {\r\n \"namespace\": \"org.kaaproject.kaa.demo.smarthouse.music\", \r\n \"type\": \"record\", \r\n \"classType\": \"event\", \r\n \"name\": \"StopRequest\", \r\n \"fields\": [\r\n], \r\n {\r\n \"namespace\": \"org.kaaproject.kaa.demo.smarthouse.music\", \r\n \"type\": \"record\", \r\n \"classType\": \"event\", \r\n \"name\": \"ChangeVolumeRequest\", \r\n \"fields\": [\r\n {\"name\": \"volume\", \"type\": [\"int\", \"null\"]} \r\n ] \r\n }, \r\n {\r\n \"namespace\": \"org.kaaproject.kaa.demo.smarthouse.music\", \r\n \"type\": \"record\", \r\n \"classType\": \"event\", \r\n \"name\": \"SeekRequest\", \r\n \"fields\": [\r\n {\"name\": \"time\", \"type\": [\"int\", \"null\"]} \r\n ] \r\n }, \r\n {\r\n \"namespace\": \"org.kaaproject.kaa.demo.smarthouse.music\", \r\n \"type\": \"enum\", \r\n \"classType\": \"object\", \r\n \"name\": \"PlaybackStatus\", \r\n \"symbols\": [\"PLAYING\", \"PAUSED\", \"STOPPED\"] \r\n }, \r\n {\r\n \"namespace\": \"org.kaaproject.kaa.demo.smarthouse.music\", \r\n \"type\": \"record\", \r\n \"classType\": \"object\", \r\n \"name\": \"PlaybackInfo\", \r\n \"fields\": [\r\n {\"name\": \"song\", \"type\": [\"org.kaaproject.kaa.demo.smarthouse.music.SongInfo\", \"null\"]}, \r\n {\"name\": \"time\", \"type\": [\"int\", \"null\"]}, \r\n {\"name\": \"volume\", \"type\": [\"int\", \"null\"]}, \r\n {\"name\": \"maxVolume\", \"type\": [\"int\", \"null\"]}, \r\n {\"name\": \"timeSetOnDevice\", \"type\": [\"boolean\", \"null\"]}, \r\n {\"name\": \"volumeSetOnDevice\", \"type\": [\"boolean\", \"null\"]}, \r\n {\"name\": \"status\", \"type\": [\"org.kaaproject.kaa.demo.smarthouse.music.PlaybackStatus\", \"null\"]} \r\n ] \r\n }, \r\n {\r\n \"namespace\": \"org.kaaproject.kaa.demo.smarthouse.music\", \r\n \"type\": \"record\", \r\n \"classType\": \"event\", \r\n \"name\": \"PlaybackInfoResponse\", \r\n \"fields\": [\r\n {\"name\": \"playbackInfo\", \"type\": [\"org.kaaproject.kaa.demo.smarthouse.music.PlaybackInfo\", \"null\"]} \r\n ] \r\n },
\"version\": 1
}
]
```

```

    ],
    "tenantId": "10"
  }
]

```

## Get event class family

Returns an event class family by event class family ID. Only users with the TENANT\_ADMIN role are allowed to request this information.

- **URL**  
/kaaAdmin/rest/api/eventClassFamily/{eventClassFamilyId}

- **Method:**

GET

- **URL params**

Parameter	Value	Description
eventClassFamilyId	string	the ID of the event class family

- **Data params**

None

- **Success response:**

- **Code: 200**
  - **Example:**

```

{
  "className": "PlayerClassFamily",
  "createdTime": 1408705243720,
  "createdUsername": "admin",
  "description": null,
  "id": "30",
  "name": "Player Event Class Family",
  "namespace": "org.kaaproject.kaa.demo.player",
  "schemas": [
    {
      "createdTime": 1408705244624,
      "createdUsername": "admin",
      "id": "40",
      "schema": "[\r\n{\r\n  \"namespace\": \"org.kaaproject.kaa.demo.player\", \r\n  \"type\": \"record\", \r\n  \"classType\": \"event\", \r\n  \"name\": \"DeviceInfoRequest\", \r\n  \"fields\": []\r\n}, \r\n{\r\n  \"namespace\": \"org.kaaproject.kaa.demo.player\", \r\n  \"type\": \"record\", \r\n  \"classType\": \"object\", \r\n  \"name\": \"DeviceInfo\", \r\n  \"fields\": [\r\n    {\"name\": \"model\", \"type\": [\"string\", \"null\"]}, \r\n    {\"name\": \"product\", \"type\": [\"string\", \"null\"]}, \r\n    {\"name\": \"manufacturer\", \"type\": [\"string\", \"null\"]}, \r\n    {\"name\": \"device\", \"type\": [\"string\", \"null\"]}, \r\n    {\"name\": \"brand\", \"type\": [\"string\", \"null\"]}\r\n  ]\r\n}, \r\n{\r\n  \"namespace\": \"org.kaaproject.kaa.demo.player\", \r\n  \"type\": \"record\", \r\n  \"classType\": \"event\", \r\n  \"name\": \"DeviceInfoResponse\", \r\n  \"fields\": [\r\n    {\r\n      \"name\": \"deviceInfo\", \"type\": [\"org.kaaproject.kaa.demo.player.DeviceInfo\", \"null\"]}\r\n  ]\r\n}, \r\n{\r\n  \"namespace\": \"org.kaaproject.kaa.demo.player\", \r\n  \"type\": \"record\", \r\n  \"classType\": \"event\", \r\n  \"name\": \"PlaylistRequest\", \r\n  \"fields\": []\r\n}, \r\n{\r\n  \"namespace\": \"org.kaaproject.kaa.demo.player\", \r\n  \"type\": \"record\", \r\n  \"classType\": \"object\", \r\n  \"name\": \"SongInfo\", \r\n  \"fields\": [\r\n    {\"name\": \"title\", \"type\": [\"string\", \"null\"]}, \r\n    {\"name\": \"artist\", \"type\": [\"string\", \"null\"]}, \r\n    {\"name\": \"url\", \"type\": [\"string\", \"null\"]}, \r\n    {\"name\": \"displayName\", \"type\": [\"string\", \"null\"]}, \r\n    {\"name\": \"duration\", \"type\": [\"int\", \"null\"]}, \r\n    {\"name\": \"album\", \"type\": [\"string\", \"null\"]}\r\n  ]\r\n}, \r\n{\r\n  \"namespace\": \"org.kaaproject.kaa.demo.player\", \r\n  \"type\": \"record\", \r\n  \"classType\": \"event\", \r\n  \"name\": \"PlaylistResponse\", \r\n  \"fields\": [\r\n    {\r\n      \"name\": \"playlist\", \"type\": [{\"type\": \"array\", \"items\": \"org.kaaproject.kaa.demo.player.SongInfo\", \"null\"}]\r\n    }\r\n  ]\r\n}, \r\n{\r\n  \"namespace\": \"org.kaaproject.kaa.demo.player\", \r\n  \"type\": \"record\", \r\n  \"classType\": \"event\", \r\n  \"name\": \"PlayRequest\", \r\n  \"fields\":

```

```

{\r\n      {\r\n        {"name": "url", "type": [{"string", "null"]}\r\n }\r\n},\r\n{\r\n "
namespace": "org.kaaproject.kaa.demo.player",\r\n "type": "record",\r\n "
classType": "event",\r\n "name": "PauseRequest",\r\n "fields": []\r\n},\r\n{\r\n "
namespace": "org.kaaproject.kaa.demo.player",\r\n "type": "record",\r\n "
classType": "event",\r\n "name": "StopRequest",\r\n "fields": []\r\n},\r\n{\r\n "
namespace": "org.kaaproject.kaa.demo.player",\r\n "type": "record",\r\n "
classType": "event",\r\n "name": "PlaybackInfoRequest",\r\n "fields": []\r\n},\r\n
{\r\n "namespace": "org.kaaproject.kaa.demo.player",\r\n "type": "enum" ,\r\n "
classType": "object",\r\n "name": "PlaybackStatus",\r\n "symbols": [{"PLAYING",
"PAUSED", "STOPPED"]\r\n},\r\n{\r\n "namespace": "org.kaaproject.kaa.demo.player",
\r\n "type": "record",\r\n "classType": "object",\r\n "name": "PlaybackInfo",
\r\n "fields": [{"name": "url", "type": [{"string", "null"]},\r\n {"
name": "time", "type": [{"int", "null"]},\r\n {"name": "status", "type":
["org.kaaproject.kaa.demo.player.PlaybackStatus", "null"]}\r\n ]\r\n},\r\n{\r\n "
namespace": "org.kaaproject.kaa.demo.player",\r\n "type": "record",\r\n "
classType": "event",\r\n "name": "PlaybackInfoResponse",\r\n "fields": [{"\r\n\t{"
name": "playbackInfo", "type": ["org.kaaproject.kaa.demo.player.PlaybackInfo", "
null"]}\r\n ]\r\n},\r\n{\r\n "namespace": "org.kaaproject.kaa.demo.player",\r\n "
type": "record",\r\n "classType": "event",\r\n "name": "BatteryInfoRequest",\r\n "
fields": [{"\r\n}\r\n},\r\n{\r\n "namespace": "org.kaaproject.kaa.demo.player",\r\n "
type": "enum" ,\r\n "classType": "object",\r\n "name": "BatteryChargingStatus",
\r\n "symbols": [{"NOT_CHARGING", "CHARGING", "CHARGED"]\r\n},\r\n{\r\n "
namespace": "org.kaaproject.kaa.demo.player",\r\n "type": "record",\r\n "
classType": "object",\r\n "name": "BatteryInfo",\r\n "fields": [{"name":
"batteryLife", "type": [{"int", "null"]},\r\n {"name": "chargingStatus", "
type": [{"org.kaaproject.kaa.demo.player.BatteryChargingStatus", "null"]}\r\n ]\r\n},
\r\n{\r\n "namespace": "org.kaaproject.kaa.demo.player",\r\n "type": "record",\r\n
"classType": "event",\r\n "name": "BatteryInfoResponse",\r\n "fields": [{"\r\n
{"name": "batteryInfo", "type": ["org.kaaproject.kaa.demo.player.BatteryInfo", "
null"]}\r\n ]\r\n}\r\n},\r\n},
"version": 1
}
],
"tenantId": "10"
}

```

• **Error response:**

Status codes	Description
400 Bad Request	eventClassFamilyId parameter is empty
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role TENANT_ADMIN or the Tenant ID of the event class family does not match the Tenant ID of the user
404 Not Found	An event class family with the specified eventClassFamilyId does not exist
500 Internal Server Error	Unexpected error occurred on the server side

• **Sample call:**

```

curl -v -S -u admin:admin123 -X GET "http://localhost:8080/kaaAdmin/rest/api/eventClassFamily/30" |
python -mjson.tool

```

```

{
  "className": "PlayerClassFamily",
  "createdTime": 1408705243720,
  "createdUsername": "admin",
  "description": null,
  "id": "30",
  "name": "Player Event Class Family",
  "namespace": "org.kaaproject.kaa.demo.player",
  "schemas": [
    {
      "createdTime": 1408705244624,

```

```

        "createdUsername": "admin",
        "id": "40",
        "schema": "[\r\n{\r\n \"namespace\": \"org.kaaproject.kaa.demo.player\", \r\n \"type\": \"record\", \r\n \"classType\": \"event\", \r\n \"name\": \"DeviceInfoRequest\", \r\n \"fields\": [\r\n ]\r\n}, \r\n{\r\n \"namespace\": \"org.kaaproject.kaa.demo.player\", \r\n \"type\": \"record\", \r\n \"classType\": \"object\", \r\n \"name\": \"DeviceInfo\", \r\n \"fields\": [\r\n {\"name\": \"model\", \"type\": [\"string\", \"null\"]}, \r\n {\"name\": \"product\", \"type\": [\"string\", \"null\"]}, \r\n {\"name\": \"manufacturer\", \"type\": [\"string\", \"null\"]}, \r\n {\"name\": \"device\", \"type\": [\"string\", \"null\"]}, \r\n {\"name\": \"brand\", \"type\": [\"string\", \"null\"]}\r\n ]\r\n}, \r\n{\r\n \"namespace\": \"org.kaaproject.kaa.demo.player\", \r\n \"type\": \"record\", \r\n \"classType\": \"event\", \r\n \"name\": \"DeviceInfoResponse\", \r\n \"fields\": [\r\n {\r\n \"name\": \"deviceInfo\", \"type\": [\"org.kaaproject.kaa.demo.player.DeviceInfo\", \"null\"]}\r\n ]\r\n}, \r\n{\r\n \"namespace\": \"org.kaaproject.kaa.demo.player\", \r\n \"type\": \"record\", \r\n \"classType\": \"event\", \r\n \"name\": \"PlaylistRequest\", \r\n \"fields\": [\r\n ]\r\n}, \r\n{\r\n \"namespace\": \"org.kaaproject.kaa.demo.player\", \r\n \"type\": \"record\", \r\n \"classType\": \"object\", \r\n \"name\": \"SongInfo\", \r\n \"fields\": [\r\n {\"name\": \"title\", \"type\": [\"string\", \"null\"]}, \r\n {\"name\": \"artist\", \"type\": [\"string\", \"null\"]}, \r\n {\"name\": \"url\", \"type\": [\"string\", \"null\"]}, \r\n {\"name\": \"displayName\", \"type\": [\"string\", \"null\"]}, \r\n {\"name\": \"duration\", \"type\": [\"int\", \"null\"]}, \r\n {\"name\": \"album\", \"type\": [\"string\", \"null\"]}\r\n ]\r\n}, \r\n{\r\n \"namespace\": \"org.kaaproject.kaa.demo.player\", \r\n \"type\": \"record\", \r\n \"classType\": \"event\", \r\n \"name\": \"PlaylistResponse\", \r\n \"fields\": [\r\n {\r\n \"name\": \"playlist\", \"type\": [\"type\": \"array\", \"items\": \"org.kaaproject.kaa.demo.player.SongInfo\"}, \"null\"]}\r\n ]\r\n}, \r\n{\r\n \"namespace\": \"org.kaaproject.kaa.demo.player\", \r\n \"type\": \"record\", \r\n \"classType\": \"event\", \r\n \"name\": \"PlayRequest\", \r\n \"fields\": [\r\n {\"name\": \"url\", \"type\": [\"string\", \"null\"]}\r\n ]\r\n}, \r\n{\r\n \"namespace\": \"org.kaaproject.kaa.demo.player\", \r\n \"type\": \"record\", \r\n \"classType\": \"event\", \r\n \"name\": \"PauseRequest\", \r\n \"fields\": [\r\n ]\r\n}, \r\n{\r\n \"namespace\": \"org.kaaproject.kaa.demo.player\", \r\n \"type\": \"record\", \r\n \"classType\": \"event\", \r\n \"name\": \"StopRequest\", \r\n \"fields\": [\r\n ]\r\n}, \r\n{\r\n \"namespace\": \"org.kaaproject.kaa.demo.player\", \r\n \"type\": \"record\", \r\n \"classType\": \"event\", \r\n \"name\": \"PlaybackInfoRequest\", \r\n \"fields\": [\r\n ]\r\n}, \r\n{\r\n \"namespace\": \"org.kaaproject.kaa.demo.player\", \r\n \"type\": \"enum\", \r\n \"classType\": \"object\", \r\n \"name\": \"PlaybackStatus\", \r\n \"symbols\": [\"PLAYING\", \"PAUSED\", \"STOPPED\"]\r\n}, \r\n{\r\n \"namespace\": \"org.kaaproject.kaa.demo.player\", \r\n \"type\": \"record\", \r\n \"classType\": \"object\", \r\n \"name\": \"PlaybackInfo\", \r\n \"fields\": [\r\n {\"name\": \"url\", \"type\": [\"string\", \"null\"]}, \r\n {\"name\": \"time\", \"type\": [\"int\", \"null\"]}, \r\n {\"name\": \"status\", \"type\": [\"org.kaaproject.kaa.demo.player.PlaybackStatus\", \"null\"]}\r\n ]\r\n}, \r\n{\r\n \"namespace\": \"org.kaaproject.kaa.demo.player\", \r\n \"type\": \"record\", \r\n \"classType\": \"event\", \r\n \"name\": \"PlaybackInfoResponse\", \r\n \"fields\": [\r\n {\r\n \"name\": \"playbackInfo\", \"type\": [\"org.kaaproject.kaa.demo.player.PlaybackInfo\", \"null\"]}\r\n ]\r\n}, \r\n{\r\n \"namespace\": \"org.kaaproject.kaa.demo.player\", \r\n \"type\": \"record\", \r\n \"classType\": \"event\", \r\n \"name\": \"BatteryInfoRequest\", \r\n \"fields\": [\r\n ]\r\n}, \r\n{\r\n \"namespace\": \"org.kaaproject.kaa.demo.player\", \r\n \"type\": \"enum\", \r\n \"classType\": \"object\", \r\n \"name\": \"BatteryChargingStatus\", \r\n \"symbols\": [\"NOT_CHARGING\", \"CHARGING\", \"CHARGED\"]\r\n}, \r\n{\r\n \"namespace\": \"org.kaaproject.kaa.demo.player\", \r\n \"type\": \"record\", \r\n \"classType\": \"object\", \r\n \"name\": \"BatteryInfo\", \r\n \"fields\": [\r\n {\"name\": \"batteryLife\", \"type\": [\"int\", \"null\"]}, \r\n {\"name\": \"chargingStatus\", \"type\": [\"org.kaaproject.kaa.demo.player.BatteryChargingStatus\", \"null\"]}\r\n ]\r\n}, \r\n{\r\n \"namespace\": \"org.kaaproject.kaa.demo.player\", \r\n \"type\": \"record\", \r\n \"classType\": \"event\", \r\n \"name\": \"BatteryInfoResponse\", \r\n \"fields\": [\r\n {\"name\": \"batteryInfo\", \"type\": [\"org.kaaproject.kaa.demo.player.BatteryInfo\", \"null\"]}\r\n ]\r\n}\r\n]\r\n],
        "version": 1
    },
    "tenantId": "10"
}

```

## Create/Edit event class family

Creates or edits an event class family. If an event class family with the specified ID does not exist, it will be created. If an event class family with the specified ID exists, it will be updated. Only users with the TENANT\_ADMIN role are allowed to perform this operation.

- **URL**  
/kaaAdmin/rest/api/eventClassFamily

- **Methods**  
POST

- **URL params**

None

- **Data params**

- **Example:**

```
{ "name": "Test Event Class Family", "className": "TestClassFamily", "description": "Test Class Family Description", "namespace": "org.kaaproject.kaa.test.family" }
```

- **Success response:**

- **Code: 200**

- **Example:**

```
{  
  "className": "TestClassFamily",  
  "createdTime": 1409142604502,  
  "createdUsername": "admin",  
  "description": "Test Class Family Description",  
  "id": "34",  
  "name": "Test Event Class Family",  
  "namespace": "org.kaaproject.kaa.test.family",  
  "schemas": null,  
  "tenantId": "10"  
}
```

- **Error response:**

Status codes	Description
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_ADMIN) or the Tenant ID of the editing event class family does not match the Tenant ID of the user
404 Not Found	Event class family to be edited with the specified eventClassFamilyId does not exist
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u admin:admin123 -X POST -H 'Content-Type: application/json' -d '{"name": "Test Event Class Family", "className": "TestClassFamily", "description": "Test Class Family Description", "namespace": "org.kaaproject.kaa.test.family"}' "http://localhost:8080/kaaAdmin/rest/api/eventClassFamily" | python -m json.tool
```

```
{  
  "className": "TestClassFamily",  
  "createdTime": 1409142604502,  
  "createdUsername": "admin",  
  "description": "Test Class Family Description",  
  "id": "34",  
  "name": "Test Event Class Family",  
  "namespace": "org.kaaproject.kaa.test.family",  
  "schemas": null,  
  "tenantId": "10"  
}
```

## Add event class family schema

Adds the event class family schema to the event class family with the specified ID. The current user will be marked as the creator of schema. Only users with the TENANT\_ADMIN role are allowed to perform this operation.

- **URL**  
/kaaAdmin/rest/api/addEventClassFamilySchema

- **Method:**  
POST

- **URL params**  
None

- **Data params**

Multipart/form-data encoding. Fields:

**Example:**

```
34
```

**File contents example:**

```
[
  {
    "namespace": "org.kaaproject.kaa.test.family",
    "type": "record",
    "classType": "event",
    "name": "MyTestRequest",
    "fields": []
  },
  {
    "namespace": "org.kaaproject.kaa.test.family",
    "type": "record",
    "classType": "event",
    "name": "MyTestResponse",
    "fields": [
      { "name": "testField", "type": ["string", "null"]}
    ]
  }
]
```

- **Success response:**

- **Code:** 200

- **Error response:**

Status codes	Description
400 Bad Request	Specified event class family schema is not a valid avro schema
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_ADMIN) or the Tenant ID of the specified event class family does not match the Tenant ID of the authenticated user
404 Not Found	File with the event class family schema not found in the form data or event class family with the specified ID does not exist
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u admin:admin123 -F'eventClassFamilyId=34;type=text/plain' -F
file=@testEventClassFamilySchema.json "http://localhost:8080/kaaAdmin/rest/api
/addEventClassFamilySchema" | python -mjson.tool
```

## Get event classes

Gets event classes by event class family ID, version and type. Only users with the TENANT\_ADMIN, TENANT\_DEVELOPER or TENANT\_USER role are allowed to request this information.

- **URL**  
/kaaAdmin/rest/api/eventClasses?eventClassFamilyId&version&type

- **Method:**

GET

- **URL params**

Parameter	Value	Description
eventClassFamilyId	string	the ID of the event class family
version	string	version of the event class family schema
type	string	event classes type, one of ["EVENT", "OBJECT"]

- **Data params**

None

- **Success response:**

- **Code: 200**
  - **Example:**

```
[
  {
    "ecfId": "34",
    "fqm": "org.kaaproject.kaa.test.family.MyTestRequest",
    "id": "177",
    "schema": "{\"type\": \"record\", \"name\": \"MyTestRequest\", \"namespace\": \"org.kaaproject.kaa.test.family\", \"fields\": [], \"classType\": \"event\"}",
    "tenantId": "10",
    "type": "EVENT",
    "version": 1
  },
  {
    "ecfId": "34",
    "fqm": "org.kaaproject.kaa.test.family.MyTestResponse",
    "id": "178",
    "schema": "{\"type\": \"record\", \"name\": \"MyTestResponse\", \"namespace\": \"org.kaaproject.kaa.test.family\", \"fields\": [{\"name\": \"testField\", \"type\": [\"string\", \"null\"]}], \"classType\": \"event\"}",
    "tenantId": "10",
    "type": "EVENT",
    "version": 1
  }
]
```

- **Error response:**

Status codes	Description
400 Bad Request	one of the url parameters is empty (eventClassFamilyId, version or type)
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_ADMIN, TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the event class family does not match the Tenant ID of the authenticated user
404 Not Found	Event class family with the specified eventClassFamilyId does not exist

500 Internal Server Error

Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u devuser:devuser123 -X GET "http://localhost:8080/kaaAdmin/rest/api/eventClasses?eventClassFamilyId=34&version=1&type=EVENT" | python -mjson.tool
```

```
[
  {
    "ecfId": "34",
    "fqcn": "org.kaaproject.kaa.test.family.MyTestRequest",
    "id": "177",
    "schema": "{\n  \"type\": \"record\",\n  \"name\": \"MyTestRequest\",\n  \"namespace\": \"org.kaaproject.kaa.test.family\",\n  \"fields\": [],\n  \"classType\": \"event\"\n}",
    "tenantId": "10",
    "type": "EVENT",
    "version": 1
  },
  {
    "ecfId": "34",
    "fqcn": "org.kaaproject.kaa.test.family.MyTestResponse",
    "id": "178",
    "schema": "{\n  \"type\": \"record\",\n  \"name\": \"MyTestResponse\",\n  \"namespace\": \"org.kaaproject.kaa.test.family\",\n  \"fields\": [{\n    \"name\": \"testField\",\n    \"type\": [\"string\", \"null\"]\n  }],\n  \"classType\": \"event\"\n}",
    "tenantId": "10",
    "type": "EVENT",
    "version": 1
  }
]
```

## Get application event family maps

Returns all application event family maps for the specified application. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to request this information.

- **URL**  
/kaaAdmin/rest/api/applicationEventMaps/{applicationId}

- **Method:**

GET

- **URL params**

Parameter	Value	Description
applicationId	string	the ID of the application

- **Data params**

None

- **Success response:**

- **Code: 200**

- **Example:**

```
[
  {
    "applicationId": "71",
    "createdTime": 1408705246676,
    "createdUsername": "devuser",
    "ecfId": "31",
    "ecfName": "Device Event Class Family",
    "eventMaps": [
```



```

    {
      "action": "BOTH",
      "eventClassId": "67",
      "fqcn": "org.kaaproject.kaa.demo.smarthouse.device.DeviceInfoRequest",
      "id": "151"
    },
    {
      "action": "BOTH",
      "eventClassId": "160",
      "fqcn": "org.kaaproject.kaa.demo.smarthouse.device.DeviceInfoResponse",
      "id": "152"
    }
  ],
  "id": "131",
  "version": 1
},
{
  "applicationId": "71",
  "createdTime": 1408705246781,
  "createdUsername": "devuser",
  "ecfId": "32",
  "ecfName": "Thermo Event Class Family",
  "eventMaps": [
    {
      "action": "BOTH",
      "eventClassId": "161",
      "fqcn": "org.kaaproject.kaa.demo.smarthouse.thermo.ThermostatInfoRequest",
      "id": "153"
    },
    {
      "action": "BOTH",
      "eventClassId": "163",
      "fqcn": "org.kaaproject.kaa.demo.smarthouse.thermo.ThermostatInfoResponse",
      "id": "154"
    },
    {
      "action": "BOTH",
      "eventClassId": "164",
      "fqcn": "org.kaaproject.kaa.demo.smarthouse.thermo.ChangeDegreeRequest",
      "id": "155"
    }
  ],
  "id": "132",
  "version": 1
},
{
  "applicationId": "71",
  "createdTime": 1408705246909,
  "createdUsername": "devuser",
  "ecfId": "33",
  "ecfName": "Music Event Class Family",
  "eventMaps": [
    {
      "action": "BOTH",
      "eventClassId": "165",
      "fqcn": "org.kaaproject.kaa.demo.smarthouse.music.PlayListRequest",
      "id": "156"
    },
    {
      "action": "BOTH",
      "eventClassId": "167",
      "fqcn": "org.kaaproject.kaa.demo.smarthouse.music.PlayListResponse",
      "id": "157"
    },
    {
      "action": "BOTH",
      "eventClassId": "168",
      "fqcn": "org.kaaproject.kaa.demo.smarthouse.music.PlayRequest",
      "id": "158"
    }
  ],
  "id": "133",
  "version": 1
}

```

```

        "action": "BOTH",
        "eventClassId": "169",
        "fqcn": "org.kaaproject.kaa.demo.smarthouse.music.PauseRequest",
        "id": "159"
    },
    {
        "action": "BOTH",
        "eventClassId": "170",
        "fqcn": "org.kaaproject.kaa.demo.smarthouse.music.StopRequest",
        "id": "180"
    },
    {
        "action": "BOTH",
        "eventClassId": "171",
        "fqcn": "org.kaaproject.kaa.demo.smarthouse.music.PlaybackInfoRequest",
        "id": "181"
    },
    {
        "action": "BOTH",
        "eventClassId": "172",
        "fqcn": "org.kaaproject.kaa.demo.smarthouse.music.ChangeVolumeRequest",
        "id": "182"
    },
    {
        "action": "BOTH",
        "eventClassId": "173",
        "fqcn": "org.kaaproject.kaa.demo.smarthouse.music.SeekRequest",
        "id": "183"
    },
    {
        "action": "BOTH",
        "eventClassId": "176",
        "fqcn": "org.kaaproject.kaa.demo.smarthouse.music.PlaybackInfoResponse",
        "id": "184"
    }
],
"id": "133",
"version": 1
}
]

```

- **Error response:**

Status codes	Description
400 Bad Request	applicationId parameter is empty
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application does not match the Tenant ID of the authenticated user
404 Not Found	Application with the specified applicationId does not exist
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u devuser:devuser123 -X GET "http://localhost:8080/kaaAdmin/rest/api/applicationEventMaps/71" | python -mjson.tool
```

```
[
  {
    "applicationId": "71",
```

```

    "createdTime": 1408705246676,
    "createdUsername": "devuser",
    "ecfId": "31",
    "ecfName": "Device Event Class Family",
    "eventMaps": [
      {
        "action": "BOTH",
        "eventClassId": "67",
        "fqcn": "org.kaaproject.kaa.demo.smarthouse.device.DeviceInfoRequest",
        "id": "151"
      },
      {
        "action": "BOTH",
        "eventClassId": "160",
        "fqcn": "org.kaaproject.kaa.demo.smarthouse.device.DeviceInfoResponse",
        "id": "152"
      }
    ],
    "id": "131",
    "version": 1
  },
  {
    "applicationId": "71",
    "createdTime": 1408705246781,
    "createdUsername": "devuser",
    "ecfId": "32",
    "ecfName": "Thermo Event Class Family",
    "eventMaps": [
      {
        "action": "BOTH",
        "eventClassId": "161",
        "fqcn": "org.kaaproject.kaa.demo.smarthouse.thermo.ThermostatInfoRequest",
        "id": "153"
      },
      {
        "action": "BOTH",
        "eventClassId": "163",
        "fqcn": "org.kaaproject.kaa.demo.smarthouse.thermo.ThermostatInfoResponse",
        "id": "154"
      },
      {
        "action": "BOTH",
        "eventClassId": "164",
        "fqcn": "org.kaaproject.kaa.demo.smarthouse.thermo.ChangeDegreeRequest",
        "id": "155"
      }
    ],
    "id": "132",
    "version": 1
  },
  {
    "applicationId": "71",
    "createdTime": 1408705246909,
    "createdUsername": "devuser",
    "ecfId": "33",
    "ecfName": "Music Event Class Family",
    "eventMaps": [
      {
        "action": "BOTH",
        "eventClassId": "165",
        "fqcn": "org.kaaproject.kaa.demo.smarthouse.music.PlayListRequest",
        "id": "156"
      },
      {
        "action": "BOTH",
        "eventClassId": "167",
        "fqcn": "org.kaaproject.kaa.demo.smarthouse.music.PlayListResponse",
        "id": "157"
      },
      {
        "action": "BOTH",

```

```

        "eventClassId": "168",
        "fqcn": "org.kaaproject.kaa.demo.smarthouse.music.PlayRequest",
        "id": "158"
    },
    {
        "action": "BOTH",
        "eventClassId": "169",
        "fqcn": "org.kaaproject.kaa.demo.smarthouse.music.PauseRequest",
        "id": "159"
    },
    {
        "action": "BOTH",
        "eventClassId": "170",
        "fqcn": "org.kaaproject.kaa.demo.smarthouse.music.StopRequest",
        "id": "180"
    },
    {
        "action": "BOTH",
        "eventClassId": "171",
        "fqcn": "org.kaaproject.kaa.demo.smarthouse.music.PlaybackInfoRequest",
        "id": "181"
    },
    {
        "action": "BOTH",
        "eventClassId": "172",
        "fqcn": "org.kaaproject.kaa.demo.smarthouse.music.ChangeVolumeRequest",
        "id": "182"
    },
    {
        "action": "BOTH",
        "eventClassId": "173",
        "fqcn": "org.kaaproject.kaa.demo.smarthouse.music.SeekRequest",
        "id": "183"
    },
    {
        "action": "BOTH",
        "eventClassId": "176",
        "fqcn": "org.kaaproject.kaa.demo.smarthouse.music.PlaybackInfoResponse",
        "id": "184"
    }
],
    "id": "133",
    "version": 1
}
]

```

## Get application event family map

Returns an application event family map by application event family map ID. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to request this information.

- **URL**  
/kaaAdmin/rest/api/applicationEventMap/{applicationEventFamilyMapId}

• **Method:**  
GET

- **URL params**

Parameter	Value	Description
applicationEventFamilyMapId	string	the ID of the application event family map

- **Data params**

None

- **Success response:**

- **Code: 200**
  - **Example:**

```
{
  "applicationId": "71",
  "createdTime": 1408705246676,
  "createdUsername": "devuser",
  "ecfId": "31",
  "ecfName": "Device Event Class Family",
  "eventMaps": [
    {
      "action": "BOTH",
      "eventClassId": "67",
      "fqcn": "org.kaaproject.kaa.demo.smarthouse.device.DeviceInfoRequest",
      "id": "151"
    },
    {
      "action": "BOTH",
      "eventClassId": "160",
      "fqcn": "org.kaaproject.kaa.demo.smarthouse.device.DeviceInfoResponse",
      "id": "152"
    }
  ],
  "id": "131",
  "version": 1
}
```

- **Error response:**

Status codes	Description
400 Bad Request	applicationEventFamilyMapId parameter is empty
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application associated with the application event family map does not match the Tenant ID of the authenticated user
404 Not Found	Application event family map with the specified applicationEventFamilyMapId does not exist
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u devuser:devuser123 -X GET "http://localhost:8080/kaaAdmin/rest/api/applicationEventMap/131" | python -mjson.tool
```

```
{
  "applicationId": "71",
  "createdTime": 1408705246676,
  "createdUsername": "devuser",
  "ecfId": "31",
  "ecfName": "Device Event Class Family",
  "eventMaps": [
    {
      "action": "BOTH",
      "eventClassId": "67",
      "fqcn": "org.kaaproject.kaa.demo.smarthouse.device.DeviceInfoRequest",
      "id": "151"
    },
    {
      "action": "BOTH",
      "eventClassId": "160",
      "fqcn": "org.kaaproject.kaa.demo.smarthouse.device.DeviceInfoResponse",
      "id": "152"
    }
  ],
  "id": "131",
  "version": 1
}
```

```

    {
      "action": "BOTH",
      "eventClassId": "160",
      "fqcn": "org.kaaproject.kaa.demo.smarthouse.device.DeviceInfoResponse",
      "id": "152"
    }
  ],
  "id": "131",
  "version": 1
}

```

## Create/Edit application event family map

Creates or edits an application event family map. If an application event family map with the specified ID does not exist, it will be created. If an application event family map with the specified ID exists, it will be updated. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to perform this operation.

- **URL**  
/kaaAdmin/rest/api/applicationEventMap

- **Method:**  
POST

- **URL params**  
None

- **Data params**

### Example:

```

{"applicationId": "71", "ecfId": "34", "ecfName": "Test Event Class Family", "eventMaps": [{"action": "BOTH", "eventClassId": "177", "fqcn": "org.kaaproject.kaa.test.family.MyTestRequest"}, {"action": "BOTH", "eventClassId": "178", "fqcn": "org.kaaproject.kaa.test.family.MyTestResponse"}]}

```

- **Success response:**

- **Code:** 200
  - **Example:**

```

{
  "applicationId": "71",
  "createdTime": 1409145316401,
  "createdUsername": "devuser",
  "ecfId": "34",
  "ecfName": "Test Event Class Family",
  "eventMaps": [
    {
      "action": "BOTH",
      "eventClassId": "177",
      "fqcn": "org.kaaproject.kaa.test.family.MyTestRequest",
      "id": "185"
    },
    {
      "action": "BOTH",
      "eventClassId": "178",
      "fqcn": "org.kaaproject.kaa.test.family.MyTestResponse",
      "id": "186"
    }
  ],
  "id": "134",
  "version": 0
}

```

- **Error response:**

Status codes	Description
--------------	-------------

401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application associated with the application event family map does not match the Tenant ID of the authenticated user
404 Not Found	Application event family map to be edited with the specified applicationEventFamilyMapId does not exist
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u devuser:devuser123 -X POST -H 'Content-Type: application/json' -d '{"applicationId": "71", "ecfId": "34", "ecfName": "Test Event Class Family", "eventMaps": [{"action": "BOTH", "eventClassId": "177", "fqcn": "org.kaaproject.kaa.test.family.MyTestRequest"}, {"action": "BOTH", "eventClassId": "178", "fqcn": "org.kaaproject.kaa.test.family.MyTestResponse"}]}' "http://localhost:8080/kaaAdmin/rest/api/applicationEventMap" | python -mjson.tool
```

```
{
  "applicationId": "71",
  "createdTime": 1409145316401,
  "createdUsername": "devuser",
  "ecfId": "34",
  "ecfName": "Test Event Class Family",
  "eventMaps": [
    {
      "action": "BOTH",
      "eventClassId": "177",
      "fqcn": "org.kaaproject.kaa.test.family.MyTestRequest",
      "id": "185"
    },
    {
      "action": "BOTH",
      "eventClassId": "178",
      "fqcn": "org.kaaproject.kaa.test.family.MyTestResponse",
      "id": "186"
    }
  ],
  "id": "134",
  "version": 0
}
```

## Get vacant event class families

Returns all vacant (not being used by application event family maps) event class families for the specified application. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to request this information.

- **URL**  
/kaaAdmin/rest/api/vacantEventClassFamilies/{applicationId}

- **Method:**  
GET

- **URL params**

Parameter	Value	Description
applicationId	string	the ID of the application.

- **Data params**

None

- **Success response:**

- **Code:** 200
  - **Example:**

```
[
  {
    "ecfId": "30",
    "ecfName": "Player Event Class Family",
    "version": 1
  },
  {
    "ecfId": "34",
    "ecfName": "Test Event Class Family",
    "version": 1
  }
]
```

- **Error response:**

Status codes	Description
400 Bad Request	applicationId parameter is empty
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application does not match the Tenant ID of the authenticated user
404 Not Found	Application with the specified applicationId does not exist
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u devuser:devuser123 -X GET "http://localhost:8080/kaaAdmin/rest/api/vacantEventClassFamilies/71" | python -mjson.tool
```

```
[
  {
    "ecfId": "30",
    "ecfName": "Player Event Class Family",
    "version": 1
  },
  {
    "ecfId": "34",
    "ecfName": "Test Event Class Family",
    "version": 1
  }
]
```

## Get application event class families

Returns all event class families for the specified application (being used by application event family maps). Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to request this information.

- **URL**  
/kaaAdmin/rest/api/eventClassFamilies/{applicationId}
- **Method:**  
GET
- **URL params**



Parameter	Value	Description
applicationId	string	the ID of the application.

- **Data params**

None

- **Success response:**

- **Code: 200**

- **Example:**

```
[
  {
    "aefMapId": "131",
    "ecfId": "31",
    "ecfName": "Device Event Class Family",
    "version": 1
  },
  {
    "aefMapId": "132",
    "ecfId": "32",
    "ecfName": "Thermo Event Class Family",
    "version": 1
  },
  {
    "aefMapId": "133",
    "ecfId": "33",
    "ecfName": "Music Event Class Family",
    "version": 1
  },
  {
    "aefMapId": "134",
    "ecfId": "34",
    "ecfName": "Test Event Class Family",
    "version": 0
  }
]
```

- **Error response:**

Status codes	Description
400 Bad Request	applicationId parameter is empty
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application does not match the Tenant ID of the authenticated user
404 Not Found	Application with the specified applicationId does not exist
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u devuser:devuser123 -X GET "http://localhost:8080/kaaAdmin/rest/api/eventClassFamilies/71" | python -mjson.tool
```

```
[
  {
```

```

    "aefMapId": "131",
    "ecfId": "31",
    "ecfName": "Device Event Class Family",
    "version": 1
  },
  {
    "aefMapId": "132",
    "ecfId": "32",
    "ecfName": "Thermo Event Class Family",
    "version": 1
  },
  {
    "aefMapId": "133",
    "ecfId": "33",
    "ecfName": "Music Event Class Family",
    "version": 1
  },
  {
    "aefMapId": "134",
    "ecfId": "34",
    "ecfName": "Test Event Class Family",
    "version": 0
  }
]

```

## Logging

### Get log schemas

Returns all log schemas for the specified application. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to request this information. The Tenant ID value of the application must match Tenant ID of the request submitter.

- **URL**  
/kaaAdmin/rest/api/logSchemas/{applicationId}

- **Method:**  
GET

- **URL params**

Parameter	Value	Description
applicationId	string	the ID of the application.

- **Data params**

None

- **Success response:**

- **Code: 200**
  - **Example:**

```

[
  {
    "applicationId": "71",
    "createdTime": 1408705246583,
    "createdUsername": "admin",
    "description": null,
    "endpointCount": 0,
    "id": "95",
    "majorVersion": 1,
    "minorVersion": 0,
    "name": "Generated",
    "schema": "{\r\n  \"type\": \"record\", \r\n  \"name\": \"LogData\", \r\n  \"namespace\": \"org.kaa.config\", \r\n  \"fields\": [\r\n    {\r\n

```

```

name\": \|\"level\", \|r\n               \|\"type\": {\r\n                                \|\"type\": \|\"enum\", \|
\r\n               \|\"name\": \|\"Level\", \|r\n                                \|\"symbols\":
[\r\n               \|\"DEBUG\", \|r\n                                \|\"ERROR\", \|
\r\n               \|\"FATAL\", \|r\n                                \|\"INFO\", \|
\r\n               \|\"TRACE\", \|r\n                                \|\"WARN\" \|
\r\n               ]\r\n                                }, \|r\n
{\r\n               \|\"name\": \|\"tag\", \|r\n               \|\"type\": \|\"string\"
}, \|r\n               {\r\n               \|\"name\": \|\"message\",
\r\n               \|\"type\": \|\"string\"\r\n               }\r\n               }\r\n
]

```

- **Error response:**

Status codes	Description
400 Bad Request	applicationId parameter is empty
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application does not match the Tenant ID of the authenticated user
404 Not Found	Application with the specified applicationId does not exist
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```

curl -v -S -u devuser:devuser123 -X GET "http://localhost:8080/kaaAdmin/rest/api/logSchemas/71" |
python -mjson.tool

```

```

[
  {
    "applicationId": "71",
    "createdTime": 1408705246583,
    "createdUsername": "admin",
    "description": null,
    "endpointCount": 0,
    "id": "95",
    "majorVersion": 1,
    "minorVersion": 0,
    "name": "Generated",
    "schema": "{\r\n \|\"type\": \|\"record\", \|r\n \|\"name\": \|\"LogData\", \|r\n \|
namespace\": \|\"org.kaa.config\", \|r\n \|\"fields\": [{\r\n \|\"type\": \|\"enum\", \|
name\": \|\"level\", \|r\n \|\"type\": {\r\n \|\"type\": \|\"enum\", \|
\r\n \|\"name\": \|\"Level\", \|r\n \|\"symbols\":
[\r\n \|\"DEBUG\", \|r\n \|\"ERROR\", \|
\r\n \|\"FATAL\", \|r\n \|\"INFO\", \|
\r\n \|\"TRACE\", \|r\n \|\"WARN\" \|
\r\n \| } \|r\n \| } \|r\n \| } \|r\n \|
\r\n \|\"type\": \|\"string\"\r\n \| } \|r\n \|
name\": \|\"message\", \|r\n \|\"type\": \|\"string\"\r\n \| } \|r\n \| } \|r\n \| } \|
}
]

```

## Get log schema

Returns a log schema by log schema ID. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to request this information.

- **URL**

```

/kaaAdmin/rest/api/logSchema/{logSchemaId}

```

- **Method:**

GET

- **URL params**

Parameter	Value	Description
logSchemald	string	the ID of the log schema

- **Data params**

None

- **Success response:**

- **Code: 200**

- **Example:**

```
{
  "applicationId": "71",
  "createdTime": 1408705246583,
  "createdUsername": "admin",
  "description": null,
  "endpointCount": 0,
  "id": "95",
  "majorVersion": 1,
  "minorVersion": 0,
  "name": "Generated",
  "schema": "{\r\n  \"type\": \"record\", \r\n  \"name\": \"LogData\", \r\n  \"namespace\": \"org.kaa.config\", \r\n  \"fields\": [\r\n    {\r\n      \"name\": \"level\", \r\n      \"type\": \"enum\", \r\n      \"symbols\": [\r\n        \"DEBUG\", \r\n        \"ERROR\", \r\n        \"FATAL\", \r\n        \"INFO\", \r\n        \"TRACE\", \r\n        \"WARN\" \r\n      ], \r\n      \"name\": \"tag\", \r\n      \"type\": \"string\" \r\n    }, \r\n    {\r\n      \"name\": \"message\", \r\n      \"type\": \"string\" \r\n    } \r\n  ]\r\n}"
```

- **Error response:**

Status codes	Description
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application associated with the log schema does not match the Tenant ID of the authenticated user
404 Not Found	Log schema with the specified logSchemald does not exist
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u devuser:devuser123 -X GET "http://localhost:8080/kaaAdmin/rest/api/logSchema/95" | python -mjson.tool
```

```
{
  "applicationId": "71",
  "createdTime": 1408705246583,
  "createdUsername": "admin",
```

```

    "description": null,
    "endpointCount": 0,
    "id": "95",
    "majorVersion": 1,
    "minorVersion": 0,
    "name": "Generated",
    "schema": "{\r\n  \r\n  \"type\": \"record\", \r\n  \r\n  \"name\": \"LogData\", \r\n  \r\n  \"namespace\": \"org.kaa.config\", \r\n  \r\n  \"fields\": [\r\n  \r\n    {\r\n  \r\n      \"name\": \"level\", \r\n  \r\n      \"type\": {\r\n  \r\n        \"type\": \"enum\", \r\n  \r\n        \"name\": \"Level\", \r\n  \r\n        \"symbols\": [\r\n  \r\n          \"DEBUG\", \r\n  \r\n          \"ERROR\", \r\n  \r\n          \"FATAL\", \r\n  \r\n          \"INFO\", \r\n  \r\n          \"TRACE\", \r\n  \r\n          \"WARN\" \r\n  \r\n        ] \r\n  \r\n      } \r\n  \r\n    }, \r\n  \r\n    {\r\n  \r\n      \"name\": \"tag\", \r\n  \r\n      \"type\": \"string\" \r\n  \r\n    }, \r\n  \r\n    {\r\n  \r\n      \"name\": \"message\", \r\n  \r\n      \"type\": \"string\" \r\n  \r\n    } \r\n  \r\n  ] \r\n}"
  }

```

## Get log schema by application token and schema version

Returns a log schema for the specified schema version and application token. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to request this information.

- **URL**  
/kaaAdmin/rest/api/logSchema/{applicationToken}/{schemaVersion}
- **Method:**  
GET
- **URL params**

Parameter	Value	Description
applicationToken	string	token of the application for the requested log schema
schemaVersion	string	version of the requested log schema

- **Data params**  
None
- **Success response:**
  - **Code: 200**
  - **Example:**

```

{
  "applicationId": "71",
  "createdTime": 1408705246583,
  "createdUsername": "admin",
  "description": null,
  "endpointCount": 0,
  "id": "95",
  "majorVersion": 1,
  "minorVersion": 0,
  "name": "Generated",
  "schema": "{\r\n  \r\n  \"type\": \"record\", \r\n  \r\n  \"name\": \"LogData\", \r\n  \r\n  \"namespace\": \"org.kaa.config\", \r\n  \r\n  \"fields\": [\r\n  \r\n    {\r\n  \r\n      \"name\": \"level\", \r\n  \r\n      \"type\": {\r\n  \r\n        \"type\": \"enum\", \r\n  \r\n        \"name\": \"Level\", \r\n  \r\n        \"symbols\": [\r\n  \r\n          \"DEBUG\", \r\n  \r\n          \"ERROR\", \r\n  \r\n          \"FATAL\", \r\n  \r\n          \"INFO\", \r\n  \r\n          \"TRACE\", \r\n  \r\n          \"WARN\" \r\n  \r\n        ] \r\n  \r\n      } \r\n  \r\n    }, \r\n  \r\n    {\r\n  \r\n      \"name\": \"tag\", \r\n  \r\n      \"type\": \"string\" \r\n  \r\n    }, \r\n  \r\n    {\r\n  \r\n      \"name\": \"message\", \r\n  \r\n      \"type\": \"string\" \r\n  \r\n    } \r\n  \r\n  ] \r\n}"
}

```

- **Error response:**

Status codes	Description
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application associated with the log schema does not match the Tenant ID of the authenticated user
404 Not Found	Application with the specified application token does not exist or application does not have log schema with the specified schema version
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u devuser:devuser123 -X GET "http://localhost:8080/kaaAdmin/rest/api/logSchema/114785424389877/1" | python -mjson.tool
```

```
{
  "applicationId": "71",
  "createdTime": 1408705246583,
  "createdUsername": "admin",
  "description": null,
  "endpointCount": 0,
  "id": "95",
  "majorVersion": 1,
  "minorVersion": 0,
  "name": "Generated",
  "schema": "{\r\n  \"type\": \"record\",\r\n  \"name\": \"LogData\",\r\n  \"namespace\": \"org.kaa.config\",\r\n  \"fields\": [\r\n    {\r\n      \"name\": \"level\",\r\n      \"type\": {\r\n        \"type\": \"enum\",\r\n        \"symbols\": [\r\n          \"DEBUG\",\r\n          \"ERROR\",\r\n          \"INFO\",\r\n          \"TRACE\",\r\n          \"WARN\"\r\n        ]\r\n      }\r\n    },\r\n    {\r\n      \"name\": \"tag\",\r\n      \"type\": \"string\"\r\n    },\r\n    {\r\n      \"name\": \"message\",\r\n      \"type\": \"string\"\r\n    }\r\n  ]\r\n}"
```

## Create log schema

Uploads a log schema. A unique version number will be generated (incrementally) for this schema, and the reateUsername field of the schema will be set to the name of the user who has uploaded it. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to perform this operation.

- **URL**

/kaaAdmin/rest/api/logSchema

- **Method:**

POST

- **URL params**

None

- **Data params**

Multipart/form-data encoding. Fields:

**Example:**

```
{"applicationId": "71", "name": "Test log schema", "description": "Log Schema Description"}
```

**File contents example:**

```
{
  "type": "record",
  "name": "TestLogData",
  "namespace": "org.kaa.config.test",
  "fields": [
    {
      "name": "level",
      "type": {
        "type": "enum",
        "name": "Level",
        "symbols": [
          "DEBUG",
          "ERROR",
          "FATAL",
          "INFO",
          "TRACE",
          "WARN"
        ]
      }
    },
    {
      "name": "tag",
      "type": "string"
    },
    {
      "name": "message",
      "type": "string"
    }
  ]
}
```

• **Success response:**

• **Code: 200**

• **Example:**

```
{
  "applicationId": "71",
  "createdTime": 1408707762378,
  "createdUsername": "devuser",
  "description": "Log Schema Description",
  "endpointCount": 0,
  "id": "98",
  "majorVersion": 2,
  "minorVersion": 0,
  "name": "Test log schema",
  "schema": "{\n  \"type\": \"record\", \n  \"name\": \"TestLogData\", \n  \"\n  namespace\": \"org.kaa.config.test\", \n  \"fields\": [\n    {\n      \"name\": \"level\", \n      \"type\": {\n        \"type\": \"enum\", \n        \"name\": \"Level\", \n        \"symbols\": [\n          \"DEBUG\", \n          \"ERROR\", \n          \"FATAL\", \n          \"INFO\", \n          \"TRACE\", \n          \"WARN\" \n        ] \n      }, \n      \"name\": \"tag\", \n      \"type\": \"string\" \n    }, \n    {\n      \"name\": \"message\", \n      \"type\": \"string\" \n    } \n  ] \n}"
```

• **Error response:**

Status codes	Description
400 Bad	Specified log schema is not a valid avro schema

Request	
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application associated with the log schema does not match the Tenant ID of the authenticated user
404 Not Found	File with a schema not found in the form data
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u devuser:devuser123 -F'logSchema={"applicationId":"71","name":"Test log schema","description":"Log Schema Description"};type=application/json' -F file=@log_schema.json "http://localhost:8080/kaaAdmin/rest/api/logSchema" | python -mjson.tool
```

```
{
  "applicationId": "71",
  "createdTime": 1408707762378,
  "createdUsername": "devuser",
  "description": "Log Schema Description",
  "endpointCount": 0,
  "id": "98",
  "majorVersion": 2,
  "minorVersion": 0,
  "name": "Test log schema",
  "schema": "{\n  \"type\": \"record\", \n  \"name\": \"TestLogData\", \n  \"namespace\": \"org.kaa.config.test\", \n  \"fields\": [\n    {\n      \"name\": \"level\", \n      \"type\": {\n        \"type\": \"enum\", \n        \"symbols\": [\n          \"DEBUG\", \n          \"ERROR\", \n          \"FATAL\", \n          \"INFO\", \n          \"TRACE\", \n          \"WARN\" \n        ], \n        \"name\": \"tag\", \n        \"type\": \"string\" \n      }, \n      \"name\": \"message\", \n      \"type\": \"string\" \n    } \n  ]\n}"
```

## Get log appenders

Returns all log appenders for the specified application. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to request this information.

- **URL**  
/kaaAdmin/rest/api/logAppenders/{applicationId}

- **Method:**  
GET

- **URL params**

Parameter	Value	Description
applicationId	string	the ID of the application.

- **Data params**

None

- **Success response:**

- **Code:** 200
  - **Example:**



```
[
  {
    "appenderClassName": "org.kaaproject.kaa.server.appenders.file.appender.
FileSystemLogAppender",
    "applicationId": "70",
    "applicationToken": "517279666821995",
    "configuration": "{\publicKey\":"DFGFDGD43FGGDFJKKJLFD34535DFDFGD\","logsRootPath\":"
/kaa_log_uploads\","rollingFileNamePatern\":"logFile.%d{yyyy-MM-dd}.
log\","rollingMaxHistory\":"30\","triggerMaxFileSize\":"1GB\","encoderPattern\":"%-4
relative [%thread] %-5level %logger{35} - %msg%n}",
    "createdTime": 1418313672013,
    "createdUsername": "devuser",
    "description": "Sample file system log appender",
    "headerStructure": [
      "KEYHASH",
      "TIMESTAMP"
    ],
    "id": "160",
    "maxLogSchemaVersion": 2147483647,
    "minLogSchemaVersion": 1,
    "name": "File system appender",
    "status": "REGISTERED",
    "tenantId": "10",
    "typeName": "File"
  }
]
```

- **Error response:**

Status codes	Description
400 Bad Request	applicationId parameter is empty
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application does not match the Tenant ID of the authenticated user
404 Not Found	Application with the specified applicationId does not exist
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u devuser:devuser123 -X GET "http://localhost:8080/kaaAdmin/rest/api/logAppenders/70" |
python -mjson.tool
```

```
[
  {
    "appenderClassName": "org.kaaproject.kaa.server.appenders.file.appender.
FileSystemLogAppender",
    "applicationId": "70",
    "applicationToken": "517279666821995",
    "configuration": "{\publicKey\":"DFGFDGD43FGGDFJKKJLFD34535DFDFGD\","logsRootPath\":"
/kaa_log_uploads\","rollingFileNamePatern\":"logFile.%d{yyyy-MM-dd}.log\","rollingMaxHistory\":"
30\","triggerMaxFileSize\":"1GB\","encoderPattern\":"%-4relative [%thread] %-5level %logger{35}
- %msg%n}",
    "createdTime": 1418313672013,
    "createdUsername": "devuser",
    "description": "Sample file system log appender",
    "headerStructure": [
      "KEYHASH",
      "TIMESTAMP"
    ],
  }
]
```

```

    "id": "160",
    "maxLogSchemaVersion": 2147483647,
    "minLogSchemaVersion": 1,
    "name": "File system appender",
    "status": "REGISTERED",
    "tenantId": "10",
    "typeName": "File"
  }
]

```

## Get log appender

Returns a log appender by log appender ID. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to request this information.

- **URL**  
/kaaAdmin/rest/api/logAppender/{logAppenderId}

- **Method:**

GET

- **URL params**

Parameter	Value	Description
logAppenderId	string	the ID of the log appender

- **Data params**

None

- **Success response:**

- **Code: 200**
  - **Example:**

```

{
  "appenderClassName": "org.kaaproject.kaa.server.appenders.file.appender.
FileSystemLogAppender",
  "applicationId": "70",
  "applicationToken": "517279666821995",
  "configuration": "{ \"publicKey\": \"DFGFDGD43FGGDFJKKJLFD34535DFDFGD\", \"logsRootPath\":
\"/kaa_log_uploads\", \"rollingFileNamePatern\": \"logFile.%d{yyyy-MM-dd}.log\", \"
rollingMaxHistory\": 30, \"triggerMaxFileSize\": \"1GB\", \"encoderPattern\": \"%-4relative [%
thread] %-5level %logger{35} - %msg%n\" }",
  "createdTime": 1418313672013,
  "createdUsername": "devuser",
  "description": "Sample file system log appender",
  "headerStructure": [
    "KEYHASH",
    "TIMESTAMP"
  ],
  "id": "160",
  "maxLogSchemaVersion": 2147483647,
  "minLogSchemaVersion": 1,
  "name": "File system appender",
  "status": "REGISTERED",
  "tenantId": "10",
  "typeName": "File"
}

```

- **Error response:**

Status codes	Description

400 Bad Request	logAppenderId parameter is empty
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application associated with the log appender does not match the Tenant ID of the authenticated user
404 Not Found	Log appender with the specified logAppenderId does not exist
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u devuser:devuser123 -X GET "http://localhost:8080/kaaAdmin/rest/api/logAppender/160" |
python -mjson.tool
```

```
{
  "appenderClassName": "org.kaaproject.kaa.server.appenders.file.appender.FileSystemLogAppender",
  "applicationId": "70",
  "applicationToken": "517279666821995",
  "configuration": "{\"publicKey\": \"DFGFDGD43FGGDFJJKJLFD34535DFDFGD\", \"logsRootPath\": \""
/kaa_log_uploads\", \"rollingFileNamePatern\": \"logFile.%d{yyyy-MM-dd}.log\", \"rollingMaxHistory\":
30, \"triggerMaxFileSize\": \"1GB\", \"encoderPattern\": \"%-4relative [%thread] %-5level %logger{35}
- %msg%n\"}",
  "createdTime": 1418313672013,
  "createdUsername": "devuser",
  "description": "Sample file system log appender",
  "headerStructure": [
    "KEYHASH",
    "TIMESTAMP"
  ],
  "id": "160",
  "maxLogSchemaVersion": 2147483647,
  "minLogSchemaVersion": 1,
  "name": "File system appender",
  "status": "REGISTERED",
  "tenantId": "10",
  "typeName": "File"
}
```

## Create/Edit log appender

Creates or edits a log appender. If a log appender with the specified ID does not exist, it will be created. If a log appender with the specified ID exists, it will be updated. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to perform this operation.

- **URL**  
/kaaAdmin/rest/api/logAppender

- **Method:**  
POST

- **URL params**  
None

- **Data params**

**Example:**

```
{ "appenderClassName": "org.kaaproject.kaa.server.appenders.file.appender.FileSystemLogAppender",
  "applicationId": "70", "applicationToken": "946558468095768", "configuration": "{\"publicKey\": \""
XXXXXXXXXXXXXXXXXXXXXXXXXXXX\", \"logsRootPath\": \"" /kaa_log_uploads_new\", \"rollingFileNamePatern\": \""
logFile.%d{yyyy-MM-dd}.log\", \"rollingMaxHistory\": 30, \"triggerMaxFileSize\": \"1GB\", \""
encoderPattern\": \"%-4relative [%thread] %-5level %logger{35} - %msg%n\"}", "description": "New
```

```
sample file system log appender", "headerStructure": [ "KEYHASH", "TIMESTAMP" ], "name": "New file
system appender", "maxLogSchemaVersion": 2147483647, "minLogSchemaVersion": 1, "status":
"REGISTERED", "tenantId": "10", "typeName": "File"}
```

- **Success response:**

- **Code:** 200
- **Example:**

```
{
  "appenderClassName": "org.kaaproject.kaa.server.appenders.file.appender.
FileSystemLogAppender",
  "applicationId": "70",
  "applicationToken": "517279666821995",
  "configuration": "{\\"publicKey\\":\\"XXXXXXXXXXXXXXXXXXXXXXXXXXXX\\",\\"logsRootPath\\":\\"
/kaa_log_uploads_new\\",\\"rollingFileNamePatern\\":\\"logFile.%d{yyyy-MM-dd}.log\\",\\"
rollingMaxHistory\\":30,\\"triggerMaxFileSize\\":\\"1GB\\",\\"encoderPattern\\":\\"%-4relative [%
thread] %-5level %logger{35} - %msg%n\\"}",
  "createdTime": 1418313982809,
  "createdUsername": "devuser",
  "description": "New sample file system log appender",
  "headerStructure": [
    "KEYHASH",
    "TIMESTAMP"
  ],
  "id": "161",
  "maxLogSchemaVersion": 2147483647,
  "minLogSchemaVersion": 1,
  "name": "New file system appender",
  "status": "REGISTERED",
  "tenantId": "10",
  "typeName": "File"
}
```

- **Error response:**

Status codes	Description
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application associated with the log appender does not match the Tenant ID of the authenticated user
404 Not Found	Log appender to be edited with the specified logAppenderId does not exist
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```
curl -v -S -u devuser:devuser123 -X POST -H 'Content-Type: application/json' -d{"appenderClassName":
"org.kaaproject.kaa.server.appenders.file.appender.FileSystemLogAppender", "applicationId": "70",
"applicationToken": "946558468095768", "configuration": "{\\"publicKey\\":\\"
XXXXXXXXXXXXXXXXXXXXXXXXXXXX\\",\\"logsRootPath\\":\\"/kaa_log_uploads_new\\",\\"rollingFileNamePatern\\":\\"
logFile.%d{yyyy-MM-dd}.log\\",\\"rollingMaxHistory\\":30,\\"triggerMaxFileSize\\":\\"1GB\\",\\"
encoderPattern\\":\\"%-4relative [%thread] %-5level %logger{35} - %msg%n\\"}", "description": "New
sample file system log appender", "headerStructure": [ "KEYHASH", "TIMESTAMP" ], "name": "New file
system appender", "maxLogSchemaVersion": 2147483647, "minLogSchemaVersion": 1, "status":
"REGISTERED", "tenantId": "10", "typeName": "File"}' "http://localhost:8080/kaaAdmin/rest/api
/logAppender" | python -mjson.tool
```

```
{
  "appenderClassName": "org.kaaproject.kaa.server.appenders.file.appender.FileSystemLogAppender",
  "applicationId": "70",
  "applicationToken": "517279666821995",
```

```

    "configuration": "{ \"publicKey\": \"XXXXXXXXXXXXXXXXXXXXXXXXXXXX\", \"logsRootPath\": \"
/kaa_log_uploads_new\", \"rollingFileNamePattern\": \"logFile.%d{yyyy-MM-dd}.log\", \"
rollingMaxHistory\": 30, \"triggerMaxFileSize\": \"1GB\", \"encoderPattern\": \"%-4relative [%thread] %
-5level %logger{35} - %msg%n\"",
    "createdTime": 1418313982809,
    "createdUsername": "devuser",
    "description": "New sample file system log appender",
    "headerStructure": [
        "KEYHASH",
        "TIMESTAMP"
    ],
    "id": "161",
    "maxLogSchemaVersion": 2147483647,
    "minLogSchemaVersion": 1,
    "name": "New file system appender",
    "status": "REGISTERED",
    "tenantId": "10",
    "typeName": "File"
}

```

## Delete log appender

Deletes a log appender by log appender ID. Only users with the TENANT\_DEVELOPER or TENANT\_USER role are allowed to perform this operation.

- **URL**  
/kaaAdmin/rest/api/delLogAppender?logAppenderId

- **Method:**  
POST

- **URL params**

Parameter	Value	Description
logAppenderId	string	the ID of the log appender to be deleted

- **Data params**

None

- **Success response:**

- **Code:** 200

- **Error response:**

Status codes	Description
400 Bad Request	logAppenderId parameter is empty
401 Unauthorized	User is not authenticated or invalid credentials provided
403 Forbidden	Authenticated user does not have the required role (TENANT_DEVELOPER or TENANT_USER) or the Tenant ID of the application associated with the log appender does not match the Tenant ID of the authenticated user
404 Not Found	Log appender with the specified logAppenderId does not exist
500 Internal Server Error	Unexpected error occurred on the server side

- **Sample call:**

```

curl -v -S -u devuser:devuser123 -X POST "http://localhost:8080/kaaAdmin/rest/api/delLogAppender?logAppenderId=161" | python -mjson.tool

```

